



11 Lewis Drive

Paola, KS 66071

Oil & Gas Well Drilling
Water Wells
Geo-Loop Installation

Phone: 913-557-9083

Fax: 913-557-9084

WELL LOG

Verde Oil Company

Campbell #95-95

API #15-001-31,146

August 27 - August 28, 2014

<u>Thickness of Strata</u>	<u>Formation</u>	<u>Total</u>
6	soil & clay	6
13	broken lime	19
43	lime	62
4	shale	66
2	lime	68
17	shale	85
20	lime	105
3	shale	108
54	lime	162 base of the Kansas City
98	shale	260
8	lime	268
29	shale	297
3	lime	300
12	shale	312
1	lime	313
5	shale	318
3	lime	321
3	shale	324
8	lime	332
22	shale	354
3	lime	357
46	shale	403
2	lime	405
15	shale	420
2	lime	422
7	shale	429
20	lime	449
25	shale	474
2	lime	476
13	shale	489
6	lime	495
2	shale	497
8	lime	505
11	shale	516
4	lime	520
7	shale	527
1	lime	528
39	shale	567
1	lime	568

42	shale	610
1	lime	611
92	shale	703
6	silty shale	709
17	shale	726
4	broken sand	730 black laminated sand, ok bleeding
2	silty shale	732
6	broken sand	738 brown & grey, laminated sand, no show
1	coal	739
65	shale	804
6	broken sand	810 hard light brown sand, no show
9	shale	819
24	oil sand	843 brown good bleeding, soft
4	oil sand	847 dark brown & grey sand, good bleeding
1	shale	848
31	sand	879 black & grey
4	shale	883
3	broken sand	886 hard grey sand with shale, no show
1	coal	887
22	shale	909 Mississippi, TD

Drilled a 9 7/8" hole to 21.7'

Drilled a 5 5/8" hole to 909'

Set 21.7' of 7" surface casing, cemented with 5 sacks cement.

Set 893' of 2 7/8" 8 round upset tubing with 4 centralizers, 1 float shoe, 1 clamp, 1 baffle, 1 seating nipple