

Oil & Gas Well Drilling Water Wells Geo-Loop Installation

Phone: 913-557-9083

Fax: 913-557-9084

WELL LOG

Paola, KS 66071

Verde Oil Company Campbell # 95-115 API #15-001-31,150

September 5 - September 9, 2014

Thickness of Strata	Formation	<u>Total</u>
8	soil & clay	8
56	limestone	64
3	shale	67
2	lime	69
18	shale	87
77	lime	164
136	shale	300
3	lime	303
17	shale	320
2	lime	322
3	shale	325
10	lime	335
87	shale	422
3	lime	425
5	shale	430
14	lime	444 brown
2	shale	446
6	lime	452
4	shale	456
1	lime	457
40	shale	497
15	lime	512
9	shale	521
2	lime	523
204	shale	727
8	brown sand	735 oil show
5	sand	740 black
59	shale	799
12	brown sand	811 no show
12	shale	823
9	oil sand	832
2	shale	834
21	oil sand	855 brown
5	oil sand	860 grey, bleeding oil
16	black sand	876
38	shale	914
1	lime	915 Mississippian, TD

Campbell # 95-115

Drilled a 9 7/8" hole to 23.6' Drilled a 5 5/8" hole to 915'

Set 23.6' of 7" surface casing, cemented with 5 sacks cement.

Set 911' of used 2 7/8" 8 round upset tubing including 1 seating nipple, 1 float shoe, 1 clamp, and 1' cement pup joint.