



11 Lewis Drive

Paola, KS 66071

Oil & Gas Well Drilling
Water Wells
Geo-Loop Installation

Phone: 913-557-9083

Fax: 913-557-9084

WELL LOG

Verde Oil Company

Campbell # I-95-125

API #15-001-31,153

September 9 - September 10, 2014

<u>Thickness of Strata</u>	<u>Formation</u>	<u>Total</u>
6	soil & clay	6
55	limestone	61
3	shale	64
3	lime	67
18	shale	85
77	lime	162
96	shale	258
3	lime	261
36	shale	297
3	lime	300
17	shale	317
16	lime	333
21	shale	354
2	lime	356
64	shale	420
3	lime	423
7	shale	430
21	lime	451
4	shale	455
1	lime	456
36	shale	492
19	lime	511
7	shale	518
6	lime	524
15	shale	539
2	lime	541
69	shale	610
1	lime	611
176	shale	787
2	broken sand	789 brown sand & grey shale oil show
24	shale	813
11	broken sand	824 brown sand, grey shale no show
15	oil sand	839 brown
6	shale	845
5	sand	850 grey with oil
6	silty shale	856 grey no show
3	silty shale	859

6	black sand	865
43	shale	908
1	lime	909 Mississippian, TD

Drilled a 9 7/8" hole to 23.7'

Drilled a 5 5/8" hole to 909'

Set 23.7' of 7" surface casing, cemented with 5 sacks cement.

Set 896.4' of used 2 7/8" 8 round upset tubing including, 4 centralizers, 1 float shoe, 1 clam, 1 cement pup joint.