



11 Lewis Drive

Paola, KS 66071

**Oil & Gas Well Drilling
Water Wells
Geo-Loop Installation**

Phone: 913-557-9083

Fax: 913-557-9084

WELL LOG

SCZ Resources, LLC

Baker #SCZ-26

API #15-121-30,484

August 7 - August 8, 2014

<u>Thickness of Strata</u>	<u>Formation</u>	<u>Total</u>
14	soil/clay	14
5	shale	19
17	lime	36
29	shale	65
6	lime	71
43	shale	114
10	lime	124
10	shale	134
32	lime	166
12	shale	178
24	lime	202
2	shale	204
6	lime	210 base of the Kansas City
109	shale	319
7	broken sand	326 30% brown sand 70% shale ok bleeding
22	shale	348
1	broken sand	349 40% brown sand 60% shale
10	oil sand	359 very soft brown sand good bleeding
2	lime	361
4	oil sand	365 black sand good bleeding thin shale laminations
4	broken sand	369 90% soft black sand 10% shale laminations
3	limey sand	372 30% white limey sand 70% hard black sand good bleeding
3	broken sand	375 60% black sand 40% shale ok bleeding
1	lime/shale	376
15	lime	391
29	shale	420 TD

Drilled a 9 7/8" hole to 20.6'

Drilled a 5 5/8" hole to 420'

Set 20.6' of 7" threaded and coupled surface casing, cemented with 4 sacks cement.

Set 411' of 2 7/8" 8 round upset tubing with 2 centralizers, 1 float shoe, 1 clamp, and 1 seating nipple..

Seating nipple set at 349'.