

TREATMENT REPORT

Acid 8	& Cement							Acid Stage No		····		
					Type Treatment:	Amt.	Type Fluid	Sand Size	Pounds	s of Sand		
Date 11/21/2014 District F.O. No. 42281					Bkdown		.,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,		, , , , , ,			
	K&N PETROLU		•		***************************************							
Well Name	& No. NORMA	N KLEPPER #1										
Location			Field									
County	BARTON		State KS		Flush							
					Treated from		ft. to		No. ft.	0		
Casing:	Size 8 5/8	Type & Wt.		Set atft.	from	······································			No. ft.	0		
Formation: Perf. to					from		ft. to	ít,	No. ft,	0		
Formation: Perf. to					Actual Volume of 0	Oil / Water to Load Hol				8bl./Gal.		
Formation: Perf. to										- Paris Paris Maria Maria		
Liner: Si					Pump Trucks.	No. Used: Std.	318 Sp.		Twin			
(Cemented:	Perforated from	om		t. Auxiliary Equipment 327							
				ft.		DON JOE AND SC		**************************************				
	Perforated fr	om	ft. to	ft.	Auxiliary Tools							
					Plugging or Sealing Materials: Type							
Open Hole Size T.D. ft.			ft. P.	8. toft.				Gals.		lb.		
Company I	Representative		ED		Treater		BRAND	ON				
TIME	PRES	SURES	Total Fluid Pumped			REMARKS						
a.m./p.m.	Tubing	Casing							***************************************			
4:30				ON LOCATION						:		
	/					 						
			***	HOLE-367'								
				PIPE-357'			······································		 			
				LJ-10'								
				DISP-22 BBL								
				MIX 350 SKS 60/40 2% GEL 3% CAL CHLORIDE 6BPM 400#								
				DISPLACE W/ 22								
				CIRCULATED CEMENT TO SURFACE								
								·····				
										····		
				THANKS								
				BRANDON			······································					
										·		

					·····	w						
						····		···				



TREATMENT REPORT

ACIG &	: Cement								Acid Stage No			
					Type Treatment:	Amt,		Type Fluid	Sand Size	Poun	ds of Sand	
Date 11/27/2014 District F.O. No. 42285				Bkdown		Bbl./Gal.						
Company K&N PETROLEUM								· · · · · · · · · · · · · · · · · · ·				
Well Name & No. NORMAN KLEPPER#1					İ	,	Bbi./Gai.					
Location Field							Bbl./Gal.		·			
County BARTON State KS					Flush		Bbl./Gal					
					Treated from					No. ft.	0	
Casing:	Size 5 1/2	Type & Wt.		Set atft.	from		ft	. to	ft.	No. ft.	0	
Formation:			Perf.	to	from		f1	. to	ft.	No. ft.	0	
				Actual Volume of Oil / Water to Load Hole: Bbl./Gal.								
Formation:			Perf.									
				Bottom atft.	Pump Trucks.	No, Used:	Std.	318 Sp.		Twin		
			rom		Auxiliary Equipme				360-310			
			Swung at	***************************************	t. Personnel BRANDON NATHAN JOE AND SCOTT							
_			ft. to		Auxiliary Tools							
					Plugging or Sealir	g Materials						
Open Hole	Size	T.D.	ft. P.	B. to ft.	E .				Gals		lb.	
					1							
Company F	lepresentative		ED		Treater			BRA	INDON			
TIME		SURES	1									
a.m./p.m.	Tubing	Casing	Total Fluid Pumped				REMAR	KS				
8:30				ON LOCATION			······································					
0,30				HOLE-3476'								
				PIPE-3472'								
							·					
	BAFFLE-3457'											
		DISPLACEMENT-84.35										
	BASKET-2,4 CENTRILIZER-1,3,6,8,11											
		BREAK CIRCULATION AND CIRCULATE FOR 1 HR W/ MUD PUMP										
				<u> </u>	IP MUD FLUSH G RAT HOLE W/ 30 SKS 60/40 2%							
	PUMP 25 SKS 60/40 2% AND 200 SKS 60/40 2% GEL 12% SALT 3/4% C-47A							C-47A				
				3/4% C41P AND								
		DISPLACED PLUG 6BPM 800#. PLUG LANDED AT 1200# AND PRESSURED UP							URED UP			
4:45				TO 1500# AND	ND RELEASE. PLUG HELD.						······	
			<u> </u>									
				THANKS								
				BRANDON								
	1											
						·····						
	<u> </u>											
						·····			*****	·		
-												
	-				,		··········			,		
-	<u> </u>	-	_	1	···							
		 										
	 											
			1									