

Skyy Drilling, L.L.C.
11551 Ash Street, Suite # 205
Leawood, Kansas 66211
Office (913) 499-8373
Fax (913) 766-1310

June 29, 2015

Company: Haas Petroleum, LLC
11551 Ash Street, # 205
Leawood, Kansas 66211

Lease: East Lidikay – Well # 40 I HP
County: Franklin
Spot: S2 NE SE SE of Sec 4, Twp 16, R 21 E
API: 15-059-26966-00-00
Spud: June 15, 2015
TD: 760'

6/15/15: Set 20' of 7" – Cemented with 5 sacks
6/17/15: Drilled from 20' to 760' TD. Ran 751' of 2 7/8 casing
6/17/15: Cemented with 100 sacks



PO Box 884, Chanute, KS 66720
620-431-9210 or 800-467-8676

FIELD TICKET & TREATMENT REPORT

CEMENT

TICKET NUMBER 51043

LOCATION Oxtawa KS

FOREMAN Fred Mader

DATE	CUSTOMER #	WELL NAME & NUMBER	SECTION	TOWNSHIP	RANGE	COUNTY
6-17-15	3451	E Lidikay 40 I H R	SE 4	16	21	FR
CUSTOMER						
Haas Petroleum LLC						
MAILING ADDRESS						
21551 Ash St. Ste 205						
CITY		STATE	ZIP CODE			
Leawood		KS	66211			

JOB TYPE <u>Long string</u>	HOLE SIZE <u>5 7/8</u>	HOLE DEPTH <u>760</u>	CASING SIZE & WEIGHT <u>2 7/8 EUE</u>
CASING DEPTH <u>7530</u>	DRILL PIPE	TUBING	OTHER
SLURRY WEIGHT	SLURRY VOL	WATER gal/sk	CEMENT LEFT in CASING <u>2 1/2" Plug</u>
DISPLACEMENT <u>4.38 BB</u>	DISPLACEMENT PSI	MIX PSI	RATE <u>4 BPM</u>

REMARKS: Hold Safety meeting. Establish circulation. Mix & Pump 100# Gel Flush. Mix & Pump 100 SKS Poz Blend I/A Cement & 2% Gel Cement to Surface. Flush pump & lines clean. Displace 2 1/2" Rubber Plug to Casing TD. Pressure to 800# PSI. Monitor Pressure for 30 min MIT. Release pressure to set float valve. Shut in Casing.

Skyy Drilling

Fred Maden

[illegible]

Revin 3737

AUTHORIZTION

TITLE

DATE _____

I acknowledge that the payment terms, unless specifically amended in writing on the front of the form or in the customer's account records, at our office, and conditions of service on the back of this form are in effect for services identified on this form.