ROBERT STOLZLE
PETROLEUM GEOLOGIST
SUITE 375
WICHITA, KANSAS

Recommended Completion Procedure:

Perforate	4360'-4365'	5	4 JSPF
Perforate	4350'-4355'	5	4 JSPF
Perforate	4340'-4345'	5	4 JSPF
Perforate	4330'-4335'	5	4 JSPF
Perforate	4320'-4325'	5	4 JSPF
Perforate	4310'-4315'	5	4 JSPF
Perforate	4300'-4305'	5	4 JSPF
Perforate	4290'-4295'	5	4 JSPF
Perforate	4280'-4285'	5	4 JSPF
Perforate	4270'-4275'	5	4 JSPF
Perforate	4260'-4265'	5	4 JSPF
Perforate	4250'-4255'	5	4 JSPF
Perforate	4240'-4245'	5	4 JSPF
Perforate	4230'-4235'	5	4 JSPF
Perforate	4220'-4225'	5	4 JSPF
Perforate	4210'-4215'	5	4 JSPF
Perforate	4200'-4205'	5	4 JSPF
Perforate	4190'-4195'	5	4 JSPF
Perforate	4180'-4185'	5	4 JSPF
Perforate	4170'-4175'	5	4 JSPF
Perforate	4160'-4165'	5	4 JSPF
Perforate	4150'-4155'	5	4 JSPF
Perforate	4140'-4145'	5	4 JSPF
Perforate	4130'-4135'	5	4 JSPF
Perforate	4120'-4125'	5	4 JSPF
Perforate	4110'-4115'	5	4 JSPF
Perforate	4100'-4105'	5	4 JSPF
Perforate	4090'-4095'	5	4 JSPF
Perforate	4080'-4085'	5	4 JSPF
Perforate	4070'-4075'	5	4 JSPF
Perforate	4060'-4065'	5	4 JSPF
Perforate	4050'-4055'	5	4 JSPF
Perforate	4040'-4045'	5	4 JSPF
Perforate	4030'-4035'	5	4 JSPF
Perforate	4020'-4025'	5	4 JSPF
Perforate	4010'-4015'	5	4 JSPF
Perforate	4000'-4005'	5	4 JSPF
Perforate	3990'-3995'	5	4 JSPF
Perforate	3980'-3985'	5	4 JSPF
Perforate	3970'-3975'	5	4 JSPF
Perforate	3960'-3965'	5	4 JSPF
Perforate	3950'-3955'	5	4 JSPF
Perforate	3940'-3945'	5	4 JSPF
Perforate	3930'-3935'	5	4 JSPF
Perforate	3920'-3925'	5	4 JSPF
Perforate	3910'-3915'	5	4 JSPF
Perforate	3900'-3905'	5	4 JSPF
Perforate	3890'-3895'	5	4 JSPF
Perforate	3880'-3885'	5	4 JSPF
Perforate	3870'-3875'	5	4 JSPF
Perforate	3860'-3865'	5	4 JSPF
Perforate	3850'-3855'	5	4 JSPF
Perforate	3840'-3845'	5	4 JSPF
Perforate	3830'-3835'	5	4 JSPF
Perforate	3820'-3825'	5	4 JSPF
Perforate	3810'-3815'	5	4 JSPF
Perforate	3800'-3805'	5	4 JSPF
Perforate	3790'-3795'	5	4 JSPF
Perforate	3780'-3785'	5	4 JSPF
Perforate	3770'-3775'	5	4 JSPF
Perforate	3760'-3765'	5	4 JSPF
Perforate	3750'-3755'	5	4 JSPF
Perforate	3740'-3745'	5	4 JSPF
Perforate	3730'-3735'	5	4 JSPF
Perforate	3720'-3725'	5	4 JSPF
Perforate	3710'-3715'	5	4 JSPF
Perforate	3700'-3705'	5	4 JSPF
Perforate	3690'-3695'	5	4 JSPF
Perforate	3680'-3685'	5	4 JSPF
Perforate	3670'-3675'	5	4 JSPF
Perforate	3660'-3665'	5	4 JSPF
Perforate	3650'-3655'	5	4 JSPF
Perforate	3640'-3645'	5	4 JSPF
Perforate	3630'-3635'	5	4 JSPF
Perforate	3620'-3625'	5	4 JSPF
Perforate	3610'-3615'	5	4 JSPF
Perforate	3600'-3605'	5	4 JSPF
Perforate	3590'-3595'	5	4 JSPF
Perforate	3580'-3585'	5	4 JSPF
Perforate	3570'-3575'	5	4 JSPF
Perforate	3560'-3565'	5	4 JSPF
Perforate	3550'-3555'	5	4 JSPF
Perforate	3540'-3545'	5	4 JSPF
Perforate	3530'-3535'	5	4 JSPF
Perforate	3520'-3525'	5	4 JSPF
Perforate	3510'-3515'	5	4 JSPF
Perforate	3500'-3505'	5	4 JSPF

Recommended Completion Procedure:

Perforate	4360'-4365'	5	4 JSPF
Perforate	4350'-4355'	5	4 JSPF
Perforate	4340'-4345'	5	4 JSPF
Perforate	4330'-4335'	5	4 JSPF
Perforate	4320'-4325'	5	4 JSPF
Perforate	4310'-4315'	5	4 JSPF
Perforate	4300'-4305'	5	4 JSPF
Perforate	4290'-4295'	5	4 JSPF
Perforate	4280'-4285'	5	4 JSPF
Perforate	4270'-4275'	5	4 JSPF
Perforate	4260'-4265'	5	4 JSPF
Perforate	4250'-4255'	5	4 JSPF
Perforate	4240'-4245'	5	4 JSPF
Perforate	4230'-4235'	5	4 JSPF
Perforate	4220'-4225'	5	4 JSPF
Perforate	4210'-4215'	5	4 JSPF
Perforate	4200'-4205'	5	4 JSPF
Perforate	4190'-4195'	5	4 JSPF
Perforate	4180'-4185'	5	4 JSPF
Perforate	4170'-4175'	5	4 JSPF
Perforate	4160'-4165'	5	4 JSPF
Perforate	4150'-4155'	5	4 JSPF
Perforate	4140'-4145'	5	4 JSPF
Perforate	4130'-4135'	5	4 JSPF
Perforate	4120'-4125'	5	4 JSPF
Perforate	4110'-4115'	5	4 JSPF
Perforate	4100'-4105'	5	4 JSPF
Perforate	4090'-4095'	5	4 JSPF
Perforate	4080'-4085'	5	4 JSPF
Perforate	4070'-4075'	5	4 JSPF
Perforate	4060'-4065'	5	4 JSPF
Perforate	4050'-4055'	5	4 JSPF
Perforate	4040'-4045'	5	4 JSPF
Perforate	4030'-4035'	5	4 JSPF
Perforate	4020'-4025'	5	4 JSPF
Perforate	4010'-4015'	5	4 JSPF
Perforate	4000'-4005'	5	4 JSPF
Perforate	3990'-3995'	5	4 JSPF
Perforate	3980'-3985'	5	4 JSPF
Perforate	3970'-3975'	5	4 JSPF
Perforate	3960'-3965'	5	4 JSPF
Perforate	3950'-3955'	5	4 JSPF
Perforate	3940'-3945'	5	4 JSPF
Perforate	3930'-3935'	5	4 JSPF
Perforate	3920'-3925'	5	4 JSPF
Perforate	3910'-3915'	5	4 JSPF
Perforate	3900'-3905'	5	4 JSPF
Perforate	3890'-3895'	5	4 JSPF
Perforate	3880'-3885'	5	4 JSPF
Perforate	3870'-3875'	5	4 JSPF
Perforate	3860'-3865'	5	4 JSPF
Perforate	3850'-3855'	5	4 JSPF
Perforate	3840'-3845'	5	4 JSPF
Perforate	3830'-3835'	5	4 JSPF
Perforate	3820'-3825'	5	4 JSPF
Perforate	3810'-3815'	5	4 JSPF
Perforate	3800'-3805'	5	4 JSPF
Perforate	3790'-3795'	5	4 JSPF
Perforate	3780'-3785'	5	4 JSPF
Perforate	3770'-3775'	5	4 JSPF
Perforate	3760'-3765'	5	4 JSPF
Perforate	3750'-3755'	5	4 JSPF
Perforate	3740'-3745'	5	4 JSPF
Perforate	3730'-3735'	5	4 JSPF
Perforate	3720'-3725'	5	4 JSPF
Perforate	3710'-3715'	5	4 JSPF
Perforate	3700'-3705'	5	4 JSPF
Perforate	3690'-3695'	5	4 JSPF
Perforate	3680'-3685'	5	4 JSPF
Perforate	3670'-3675'	5	4 JSPF
Perforate	3660'-3665'	5	4 JSPF
Perforate	3650'-3655'	5	4 JSPF
Perforate	3640'-3645'	5	4 JSPF
Perforate	3630'-3635'	5	4 JSPF
Perforate	3620'-3625'	5	4 JSPF
Perforate	3610'-3615'	5	4 JSPF
Perforate	3600'-3605'	5	4 JSPF
Perforate	3590'-3595'	5	4 JSPF
Perforate	3580'-3585'	5	4 JSPF
Perforate	3570'-3575'	5	4 JSPF
Perforate	3560'-3565'	5	4 JSPF
Perforate	3550'-3555'	5	4 JSPF
Perforate	3540'-3545'	5	4 JSPF
Perforate	3530'-3535'	5	4 JSPF
Perforate	3520'-3525'	5	4 JSPF
Perforate	3510'-3515'	5	4 JSPF
Perforate	3500'-3505'	5	4 JSPF

DST # 1 ZONE: Cherokee Sandstone
INTERVAL: 4096'-4102'

Pressures:	Time	Press.	RECOVERY
1. Initial Hydrostatic		1944	Gas to surface.
2. Initial Flow: Start	0	936	10' Clean oil.
3. Initial Shut-in: End	30	983	Stabilized at:
4. Initial Shut-in: End	60	1002	8 MINUTES
5. Final Flow: Start	0	948	12 BBLS oil/min.
6. Final Flow: End	30	992	Est. Final Rate
7. Final Shut-in: End	60	1008	20 BPH
8. Final Hydrostatic		1922	

Diff.: 1178
Re:

DST # 2 ZONE: Conglomerate Sandstone
INTERVAL: 4206'-4212'

Pressures:	Time	Press.	RECOVERY
1. Initial Hydrostatic		2062	695' Muddy oil
2. Initial Flow: Start	0	23	And Oil cut mud
3. Initial Flow: End	30	49	Rec. 150' Mud with
4. Initial Shut-in: End	60	1896	Gas cut Mud
5. Final Flow: Start	0	92	(Water, no Show)
6. Final Flow: End	45	71	60' Gassy oil
7. Final Shut-in: End	90	1893	(80% oil)
8. Final Hydrostatic		1977	35' Muddy gas

Diff.: 1185
Re:

DST # 3 ZONE: Miss. Dpsy, Chat, Kinderhook Ss.
INTERVAL: 4115'-4140'

Pressures:	Time	Press.	RECOVERY
1. Initial Hydrostatic		1984	240' Heavy Mud
2. Initial Flow: Start	0	20	Slight show of oil
3. Initial Flow: End	30	76	Slight Show Gas
4. Initial Shut-in: End	60	83	1/2" Bottle Rate
5. Final Flow: Start	0	15	Mud Cut Oil Trace
6. Final Flow: End	45	27	1/4" Bottle Rate
7. Final Shut-in: End	90	81	Est. Additional
8. Final Hydrostatic		1946	

Diff.: 1115
Re:

DST # 4 ZONE: Mississippi Lime
INTERVAL: 4147'-4195'

Pressures:	Time	Press.	RECOVERY
1. Initial Hydrostatic		1935	300' Gas in pipe
2. Initial Flow: Start	0	21	80' Gassy Oil Cut
3. Initial Flow: End	30	32	Mud Cut Oil Trace
4. Initial Shut-in: End	60	106	Slight Show Gas
5. Final Flow: Start	0	38	Slight Show Oil
6. Final Flow: End	30	49	1/2" Bottle Rate
7. Final Shut-in: End	60	610	Est. Additional
8. Final Hydrostatic		1974	Est. 800' Clean

Diff.: 1125
Re:

DST # 1 ZONE: Cherokee Sandstone
Interval: 4096'-4102'
Chart Depth: 4049'

DST # 2 ZONE: Conglomerate Sandstone
Interval: 4206'-4212'
Chart Depth: 4087'



DST # 3 ZONE: Miss. Dpsy, Chat, Kinderhook Ss.
Interval: 4115'-40'
Chart Depth: 4118'

DST # 4 ZONE: Mississippi Lime
Interval: 4147'-95'
Chart Depth: 4155'

ABBREVIATIONS USED

ROCK TYPES:
Ls = Limestone
Dol = Dolomite
Ss = Sandstone
Sh = Shale
Cht = Chert
Coal = Coal
Bent = Bentonite

COLOR:
Bk = Black
Gy = Gray
Wh = White
Br = Brown
Gn = Green
Red = Red
Tan = Tan

HARDNESS:
Fri = Friable
Mod = Moderately soft
Hd = Hard
Vhd = Very hard

TEXTURE:
Xln = Crystalline
Vf = Very fine
Fn = Fine
Med = Medium
Crs = Coarse
Vc = Very coarse
Sil = Siliceous
Arg = Argillaceous
Calc = Calcareous
Sdy = Sandy
Glau = Glauconitic
Pyr = Pyritic
Carb = Carbonaceous
Fos = Fossiliferous
Ool = Oolitic
Cht = Chert
Bent = Bentonite
Anhy = Anhydrite
Gyp = Gypsum
Salt = Salt
Dol = Dolomite
Ls = Limestone

POROSITY:
Tt = Tight
Pr = Poor
Mod = Mod. Porosity
Gd = Good
Ex = Excellent
Vug = Vuggy
Mv = Moldic Vug
Fr = Fracture
Ch = Chalky
Pp = Pinpoint
Ip = Intergranular
Oo = Oomoldic
Sl = Slight
Mod = Moderate
Hvy = Heavy

OIL SHOW:
○ Wash Oil Show
○ Fair Oil Show
○ Good Oil Show
○ Excellent Oil Show

ROCK DESCRIPTIONS:
Rock of Mississippian in Hooker Gas Field
K.B. = 3,934'GR

"Marker" at 3,930'

Mississippian Lime
Ls, gy, vf-xln, sl. sil, sl. arg, sl. calc, sl. sdy, sl. fos, sl. oo, sl. cht, sl. pp por, sl. vug por, sl. fr por, sl. ch por, sl. gd stn, sl. gd cut, sl. gd fluor, sl. gd odor, sl. gd show oil, sl. gd free oil, sl. gd gas, sl. gd gas in mud, sl. gd gas in pipe, sl. gd gas in pipe, sl. gd gas in pipe