

Miami County, KS
 Well:Gerken I-4
 Lease Owner:Triple T

Town Oilfield Service, Inc.
 (913) 837-8400

Commenced Spudding:
 10/22/2015

WELL LOG

Thickness of Strata	Formation	Total Depth
0-9	Soil-Clay	9
29	Lime	38
12	Shale	50
19	Lime	69
4	Shale	73
2	Lime	75
4	Shale	79
7	Lime	86
4	Shale	90
2	Lime	92
15	Shale	107
13	Sand	120
45	Sandy Shale	165
89	Shale	254
4	Lime	258
35	Shale	293
5	Lime	298
21	Shale	319
9	Lime	328
12	Shale	340
4	Lime	344
4	Shale	348
7	Sand	355
30	Lime	385
5	Shale	390
3	Lime	393
59	Shale	452
3	Sandy Shale	455
3	Broken Sand	458
9	Sandy Shale	467
3	Sand & Sandy Shale	469
5	Shale	474
5	Sand	479
12	Shale	491
1	Coal	492
3	Lime	495
65	Shale	560-TD

Log Book

Well No. I-4

Farm Corken

KS Miami
(State) (County)

29 18 24
(Section) (Township) (Range)

For Triple T Oil
(Well Owner)

Town Oilfield Services, Inc.

1207 N. 1st East
Louisburg, KS 66053
913-710-5400

Thickness of Strata	Formation	Total Depth	Remarks
0-9	Soil-clay	9	
29	Lime	38	
12	Shale	50	
19	Lime	69	
4	Shale	73	
2	Lime	75	
4	Shale	79	
7	Lime	86	H-stha
4	Shale	90	
2	Lime	92	
15	Shale	107	
13	sand	120	slight show
45	sandy shale	165	
89	Shale	254	
4	Lime	258	
35	Shale	293	
5	Lime	298	
21	Shale	319	
9	Lime	328	
12	Shale	340	
4	Lime	344	
4	Shale	348	
7	sand	355	no Oil
30	Lime	385	
5	Shale	390	
3	Lime	393	
59	Shale	452	



PO Box 884, Chanute, KS 66720
820-431-9210 or 800-457-8676

4619
4529

TICKET NUMBER 49868

LOCATION Ottawa, KS

FOREMAN Fred Maden

**FIELD TICKET & TREATMENT REPORT
CEMENT**

DATE	CUSTOMER #	WELL NAME & NUMBER	SECTION	TOWNSHIP	RANGE	COUNTY
10-23-15	7966	Garden # I-4	NE 29	18	24	MI
CUSTOMER			TRUCK #	DRIVER	TRUCK #	DRIVER
Total T Oil			712	Fred Maden		
MAILING ADDRESS			495	Har Bar		
P.O. Box 339			475	141 Dot		
CITY	STATE	ZIP CODE	548	Tro Har		
Louisburg	KS	66053				

JOB TYPE Longstring HOLE SIZE 5 7/8" HOLE DEPTH 560' CASING SIZE & WEIGHT 2 7/8 EUE
 CASING DEPTH 543' DRILL PIPE 5/8" Galv RUBING 515' OTHER _____
 SLURRY WEIGHT _____ SLURRY VOL _____ WATER gal/ek _____ CEMENT LEFT IN CASING 25' + Plug
 DISPLACEMENT 2.97 BBL DISPLACEMENT PSI _____ MIX PSI _____ RATE 4 BPM

REMARKS: Hold Safety meeting. Establish pump rate. Mix Pump 100%
Get Flush Mix + Pump 70 SKs Portland I A Cement 290 Gal
Cement to Surface. Flush pump + lines clean. Displace
2 1/2" Rubber plug to Baffle in casing. Pressure to 500 PSI.
Monitor pressure for 30 minute MIT. Release pressure
to set float valve. Shut in casing.

TOS Drilling - Wec.

Fred Maden

ACCOUNT CODE	QUANTITY or UNITS	DESCRIPTION of SERVICES or PRODUCT	UNIT PRICE	TOTAL
PE0450	1	PUMP CHARGE	495	1500.00
CE0002	-	MILEAGE	N/A	
CE0710	to minimum	Ten Miles	548	220.00
WE0853	1hr	80 BBL Var. Truck	675	100.00
		Sub Total		1820.00
		Less 46%		-837.20
				982.80
CC0440	70 BKS	Por Bland I. A Cement	945.00	
CC5965	218"	Bandmate Gel	65.40	
PP8126	1	2 1/2" Rubber Plug	45.00	
		Sub Total		1055.40
		Less 46%		-485.48
				569.92
		SALES TAX		45.39
		ESTIMATED TOTAL		1595.31
				(2939.83)

Revin 5757

AUTHORIZATION _____ TITLE _____ DATE _____

I acknowledge that the payment terms, unless specifically amended in writing on the front of the form or in the customer's account records, at our office, and conditions of service on the back of this form are in effect for services identified on this form.