

Miami County, KS
 Well: Gerken I-3
 Lease Owner: Triple T

Town Oilfield Service, Inc.
 (913) 837-8400

Commenced Spudding:
 10/29/2015

WELL LOG

Thickness of Strata	Formation	Total Depth
0-6	Soil-Clay	6
28	Lime	34
8	Shale	42
20	Lime	62
4	Shale	66
3	Lime	69
4	Shale	73
6	Lime	79
23	Shale	102
22	Sand	124
20	Sandy Shale	144
139	Shale	283
5	Lime	288
10	Shale	298
2	Lime	300
9	Shale	309
6	Lime	315
16	Shale	331
4	Lime	335
5	Shale	340
8	Sand	348
29	Lime	377
5	Shale	382
2	Lime	384
54	Shale	438
5	Sandy Shale	443
4	Sand	447
4	Sand	451
11	Sandy Shale	462
2	Sand	464
3	Shale	467
2	Sand	469
10	Shale	479
2	Coal	481
3	Lime	484
76	Shale	560-TD

Log Book

Well No. I-3

Farm Cresken

KS Miami
(State) (County)

29 18 24
(Section) (Township) (Range)

For Triple T Oil
(Well Owner)

**Town Oilfield
Services, Inc.**
1207 N. 1st East
Louisburg, KS 66053
913-710-5400

Thickness of Strata	Formation	Total Depth	Remarks
0-6	soil-clay	6	
28	Lime	34	
8	Shale	42	
20	Lime	62	
4	Shale	66	
3	Lime	69	
4	Shale	73	
6	Lime	79	Heathy
23	Shale	102	
22	sand	124	gas odor
20	sandy shale	144	
139	Shale	283	
5	Lime	288	
10	Shale	298	
2	Lime	300	
9	Shale	309	
6	Lime	315	
16	Shale	331	
4	Lime	335	
5	Shale	340	
8	Sand	348	no Oil
29	Lime	377	
5	Shale	382	
2	Lime	384	
54	Shale	438	
5	sandy shale	443	
4	sand	447	no Oil



CONSOLIDATED
Oil Well Services, LLC

44888 / 4594

TICKET NUMBER 49891

LOCATION Ottawa KS

FOREMAN Fred Maden

PO Box 884, Chanute, KS 66720
620-431-9210 or 800-467-8676

FIELD TICKET & TREATMENT REPORT
CEMENT

DATE	CUSTOMER #	WELL NAME & NUMBER	SECTION	TOWNSHIP	RANGE	COUNTY
10-30-15	7966	Gorken # I.3	NE 29	18	24	MI
CUSTOMER			TRUCK #			
Triple T - Oil			DRIVER			
MAILING ADDRESS			TRUCK #			
P.O. Box 339			DRIVER			
CITY			TRUCK #			
Louisburg			DRIVER			
STATE			TRUCK #			
KS			DRIVER			
ZIP CODE			TRUCK #			
66053			DRIVER			

JOB TYPE Longstring HOLE SIZE _____ HOLE DEPTH 560 CASING SIZE & WEIGHT 2 7/8 EUE
 CASING DEPTH 544' DRILL PIPE Baffle TUBING @ 5 1/2" OTHER _____
 SLURRY WEIGHT _____ SLURRY VOL _____ WATER gal/sk _____ CEMENT LEFT in CASING 30' x Plug
 DISPLACEMENT 3 BA DISPLACEMENT PSI _____ MIX PSI _____ CEMENT RATE 4 BPM

REMARKS: Hold Safety Meeting Establish Circulation. Mix Pump 100'
Get Flush. Mix & Pump 74 sks Por Blend I A Cement 270 Gal.
Cement to surface. Flush pump & line clean. Displace
2 1/2" Rubber plug to baffle in casing. Pressure to 600 PSI.
Monitor pressure for 30 minute M.I.T. Release pressure to
set float valve. Shut in Casing.

TOS Drilling (was)

Fred Maden

ACCOUNT CODE	QUANTITY or UNITS	DESCRIPTION of SERVICES or PRODUCT	UNIT PRICE	TOTAL
CA0450	1	PUMP CHARGE	495	1500 ⁰⁰
CE0002	-	MILEAGE		NIC
CE0711	1/3 Minimum	Ten Miles Delivery	545	220 ⁰⁰
WE0853	1 hr	60 BBL Vac Truck	475	100 ⁰⁰
		Sub Total		1820 ⁰⁰
		less 46%		- 837 ⁰⁰
				982 ⁰⁰
CC5840	74.5 SKS	Por Blend I A Cement		999 ⁰⁰
CC5965	224 ⁰⁰	Bentonite Gel		67 ⁰⁰
CP8176	1	2 1/2" Rubber Plug		45 ⁰⁰
		Sub Total		1111 ⁰⁰
		less 46%		- 511 ⁰⁰
				600 ⁰⁰
			8%	SALES TAX
				48 ⁰⁰

Revin 3737

AUTHORIZATION [Signature]

TITLE _____

DATE 3020.10

ESTIMATED TOTAL 1630⁰⁰

I acknowledge that the payment terms, unless specifically amended in writing on the front of the form or in the customer's account records, at our office, and conditions of service on the back of this form are in effect for services identified on this for