

JOB LOG

SWIFT Services, Inc.

DATE 2 MAR 16 PAGE NO. 1

CUSTOMER Hess O.T WELL NO. 42 LEASE June JOB TYPE Plug to Abandon TICKET NO. 28106

CHART NO.	TIME	RATE (BPM)	VOLUME (BBL) (GAL)	PUMPS		PRESSURE (PSI)		DESCRIPTION OF OPERATION AND MATERIALS
				T	C	TUBING	CASING	
								300sk 60/40 Pozmix (4% gel) 18 sk Bentonite gel 2 3/4 x 5 1/2
	1035							on loc TRX 11F
	1051		5					Pump 5 bbl H ₂ O - Blow on backside
		3 3/4						mix Bentonite gel 18 sk 18 sk gel
		3 3/4	5			400		catch pressure
		3 3/4	12			400		- Circ to surface -
		3 3/4	51			400		switch to count
		3 3/4	20			400		Mix 60/40 poz (4%) w/ hulls @ 13.1 ppq
		3 3/4	16			200		switch to flush 75 sk Kickout
	1132							pull tubing to 1685'
	1233	3 3/4				100		mix 60/40 pozmix (4%) @ 13.1 ppq
		3 3/4	5			100		- circ fluid to pit
		3 3/4	47			300		- cement to surface
	1250							pull tubing from hole {175 sk mixed}
	1345		1 1/2			300		pump down BACKSIDE (8F) holding 300psi 55 sk
			6					- Vertical rock to sec. top 86 5 1/2 255 sk
	1350							{5 1/2 standing full of cement} 280 sk total w: ket 18
	1425							wash truck Pack up job complete. Trucks Blaine, STANL, FLINT & PERSON