

SM Oil & Gas, Inc.
P. O. Box 189
Skiatook, Oklahoma 74070
620-725-3200

September 15, 2016

Kansas Corporation Commission
Conservation Division
266 N. Main Street – Suite #220
Wichita, Kansas 67202-1513


Re: Fulsom "B" #3 INJ
15-019-27540-00-00
Cement Usage ACO-1

To Whom It May Concern:

SM Oil & Gas, Inc. buys quantities of Portland Type I cement, which comes on pallets of 35 sacks per pallet, for the companies usage. In this case, the required 14 sacks of cement is mixed by our own drilling rig personnel and is used to properly install the surface casing.

An invoice showing the bulk quantity of cement is available if needed.

Thank you,



Thomas H. Oast
Area Manager

810 E 7TH
 PO Box 92
 EUREKA, KS 67045
 (620) 583-5561



Cement or Acid Field Report

Ticket No. 2793
 Foreman Russell mcgoy
 Camp Eureka

Date	Cust. ID #	Lease & Well Number	Section	Township	Range	County	State
6-3-16	1180	Folsom B 3 Injection				CO	KS
Customer			Safety Meeting	Unit #	Driver	Unit #	Driver
S M Oil + GAS INC.			Rm	104	ALAN		
Mailing Address			AIN	110	Russ		
P.O. Box 189			STEVE	113	Steve		
City			AB	140	AB		
State							
Zip Code							
OK							
74070							

Job Type LIS Hole Depth 2106 Slurry Vol. 80 Bbl Tubing _____
 Casing Depth 2103 Hole Size 6 3/4 Slurry Wt. 13.2 14 # Drill Pipe _____
 Casing Size & Wt. 4 1/2 Cement Left in Casing 33 Water Gal/SK _____ Other _____
 Displacement 32.6 Displacement PSI 2500 # Bump Plug to _____ BPM 4 BPM

Remarks: Safety meeting, Rig up TO 4 1/2 casing w/ Elite wash HEAD. wash down BS 4 1/2 w/ s m oil mud Pump. wash 15 min on Bottom to clean Hole @ approx 4 BPM. Rig up 4 1/2 cement HEAD. Pump 10 Bbl water, mix + Pump 10 SK's Gel w/ 1 SK Hull's Pump 5 Bbl spacer. mix + Pump 175 SK's 50/50 Light cement @ 13.1 # = 52 Bbl Slurry Tail w/ 100 SK's OWC w/ 1# Phenoseal @ 14 # = 28 Slurry wash out Pump + Liner's Release 4 1/2 Top Rubber Plug start Displacement @ 10 Bbl PSI was 700 # slow Pump Rate @ 20 Bbl IN to 3 BPM 1400 # 30 Bbl IN slow to 2 BPM 1000 # shot down at 32.6 Bbl 2500 # bleed back to 32 1/4 Bbl = 2080 FT Plug Depth. TOTAL Displacement should of been 32.6 Approx 30 FT of cement By water measurements THANKS Russ + crew 14 Bbl Slurry to Pit GOOD cement (TAG cement @ 2050' w/ Tubing) 6-6-15 (Company Rig)

Code	Qty or Units	Description of Product or Services	Unit Price	Total
C-102	1	Pump Charge	1050.00	1050.00
C-107	30	Mileage	3.95	118.50
C-204	175 SK	50/50 Pozmix cement	11.25	1968.75
C-206	900 #	Gel = 6%	.20	180.00
C-208	175 #	Phenoseal 1# per SK	1.25	218.75
C-202	100 SK	OWC cement	19.15	1915.00
C-208	100 #	Phenoseal = 1# per SK	1.25	125.00
C-206	500 #	Gel Flush	.20	100.00
C-214	40 #	cotton seed Hulls	.45	18.00
C-108A		Tow mileage Bulk Trucks x 2	M/L	690.00
C-114	2 hr	130 Bbl Transport	110.00	220.00
C-224	4,000	city water	10 / 1000	40.00
C-403	1	4 1/2 Top Rubber Plug	45.00	45.00
			5.6 Total	6,689.00
			Sales Tax	391.89
			Total	1080.89

Authorization _____

Title CO/owner

Total

I agree to the payment terms and conditions of services provided on the back of this job ticket. Any amendments to payment terms must be in writing on the front of this job ticket or in the Customer's records at ELITE's office.