

Oll & Gas Well Drilling Water Wells Geo-Loop Installation

Phone: 913-557-9083 Fax: 913-557-9084

Paola, KS 66071

WELL LOG

Tailwater, Inc.
Simon Brothers Farms #32-T
API #15-003-26,559
October 4 - October 5, 2016

Thickness of Strata	<u>Formation</u>	Total
8	soil & clay	8
6	gravel	14
41	shale	55
28	lime	83
67	shale	150
9	lime ,	400
5	shale	164
37	lime	
6	shale	207
24	lime	231
3	shale	234
24	lime	258 base of the Kansas City
178	shale 🛔 🛔	436
4	lime	440 🌲
5	shale 👢 🦂 🦠	445
6	lime i	▶451 oil show
18	shale ************************************	469
1	coal	470
2	shale	472
6	silty shale	478
3	oil sand	481 grey, light oil show
7	shale	488
6	oil sand	494 green, ok bleeding
8	silty shale	502
1	coal	503
2	shale	505
5	lime	510
41	shale	551
13	lime	564
18	shale	582 brown & green, light bleeding
3	lime	585
18	shale	603
2	coal	605
14	shale	619
20	broken sand	639 brown & grey, oil odor, gassy
8	oil sand	647 light brown, oil odor, gassy
6	oil sand	653 brown, light oil show
6	oil sand	659 black, oil odor
8	shale	667
Ğ	0.,010	~~.

6	silty shale	673
10	shale	683
1	coal	684
7	shale	691
4	broken sand	695 black & white, no bleeding
7	silty shale	702
1	coal	703
51	shale	754
3	sand	757 white, no oil
83	shale	840 TD

Drilled a 9 7/8" hole to 22.4' Drilled a 5 5/8" hole to 840'

Set 22.4' of 7" surface casing with 5 sacks of cement.

This well was plugged from 630'-580 with 10 sacks of cement, 275-225' with 10 sacks of cement, and from 175' to the top.