

## KANSAS CORPORATION COMMISSION OIL & GAS CONSERVATION DIVISION

1349305

Form CB-1 Oct 2016 Form must be Typed Form must be Signed All blanks must be Filled

## **CATHODIC PROTECTION BOREHOLE INTENT**

Must be approved by the KCC sixty (60) days prior to commencing well.

Forestad Could Date	
Expected Spud Date:	Spot Description:
, ,	
OPERATOR: License#	feet from N / S Line of Section
Name:	feet from E / W Line of Section
Address 1:	Is SECTION: Regular Irregular?
Address 2:	(Check directions from nearest outside corner boundries)
City:	County
Contact Person:	County:
Phone:	Facility Name:
	Borehole Number:
CONTRACTOR: License#	Ground Surface Elevation: MSI
Name:	Cathodic Borehole Total Depth:
Type Drilling Equipment:	Depth to Bedrock:
Air Rotary Other	Water Information
Construction Features	Aquifer Penetration: None Single Multiple
Length of Cathodic Surface (Non-Metallic) Casing	Depth to bottom of fresh water:
Planned to be set: feet	Depth to bottom of usable water:
Length of Conductor pipe (if any): feet	Water well within one-quarter mile: Yes No
Surface casing borehole size: inches	Public water supply well within one mile: Yes No
Cathodic surface casing size: inches	Water Source for Drilling Operations:
Cathodic surface casing centralizers set at depths of:;;	☐ Well ☐ Farm Pond ☐ Stream ☐ Other
;;;;;	Water Well Location:
Cathodic surface casing will terminate at:	DWR Permit #
Above surface Surface Vault Below Surface Vault	Standard Dimension Ratio (SDR) is =
Pitless casing adaptor will be used: Yes No Depth feet	(Cathodic surface csg. O.D. in inches / MWT in inches = SDR)
Anode installation depths are:;; ;; ;;	Annular space between borehole and casing will be grouted with:
7.110de ilistaliation deptilis are	☐ Concrete ☐ Neat Cement ☐ Bentonite Cement ☐ Bentonite Clay
;;;;;;	Anode vent pipe will be set at: feet above surface
	Anode conductor (backfill) material TYPE:
	Depth of BASE of Backfill installation material:
AFFIDAVIT	Depth of TOP of Backfill installation material:
The undersigned hereby affirms that the drilling, completion and eventual plugging	Borehole will be Pre-Plugged? Yes No
of this well will comply with K.S.A. 55-101 et. seq.	
is agreed that the following minimum requirements will be met:	
<ol> <li>Notify the appropriate District office prior to spudding and again before plugging the and placement is necessary prior to plugging. In all cases, notify District Office prior</li> </ol>	
Notify appropriate District Office 48 hours prior to workover or re-entry.	
Notify appropriate District Office 48 hours prior to workover or re-entry.  A copy of the approved notice of intent to drill shall be posted on each drilling rig.	to any grouting.
2. Notify appropriate District Office 48 hours prior to workover or re-entry. 3. A copy of the approved notice of intent to drill shall be posted on each drilling rig. 4. The minimum amount of cathodic surface casing as specified below shall be set by	r to any grouting.  grouting to the top when the cathodic surface casing is set.
<ul> <li>Notify appropriate District Office 48 hours prior to workover or re-entry.</li> <li>A copy of the approved notice of intent to drill shall be posted on each drilling rig.</li> <li>The minimum amount of cathodic surface casing as specified below shall be set by good to be approved in the prior of the prior o</li></ul>	grouting to the top when the cathodic surface casing is set.
<ol> <li>Notify appropriate District Office 48 hours prior to workover or re-entry.</li> <li>A copy of the approved notice of intent to drill shall be posted on each drilling rig.</li> <li>The minimum amount of cathodic surface casing as specified below shall be set by S. File all required forms: a. File Drill Pit Application (form CDP-1) with Intent to Drill (form CDP-1).</li> </ol>	grouting to the top when the cathodic surface casing is set.
<ol> <li>Notify appropriate District Office 48 hours prior to workover or re-entry.</li> <li>A copy of the approved notice of intent to drill shall be posted on each drilling rig.</li> <li>The minimum amount of cathodic surface casing as specified below shall be set by 5.</li> <li>File all required forms: a. File Drill Pit Application (form CDP-1) with Intent to Drill (fact (form KSONA-1) with Cathodic Protection Borehole Intent (CB-1) c. File Complete</li> </ol>	grouting to the top when the cathodic surface casing is set.
2. Notify appropriate District Office 48 hours prior to workover or re-entry. 3. A copy of the approved notice of intent to drill shall be posted on each drilling rig. 4. The minimum amount of cathodic surface casing as specified below shall be set by 5. 5. File all required forms: a. File Drill Pit Application (form CDP-1) with Intent to Drill (form KSONA-1) with Cathodic Protection Borehole Intent (CB-1) c. File Completed. 5. Submit plugging report (CP-4) within 60 days after final plugging is completed.	grouting to the top when the cathodic surface casing is set.
2. Notify appropriate District Office 48 hours prior to workover or re-entry. 3. A copy of the approved notice of intent to drill shall be posted on each drilling rig. 4. The minimum amount of cathodic surface casing as specified below shall be set by 5. 5. File all required forms: a. File Drill Pit Application (form CDP-1) with Intent to Drill (form KSONA-1) with Cathodic Protection Borehole Intent (CB-1) c. File Completed.  Submit plugging report (CP-4) within 60 days after final plugging is completed.	grouting to the top when the cathodic surface casing is set.
2. Notify appropriate District Office 48 hours prior to workover or re-entry. 3. A copy of the approved notice of intent to drill shall be posted on each drilling rig. 4. The minimum amount of cathodic surface casing as specified below shall be set by a full required forms: a. File Drill Pit Application (form CDP-1) with Intent to Drill (form KSONA-1) with Cathodic Protection Borehole Intent (CB-1) c. File Completed. 5. Submit plugging report (CP-4) within 60 days after final plugging is completed. 6. Submit plugging report (CP-4) within 60 days after final plugging is completed.	grouting to the top when the cathodic surface casing is set.
Notify appropriate District Office 48 hours prior to workover or re-entry.  A copy of the approved notice of intent to drill shall be posted on each drilling rig.  The minimum amount of cathodic surface casing as specified below shall be set by the set of the set	grouting to the top when the cathodic surface casing is set.
Notify appropriate District Office 48 hours prior to workover or re-entry.  A copy of the approved notice of intent to drill shall be posted on each drilling rig.  The minimum amount of cathodic surface casing as specified below shall be set by the set of the set	grouting to the top when the cathodic surface casing is set. form CB-1). b. File Certification of Compliance with Kansas Surface Owner Notification etion Form (ACO-1) within 60 days from spud date.
Notify appropriate District Office 48 hours prior to workover or re-entry.  A copy of the approved notice of intent to drill shall be posted on each drilling rig.  The minimum amount of cathodic surface casing as specified below shall be set by the set of the set	grouting to the top when the cathodic surface casing is set.
Notify appropriate District Office 48 hours prior to workover or re-entry.  A copy of the approved notice of intent to drill shall be posted on each drilling rig.  The minimum amount of cathodic surface casing as specified below shall be set by the set of the set	grouting to the top when the cathodic surface casing is set.  form CB-1). b. File Certification of Compliance with Kansas Surface Owner Notification betion Form (ACO-1) within 60 days from spud date.
Notify appropriate District Office 48 hours prior to workover or re-entry.  A copy of the approved notice of intent to drill shall be posted on each drilling rig.  The minimum amount of cathodic surface casing as specified below shall be set by the set of the set	grouting to the top when the cathodic surface casing is set.  form CB-1). b. File Certification of Compliance with Kansas Surface Owner Notification etion Form (ACO-1) within 60 days from spud date.  If this permit has expired or will not be drilled, check a box below, sign, date and return to the address below.
Notify appropriate District Office 48 hours prior to workover or re-entry.  A copy of the approved notice of intent to drill shall be posted on each drilling rig.  The minimum amount of cathodic surface casing as specified below shall be set by the set of the set	grouting to the top when the cathodic surface casing is set.  form CB-1). b. File Certification of Compliance with Kansas Surface Owner Notification betion Form (ACO-1) within 60 days from spud date.
2. Notify appropriate District Office 48 hours prior to workover or re-entry. 3. A copy of the approved notice of intent to drill shall be posted on each drilling rig. 4. The minimum amount of cathodic surface casing as specified below shall be set by a specified below shall be	grouting to the top when the cathodic surface casing is set.  form CB-1). b. File Certification of Compliance with Kansas Surface Owner Notification etion Form (ACO-1) within 60 days from spud date.  If this permit has expired or will not be drilled, check a box below, sign, date and return to the address below.
2. Notify appropriate District Office 48 hours prior to workover or re-entry. 3. A copy of the approved notice of intent to drill shall be posted on each drilling rig. 4. The minimum amount of cathodic surface casing as specified below shall be set by a specified all required forms: a. File Drill Pit Application (form CDP-1) with Intent to Drill (form KSONA-1) with Cathodic Protection Borehole Intent (CB-1) c. File Completed.  3. Submit plugging report (CP-4) within 60 days after final plugging is completed.  4. Submitted Electronically  4. For KCC Use ONLY  4. API # 15 -  Conductor pipe required	grouting to the top when the cathodic surface casing is set.  form CB-1). b. File Certification of Compliance with Kansas Surface Owner Notification etion Form (ACO-1) within 60 days from spud date.  If this permit has expired or will not be drilled, check a box below, sign, date and return to the address below.
2. Notify appropriate District Office 48 hours prior to workover or re-entry. 3. A copy of the approved notice of intent to drill shall be posted on each drilling rig. 4. The minimum amount of cathodic surface casing as specified below shall be set by a specified below shall be	grouting to the top when the cathodic surface casing is set.  form CB-1). b. File Certification of Compliance with Kansas Surface Owner Notification etion Form (ACO-1) within 60 days from spud date.  If this permit has expired or will not be drilled, check a box below, sign, date and return to the address below.  Permit Expired Well Not Drilled
2. Notify appropriate District Office 48 hours prior to workover or re-entry. 3. A copy of the approved notice of intent to drill shall be posted on each drilling rig. 4. The minimum amount of cathodic surface casing as specified below shall be set by a specified below shall be	grouting to the top when the cathodic surface casing is set.  form CB-1). b. File Certification of Compliance with Kansas Surface Owner Notification etion Form (ACO-1) within 60 days from spud date.  If this permit has expired or will not be drilled, check a box below, sign, date and return to the address below.

c:	4~	T.	

1349305

SEWARD CO. 3390' FEL

For KCC Use ONLY	
API # 15	

## IN ALL CASES, PLEASE FULLY COMPLETE THIS SIDE OF THE FORM.

In all cases, please fully complete this side of the form. Include items 1 through 3 at the bottom of this page.

				Location of	of Well: County: _	Г	<b></b>	1	
•						feet from	N /	S Line of S	
Borehole N	Number:			Sec	Twp	feet from L S. R	IJ E / L [	│ W Line of S │ E │ │ W	ection
				Is Section		_			
					n is Irregular, loca orner used:	ate well from n	earest cori	_	<i>/</i> .
		ne Cathodic Boreholo batteries, pipelines a	and electrical lines,		Kansas Surface O				
			:						
						LEG	END		
						Tank Pipel	Location Battery Location ine Location ric Line Location e Road Location	on ocation	
387 ft.	<del> </del>				• • • •				
			32		EX	AMPLE :			
						<b>Ο-</b> 7		198	30' FSL
							: :		

NOTE: In all cases locate the spot of the proposed drilling locaton.

#### In plotting the proposed location of the well, you must show:

- 1. The manner in which you are using the depicted plat by identifying section lines, i.e. 1 section, 1 section with 8 surrounding sections, 4 sections, etc.;
- 2. The distance of the proposed drilling location from the section's south / north and east / west; line.
- 3. The predicted locations of lease roads, tank batteries, pipelines, and electrical lines.



1349305

Form CDP-1 July 2014 Form must be Typed

## **APPLICATION FOR SURFACE PIT**

Submit in Duplicate

Operator Name:			License Number:
Operator Address:			
Contact Person:			Phone Number:
Lease Name & Well No.:			Pit Location (QQQQ):
Type of Pit:  Emergency Pit Burn Pit  Settling Pit Drilling Pit  Workover Pit Haul-Off Pit  (If WP Supply API No. or Year Drilled)  Is the pit located in a Sensitive Ground Water A	Pit is:  Proposed Existing  If Existing, date constructed:  Pit capacity:  (bbls)		SecTwpR East West West Feet from North / South Line of Section Feet from East / West Line of Section County mg/l
Is the bottom below ground level?	Artificial Liner?	No	(For Emergency Pits and Settling Pits only)  How is the pit lined if a plastic liner is not used?
Pit dimensions (all but working pits):	Length (fee	et)	Width (feet) N/A: Steel Pits
Depth from the pit is lined give a brief description of the list material, thickness and installation procedure.	om ground level to dee	Describe proce	dures for periodic maintenance and determining any special monitoring.
Distance to nearest water well within one-mile of	of pit:	Depth to shallo Source of infor	west fresh water feet. mation:
feet Depth of water well	feet	measured	well owner electric log KDWR
Emergency, Settling and Burn Pits ONLY:  Producing Formation:  Number of producing wells on lease:  Barrels of fluid produced daily:  Does the slope from the tank battery allow all s flow into the pit?  Yes No  Submitted Electronically		Type of materia  Number of work  Abandonment p  Drill pits must b	over and Haul-Off Pits ONLY:  all utilized in drilling/workover:  king pits to be utilized:  procedure:  de closed within 365 days of spud date.
	KCC	OFFICE USE O	
Date Received: Permit Num	ber:	Permi	Liner Steel Pit RFAC RFAS  It Date: Lease Inspection: Yes No

## Kansas Corporation Commission Oil & Gas Conservation Division

1349305

Form KSONA-1
July 2014
Form Must Be Typed
Form must be Signed
All blanks must be Filled

# CERTIFICATION OF COMPLIANCE WITH THE KANSAS SURFACE OWNER NOTIFICATION ACT

This form must be submitted with all Forms C-1 (Notice of Intent to Drill); CB-1 (Cathodic Protection Borehole Intent); T-1 (Request for Change of Operator Transfer of Injection or Surface Pit Permit); and CP-1 (Well Plugging Application).

Any such form submitted without an accompanying Form KSONA-1 will be returned.

OPERATOR: License #	Well Location:
Name:	
Address 1:	County:
Address 2:	Lease Name: Well #:
City: State: Zip:+	g
Contact Person:	the lease below:
Phone: ( ) Fax: ( )	-
Email Address:	-
Surface Owner Information:	
Name:	
Address 1:	sheet listing all of the information to the left for each surface owner. Surface owner information can be found in the records of the register of deeds for the
Address 2:	and the second in the construction of the cons
City: State: Zip:+	-
	ank batteries, pipelines, and electrical lines. The locations shown on the plat I on the Form C-1 plat, Form CB-1 plat, or a separate plat may be submitted.
owner(s) of the land upon which the subject well is or will be	e Act (House Bill 2032), I have provided the following to the surface e located: 1) a copy of the Form C-1, Form CB-1, Form T-1, or Form being filed is a Form C-1 or Form CB-1, the plat(s) required by this , and email address.
KCC will be required to send this information to the surface	I acknowledge that, because I have not provided this information, the owner(s). To mitigate the additional cost of the KCC performing this so of the surface owner by filling out the top section of this form and e KCC, which is enclosed with this form.
KCC will be required to send this information to the surface task, I acknowledge that I must provide the name and address that I am being charged a \$30.00 handling fee, payable to the	owner(s). To mitigate the additional cost of the KCC performing this so of the surface owner by filling out the top section of this form and e KCC, which is enclosed with this form.  If the fee is not received with this form, the KSONA-1
KCC will be required to send this information to the surface task, I acknowledge that I must provide the name and address that I am being charged a \$30.00 handling fee, payable to the If choosing the second option, submit payment of the \$30.00 handling fee.	owner(s). To mitigate the additional cost of the KCC performing this so of the surface owner by filling out the top section of this form and e KCC, which is enclosed with this form.  If the fee is not received with this form, the KSONA-1

Form	CB1CDP1 - Cathodic Protection Borehole Intent
Operator	Magellan Pipeline Company LP
Well Name	COFFEYVILLE 10" PIPELINE AC WELL #8A
Doc ID	1349305

# Anode Installation Depths

Depth	
55	
65	
75	
85	
95	
05	
15	
25	
35	
45	
55	
65	
75	
85	
95	
05	
15	
25	
35	
45	
55	
65	
75	
85	

Form	CB1CDP1 - Cathodic Protection Borehole Intent		
Operator	Magellan Pipeline Company LP		
Well Name	COFFEYVILLE 10" PIPELINE AC WELL #8A		
Doc ID	1349305		

# Anode Installation Depths

Depth	
395	

# **Cathodic Protection Installation Request**

Coffeville to Caney 10"

# AC Mitigation Deep Well #8A



Region:	CENTRAL	Area:	COFFEYVILLE		Pipeline:	Coffeyville to C	aney 10"
Alignment Sheet:		Tract:	6561-MG-30	Mile Post:	5.18 miles	Survey Station:	275+10
State :	Kansas	County:	Montgomery	Longitude:	-95.693018°	Latitude: 37	.045224°
Section:	31	1/4 Sec.of 1/4:	SW/SW/NE/SE	Township:	T34S	Range:	16E
Location: Property Owner Contact & Information: Power Company Contact and Information:		EN OESTMAN - 801 HIE	BBARD DEARING, COFFE	/VILLE, KS			
Groundbed Type:			Current Required:	NA	Soil Resistance:	13.82094 ohm meters	
Anode Type:	ANOTEC HSCI 26	60	Number of Anodes:	25	Type of Backfill:	LORESCO SC3	
Amount of Backfill:	9,3	00LBS	Type of Cable: 2/0	HMWPE		Amount of Cable:	175'
New Rectifier Required: (yes/no):	N/A		Rectifier Type: N/A			Anode Depth:	255'
Anode Spacing:	10'	Anode Hole Specs:	420 X 10	Design Life:	20 YEARS		
Require	ed Installation Date	):		Cons	struction Company:	Pipeline Controls a	and Services
Driving Directions			R 4100 travel South 2180ft From East survey line go V		<b>.</b>		
Details:	GROUNDBED TO	BE COMPLETED BELO	W GRADE AND ANODE W	IRES WILL BE TE	ERMINATED AT PCR	RBOX	
Requested By:	TVANGOOR	_	Date	03/22/16			