

SM Oil & Gas, Inc.
P. O. Box 189
Skiatook, Oklahoma 74070
620-725-3200

October 24, 2016

Kansas Corporation Commission
Conservation Division
266 N. Main Street – Suite #220
Wichita, Kansas 67202-1513

Re: ~~Fulsom B #14-3~~ #14-2
API #15-019-27563-00-00
Cement Usage ACO-1

To Whom It May Concern:

SM Oil & Gas, Inc. buys quantities of Portland Type I cement, which comes on pallets of 35 sacks per pallet, for the companies usage. In this case, the required 10 sacks of cement were mixed by our own drilling rig personnel and used to properly install the surface casing.

An invoice showing the bulk quantity of cement is available if needed.

Thank you,



Thomas H. Oast
Area Manager

810 E 7TH
 PO Box 92
 EUREKA, KS 67045
 (620) 583-5561



Cement or Acid Field Report
 Ticket No. 3008
 Foreman Kevin McCoy
 Camp EUREKA

Date	Cust. ID #	Lease & Well Number	Section	Township	Range	County	State	
11-8-16	1180	Fulson B 14-B 14-2				CQ	Ks	
Customer S.M. OIL & GAS INC.			Unit #		Driver		Unit #	Driver
Mailing Address P.O. Box 189			Safety Meeting		104		ALAN M.	
			KM		112		KEVIN M.	
			AM		113		STEVE M.	
			SM		141		RICK L.	
			RL		120 P.U.		GREG M.	
GM								
City	State	Zip Code						
SKIATOOK	OK	74070						

Job Type Longstring Hole Depth 1578' Slurry Vol. 36 LEAD 20 TAIL Tubing _____
 Casing Depth 1573' Hole Size 6 3/4" Slurry Wt. 12.8 - 14" Drill Pipe _____
 Casing Size & Wt. 4 1/2 11.60" Cement Left in Casing 0' Water Gal/SK _____ Other _____
 Displacement 24.5 BBL Displacement PSI 750 Bump Plug to 1250 PSI BPM _____

Remarks: Safety Meeting; Rig up to 4 1/2 casing. BREAK CIRCULATION w/ 35 BBL fresh water. Pump 500* Gel flush w/ Hulls, 5 BBL water spacer. Mixed 135 SKS 50/50 Pacmix Cement w/ 6% Gel, 1* PhenoSeal /SK @ 12.8" /GAL, yield 1.50 = 36 BBL slurry TAIL in w/ 75 SKS OWC Cement w/ 1* PhenoSeal @ 14" /GAL, yield 1.50 = 20 BBL slurry. wash out Pump & Lines. Shut down. Release Plug. Displace Plug to Seat w/ 24.5 BBL fresh water. FINAL pumping pressure 750 PSI. Bump Plug to 1250 PSI. wait 2 mins. Release pressure. Flat held. Shut in @ 0 PSI. Good Cement to SURFACE = 6 BBL slurry. Job Complete. Rig down.

Code	Qty or Units	Description of Product or Services	Unit Price	Total
C 102	1	Pump Charge	1050.00	1050.00
C 107	30	Mileage	3.95	118.50
C 204	135 SKS	50/50 Pacmix Cement	11.25	1518.75
C 206	680 "	Gel 6%	.20	136.00
C 208	135	PhenoSeal 1*/SK	1.25	168.75
C 202	75 SKS	OWC Cement	19.15	1436.25
C 208	75 "	PhenoSeal 1*/SK	1.25	93.75
C 206	500 *	Gel flush	.20	100.00
C 204	40 *	Hulls	.45	18.00
C 108 A	9.57 tons	Ton Mileage	M/L	690.00
C 403	1	4 1/2 Top Rubber Plug	45.00	45.00
C 113	3 Hrs	80 BBL VAC TRUCK	85.00	255.00
C 224	3300 gals	City water	10.00/1000	33.00
			Sub TOTAL	5663.00
			Less 5%	298.24
			8.5% Sales Tax	301.71
			Total	5666.47

Authorization [Signature]

Title _____

Total 5666.47

I agree to the payment terms and conditions of services provided on the back of this job ticket. Any amendments to payment terms must be in writing on the front of this job ticket or in the Customer's records at ELITE's office.