

Well Refined Drilling Company, Inc.

4270 Gray Road - Thayer, KS 66776

Contractor License # 33072 - FEIN # 48-1248553

620-763-2619/Office; 620-432-6170/Truck; 620-763-2065/FAX



Rig #:	3	S 1	T 31S	R 17E
API #:	15-099-23952-00-00	Location:	NE, SE, SW, NW	
Operator:	Colt Energy Inc.	County:	Labette	
Address:	P.O. Box 388			

lola, Ks 66749			Gas Tests				
Well #:	5-1A	Lease Name:	Enegren	Depth	Oz.	Orifice	flow - MCF
Location:	2150 ft. from N	Line		355	8	1/2"	17.2
	1100 ft. from W	Line		455	6	1/2"	15.4
Spud Date:	5/25/2006			555	10	1/2"	19.9
Date Completed:	5/26/2006	TD:	1155	605	7	1/2"	16.7
Driller:	Joe Chapulek			630	8	1/2"	17.2
Casing Record	Surface	Production		655	11	1/2"	20.9
Hole Size	12 1/4"	6 3/4"		680	14	1/2"	23.7
Casing Size	8 5/8"			705	5	3/4"	31.6
Weight	26 #			730	Gas Check Same		
Setting Depth	21' 6"			755	4	3/4"	28.3
Cement Type	Portland			780	Gas Check Same		
Sacks	6			830	2	3/4"	20
Feet of Casing	21' 6"			980	Gas Check Same		
				1005	3	3/4"	24.5
Rig Time	Work Performed			1055	2	3/4"	20
				1065	Gas Check Same		
				1080	1	3/4"	14.2

Well Log

Top	Bottom	Formation	Top	Bottom	Formation	Top	Bottom	Formation
0	1	OB	218	232	lime	476	510	sand
1	3	clay	232	235	shale	510	519	shale
3	14	sand	235	260	lime	519	537	lime
14	16	shale	260	271	shale	537	538	shale
16	20	lime	271	286	lime	538	543	blk shale
20	91	shale	286	338	shale	543	544	Lexington- coal
91	122	lime	338	351	lime	544	562	shale
122	123	shale	351	360	shale	562	582	sand
123	125	blk shale	360	366	sand	582	596	shale
125	130	lime	366	376	shale	596	627	Oswego- lime
130	138	shale	376	386	Alamont- lime	605	607	Oil Odor
138	151	sand	386	389	shale	627	630	shale
151	153	shale	389	397	lime	630	631	blk shale
153	172	sand	397	405	shale	631	651	shale
172	184	shale	405	409	lime	651	654	sand
184	212	lime	409	434	shale	654	655	Excello- coal
205		Add Water	434	443	Weiser- sand	655	657	shale
212	218	shale	443	476	shale	657	658' 6"	Mulky- coal

Operator: Colt Energy Inc.			Lease Name: Enegren			Well # 5-1A		page 2
Top	Bottom	Formation	Top	Bottom	Formation	Top	Bottom	Formation
658' 6"	666	lime	992' 6"	1015	shale			
666	672	shale	1015	1031	sand			
672	675	lime	1031	1035	shale			
675	690	shale	1035	1041	blk shale			
680	691	coal	1041	1043	shale			
691	693	shale	1043	1054	sand			
693	695	lime	1054	1056	coal			
695	710	shale	1056	1060	shale			
710	711	lime	1060	1062	Riverton- coal			
711	712	shale	1062	1066	shale			
712	713	Crowburg- coal	1066	1155	Mississippi- lime			
713	719	shale	1155		Total Depth			
719	751	sand						
751	752	shale						
752	754	blk shale						
754	756	Mineral- coal						
756	793	shale						
793	805	sand						
805	821	shale						
821	824	blk shale						
824	825	coal						
825	842	shale						
842	861	sand						
861	864	Laminated sand						
864	874	shale						
874	909	sand						
909	917	shale						
917	937	sand						
937	941	Laminated sand						
941	971	shale						
971	974	Laminated sand						
974	984	sand						
984	985	coal						
985	991	shale						
991	992' 6"	coal						

Notes: 06LE-052606-R3-051-Enegren 5-1A - Colt

Keep Drilling - We're Willing !!