			E 5 SAE	PAGE	1	OF	1		
CLIENT: ONEOK			PROJECT NAME:	Groundbed Installation DATE DRILLED: TBD					
SITE: Multple			_LOCATION	: Kansas					
OTHER ID#		FACI	LITY:		GPS				
COMPANY : Woofter Pump and Well			_	BOREHOLE: 10 inch					
LOGGED BY: <u>Brewer</u>			DRILLING METHOD: Wet Rotary or Dry FLUID Water if wet rotary						
	TYF	PE II	NTERVAL	MATERIAL JOINT LENGTH		DIAMETER			
CASING:	SDR	21	0-20"	PVC			10"		
Casing data			and cement.	Total of 1128 pounds used.					
Plug Portland plug to 53' bgs									
DEEP GROUNDBE CONSTRUCTI		2 DEPTH (FT.)	s	DESCRIPTION/	COMMENTS				
		20	l c	A S I N G		<u> </u>			
		Γ 1							
		T 1							
			P	ORTL A	N D				
		L J		1 1 2 8#			23 sacks		
		L 1					– –		
		53							
		F 4				!			
		F 1						 	
		├ -						 	
		F 1				<u> </u>			
		F 1							
		r 1					 I		
		T 1							
			s	A E E N	VIRO		- 		
				A N	O D E		 		
		L 1		s Y	STEM	!	– –		
		<u> </u>				!			
		F						<u> </u>	
		240						<u> </u>	
Initial Depth to Wat	er:								
Static Depth to Wa									
Comments		Not to scale							