

F. G. HOLL

6427 EAST KELLOGG

WICHITA, KANSAS 67207

DRILLING REPORT

COFFMAN 2 - 9
SW SW NE
Section 9-24-17W
Edwards County, Kansas

Contractor: Sterling Drilling Co.
Geologist: Jerry Monk
Elevation: 2115 KB
2112 DF
2106 GL

10-10-80 MIRT

SAMPLE TOPS

10-11-80 Spudded 9:45 a.m. Ran 6 jts. used
8 5/8" Csg. 259.44' set at 271 KB
with 225 sx. 60-40 pos. 3% cc by
HOWCO. Cement circulated. Plug down
at 2:00 p.m.

| | | |
|------------------|------|-------|
| Heebner | 3735 | -1620 |
| Brown Lime | 3859 | -1744 |
| Lansing | 3872 | -1757 |
| Base K.C. | 4164 | -2049 |
| Cherokee | 4287 | -2172 |
| Cherokee Sand | 4329 | -2214 |
| Mississippian | 4346 | -2231 |
| Kinderhook Shale | 4389 | -2274 |
| Viola | 4435 | -2320 |
| RTD | 4460 | -2345 |

10-12-80 ∅ at 1490'.

10-13-80 ∅ at 2625'.

10-14-80 ∅ at 3460'.

10-15-80 ∅ at 4155'. DST # 1, 4305-4380,
30-30-60-30, ISIP 447, IF 83, FSIP
675, FF 135, 30' of slightly oil and
gas cut mud, 180' of heavy oil and gas
cut mud

10-16-80 ∅ at 4380'. TD 4460, Logged.

10-17-80 Ran 13 jts. used 10½# csg., 109 jts.
new. 4448. 01' set at 4457 KB with
225 sx. Plug down at 11:45 a.m. 3
centralizers and 110' of rotating scratchers.