



The Loftis Company
PO Box 7847 Midland TX 79708
432-682-8343
Cathodic Protection Since 1952

Drilling Log

COMPANY	DCP Midstream	TOTAL DEPTH	300'	CASING SIZE	10"
LOCATION	Off CR W, Kismet	HOLE SIZE	10"	CASING LENGTH	20'
COUNTY	Seward	STATE	KS	CASING TYPE	Sch 40 PVC
UNIT NO.	Hawk Booster CP Unit	NO. of ANODES	15	DATE	9/22/2019
CONTRACT	PO 466205	ANODE TYPE	Silicon Iron	OTHER	

Depth	Formation	Amps	Depth	Formation	Amps	Anode	Depth	Before Coke	After Coke
5	Top Soil		295			1	285	0.4	5.3
10			300			2	275	1.4	8.8
15	Sand		305			3	265	1.9	10.1
20			310			4	255	2.8	11.5
25			315			5	245	1.9	11.0
30			320			6	235	1.9	10.6
35			325			7	225	0.2	8.8
40			330			8	215	0.3	7.6
45			335			9	205	0.4	6.6
50			340			10	195	0.3	5.9
55			345			11	185	0.4	5.4
60			350			12	175	0.8	5.2
65			355			13	165	0.7	4.7
70			360			14	155	1.4	5.6
75			365			15	145	2.0	5.9
80			370			16			
85			375			17			
90			380			18			
95			385			19			
100			390			20			
105			395			21			
110			400			22			
115			405			23			
120			410			24			
125			415			25			
130			420			26			
135			425			27			
140	Brown Clay		430			28			
145			435			29			
150			440			30			
155			445						
160			450						
165			455						
170	Sandy Clay		460						
175			465						
180			470						
185			475						
190			480						
195			485						
200			490						
205			495						
210			500						
215			505						
220			510						
225			515						
230			520						
235			525						
240	Brown Sandy Clay		530						
245			535						
250			540						
255			545						
260			550						
265			555						
270			560						
275			565						
280			570						
285			575						
290	(TD @ 290')		580						

Logging Volts: 13.10

Total Amps: 18.3

Remarks: Hydrovac used
 Negative Cadweld Made

Job # M2386