KOLAR Document ID: 1469324

Confidentiality Requested:

Yes No

Kansas Corporation Commission Oil & Gas Conservation Division

Form ACO-1
January 2018
Form must be Typed
Form must be Signed
All blanks must be Filled

WELL COMPLETION FORM WELL HISTORY - DESCRIPTION OF WELL & LEASE

OPERATOR: License #	API No.:
Name:	Spot Description:
Address 1:	SecTwpS. R
Address 2:	Feet from North / South Line of Section
City: State: Zip:+	Feet from East / West Line of Section
Contact Person:	Footages Calculated from Nearest Outside Section Corner:
Phone: ()	□NE □NW □SE □SW
CONTRACTOR: License #	GPS Location: Lat:, Long:
Name:	(e.g. xx.xxxxxx) (e.gxxx.xxxxxx)
Wellsite Geologist:	Datum: NAD27 NAD83 WGS84
Purchaser:	County:
Designate Type of Completion:	Lease Name: Well #:
New Well Re-Entry Workover	Field Name:
	Producing Formation:
☐ Oil ☐ WSW ☐ SWD	Elevation: Ground: Kelly Bushing:
☐ Gas ☐ DH ☐ EOR	Total Vertical Depth: Plug Back Total Depth:
☐ OG ☐ GSW	Amount of Surface Pipe Set and Cemented at: Feet
CM (Coal Bed Methane)	Multiple Stage Cementing Collar Used? Yes No
Cathodic Other (Core, Expl., etc.):	
If Workover/Re-entry: Old Well Info as follows:	If yes, show depth set: Feet
Operator:	If Alternate II completion, cement circulated from:
Well Name:	feet depth to: w/ sx cmt.
Original Comp. Date: Original Total Depth:	
☐ Deepening ☐ Re-perf. ☐ Conv. to EOR ☐ Conv. to SWD	Drilling Fluid Management Plan
☐ Plug Back ☐ Liner ☐ Conv. to GSW ☐ Conv. to Producer	(Data must be collected from the Reserve Pit)
Commingled Permit #:	Chloride content: ppm Fluid volume: bbls
Dual Completion Permit #:	Dewatering method used:
SWD Permit #:	Location of fluid disposal if hauled offsite:
☐ EOR Permit #:	Location of haid disposal if hadica offsite.
GSW Permit #:	Operator Name:
	Lease Name: License #:
Spud Date or Date Reached TD Completion Date or	Quarter Sec TwpS. R
Recompletion Date Recompletion Date	County: Permit #:

AFFIDAVIT

I am the affiant and I hereby certify that all requirements of the statutes, rules and regulations promulgated to regulate the oil and gas industry have been fully complied with and the statements herein are complete and correct to the best of my knowledge.

Submitted Electronically

KCC Office Use ONLY						
Confidentiality Requested						
Date:						
Confidential Release Date:						
Wireline Log Received Drill Stem Tests Received						
Geologist Report / Mud Logs Received						
UIC Distribution						
ALT I II Approved by: Date:						

KOLAR Document ID: 1469324

Page Two

Operator Name	:						Lease	Name: _				W	/ell #:	
Sec Tv	vp	S. R.		East	t 🔲 W	/est	Count	ty:						
open and closed and flow rates if	d, flowing a gas to surf tity Log, Fir	ind shu face tes nal Logs	t-in pressu st, along w s run to ob	ures, who vith final otain Geo	ether sl chart(s ophysic	hut-in pre i). Attach cal Data a	essure rea extra she and Final I	iched stat eet if more Electric Lo	ic level space	, hydrosta e is needed	tic pressures d.	s, botton	n hole tempe	val tested, time tool erature, fluid recovery, v. Digital electronic log
Drill Stem Tests (Attach Addi	Taken	s)			/es [No		L	.og	Formatio	n (Top), Dep	oth and	Datum	Sample
Samples Sent to		•	∋y		es [No		Nam	е				Тор	Datum
Cores Taken Electric Log Rur Geologist Repo	rt / Mud Lo	gs			/es [/es [No No No								
List / III L. Logo	i turi.													
				Rep	ort all st		RECORD			Used ite, producti	on, etc.			
Purpose of S	String	Size Dril			ize Casi et (In O.I			eight s. / Ft.		Setting Depth	Type of Cement		# Sacks Used	Type and Percent Additives
					ADI	DITIONAL	. CEMENT	ING / SQL	JEEZE	RECORD				
Purpose: Perforate Protect C Plug Back	asing		pth Sottom	Тур	e of Cer	ment	# Sack	ks Used	d Type and Percent Additives					
Plug Off 2														
Did you perform Does the volum Was the hydrau	ne of the tota	al base fl	uid of the h	ydraulic fr	racturing	•				Yes Yes Yes	No (If N	lo, skip c	questions 2 an question 3) t Page Three (·
Date of first Produ	uction/Injecti	ion or Re	sumed Pro	duction/		ucing Meth	nod:	ina	Gas Li	ft 🗆 C	ther (Explain)			
Estimated Produ Per 24 Hours			Oil E	Bbls.			Mcf	Wat			ols.	Gas	:-Oil Ratio	Gravity
DISP	POSITION O	F GAS:				N	METHOD C	F COMPLI	ETION:				PRODUCTIC Top	ON INTERVAL: Bottom
Vented (If vent	Sold [_	on Lease		Open H	lole	Perf.		Comp t ACO-5		nmingled mit ACO-4)			
Shots Per Foot	Perfora Top		Perforat Bottor		Bridge Typ		Bridge P Set At			Acid,	Fracture, Shot		nting Squeeze Material Used)	Record
TUBING RECOF	BD:	Size:		Set At:	<u> </u>		Packer At:							
				JULAI.			. wonor At.							

Form	ACO1 - Well Completion
Operator	Brehm Asset Management, LLC
Well Name	BOWMAN 1
Doc ID	1469324

Casing

Purpose Of String	Size Hole Drilled	Size Casing Set	Weight	Setting Depth	Type Of Cement		Type and Percent Additives
Surface	12.25	8.625	20	43	Common	10	None

BREHM ASSET MANAGEMENT, LLC

WELLSITE CONSULTING

BOWMAN #1 SW NW SEC34-T34S-R12E CHAUTAUQUA COUNTY, KANSAS API 15-019-27663-00 SUPPLEMENTAL DEEPENING REPORT

C&G Drilling Rig #1 spud the well on July 23^{rd} , 2019. Re-Entry of the wellbore began at 12:00 Noon on the 23^{rd} . Cement plugs were drilled 0' - 740', 1,150' - 1,200', 1,850' - 1,900', and, the old total depth of 1,915' was reached. The hole was also reamed from $6\frac{3}{4}$ " to $7\frac{7}{8}$ ". New $7\frac{7}{8}$ " hole was then drilled to a total depth of 2,260' reached at 1:00 AM, July 25^{th} , 2019. The well bore was then open hole logged by **Osage Wireline**. The suite of logs run was *Dual Induction* & *Density/Neutron*.

Samples were caught at ten-foot intervals from the old total depth to the new TD of 2,260'. From previous TD to 2,072' Mississippian, from 2,072' - 2,116' Kinderhook & Woodford Shales, from 2,116' - 2,260' New TD Arbuckle.

ARBUCKLE

Litho	Description	Depth	Notes
	Dolo LS Gray-Brown	2,116-2,130	Odor, s scatt flour, vssfo
	Dolo LS Gray-Brown	2,130-2,140	Odor, s scatt flour, s stain
	Dolo LS Gray-Brown	2,140-2,150	Odor, s scatt flour, s stain
	LS Brown Dense Xtall	2,150-2,160	
	LS Brown Dense Xtall	2,160-2,170	
	LS Brown Dense Xtall	2,170-2,180	
	LS Brown Dense Xtall	2,180-2,190	
	LS Brown Dense Xtall	2,190-2,200	
	LS Cream-Tan s ool	2,200-2,210	
	LS Gray-Brown Dense	2,210-2,220	
	LS Gray-Brown Dense	2,220-2,230	
	LS Cream-Gray Dense	2,230-2,240	
	LS Cream-Gray Dense	2,240-2,250	
	LS Cream-Gray Dense	2,250-2,260	

In conclusion. The target formation, the Arbuckle, was predominantly solid dense limestone. There was a noticeable dolomitic section in the top thirty feet, and, the same section carried an odor. With only a slight show of oil & some staining, there was a lack of free oil show. The log suite confirmed the sample study as it showed a consistently low to no porosity dense carbonate. Dwight Brehm Oil & Gas Consultant