

TIM PRIEST
Petroleum Geologist

(316) 213-6115

GEOLOGIST'S REPORT
DRILLING TIME AND SAMPLE LOG
ELEVATIONS

COMPANY **VAL ENERGY, INC.**

LEASE **WILSON 1-3**

FIELD **Wild cat**

LOCATION **1838 FSL, 47°2' FWL**

SEC. **3**

TWP. **8S**

RGE. **35W**

Kansas

COUNTY **Thomas**

STATE **Kansas**

CONTRACTOR **WW Drilling, Rig #10**

SPUD **10-12-17**

RTD **'**

LTD **,**

MUD UP **3600'**

TYPE MUD **Chemical**

PRODUCTION **SURFACE 8-5/8" @ 261'**

CONDUCTOR **N/A**

SURFACE **8-5/8" @ 261'**

PRODUCTION **8-5/8" @ 261'**

CASING **N/A**

PRODUCTION **8-5/8" @ 261'**

ELECTRICAL **N/A**

PRODUCTION **8-5/8" @ 261'**

SURVEYS **N/A**

PRODUCTION **8-5/8" @ 261'**

CND DSP:PE **N/A**

Misc. **N/A**

PRODUCTION **8-5/8" @ 261'**

REMARKS **None**

API #15-193-21003

Respectfully Submitted,

Tim Priest

Petroleum Geologist

13-30-15-45

PF: BOB 15' 30' 45'

FF: No blow, no return

Rec: 315' MW(67%W,

33%N)

Rate: 60' MW(67%W,

33%N)

HGT: 132' 132'

SP: 132' 132'

CHL: 132' 132'

Total Fluid: 35,000 rpm

Fps: 404.7148/730.7978

SPs: 859.08/404.7148

HP: 132' 132'

BP: 132' 132'

Gravty: .39

13-30-15-45

PF: BOB 15' 30' 45'

FF: No blow, no return

Rec: 315' MW(67%W,

33%N)

Rate: 60' MW(67%W,

33%N)

HGT: 132' 132'

SP: 132' 132'

CHL: 132' 132'

Total Fluid: 35,000 rpm

Fps: 404.7148/730.7978

SPs: 859.08/404.7148

HP: 132' 132'

BP: 132' 132'

Gravty: .39

13-30-15-45

PF: BOB 15' 30' 45'

FF: No blow, no return

Rec: 315' MW(67%W,

33%N)

Rate: 60' MW(67%W,

33%N)

HGT: 132' 132'

SP: 132' 132'

CHL: 132' 132'

Total Fluid: 35,000 rpm

Fps: 404.7148/730.7978

SPs: 859.08/404.7148

HP: 132' 132'

BP: 132' 132'

Gravty: .39

13-30-15-45

PF: BOB 15' 30' 45'

FF: No blow, no return

Rec: 315' MW(67%W,

33%N)

Rate: 60' MW(67%W,

33%N)

HGT: 132' 132'

SP: 132' 132'

CHL: 132' 132'

Total Fluid: 35,000 rpm

Fps: 404.7148/730.7978

SPs: 859.08/404.7148

HP: 132' 132'

BP: 132' 132'

Gravty: .39

13-30-15-45

PF: BOB 15' 30' 45'

FF: No blow, no return

Rec: 315' MW(67%W,

33%N)

Rate: 60' MW(67%W,

33%N)

HGT: 132' 132'

SP: 132' 132'

CHL: 132' 132'

Total Fluid: 35,000 rpm

Fps: 404.7148/730.7978

SPs: 859.08/404.7148

HP: 132' 132'

BP: 132' 132'

Gravty: .39

13-30-15-45

PF: BOB 15' 30' 45'

FF: No blow, no return

Rec: 315' MW(67%W,

33%N)

Rate: 60' MW(67%W,

33%N)

HGT: 132' 132'

SP: 132' 132'

CHL: 132' 132'

Total Fluid: 35,000 rpm

Fps: 404.7148/730.7978

SPs: 859.08/404.7148

HP: 132' 132'

BP: 132' 132'

Gravty: .39

13-30-15-45

PF: BOB 15' 30' 45'

FF: No blow, no return

Rec: 315' MW(67%W,

33%N)

Rate: 60' MW(67%W,

33%N)

HGT: 132' 132'

SP: 132' 132'

CHL: 132' 132'

Total Fluid: 35,000 rpm

Fps: 404.7148/730.7978

SPs: 859.08/404.7148

HP: 132' 132'

BP: 132' 132'

Gravty: .39

13-30-15-45

PF: BOB 15' 30' 45'

FF: No blow, no return

Rec: 315' MW(67%W,

33%N)

Rate: 60' MW(67%W,

33%N)

HGT: 132' 132'

SP: 132' 132'

CHL: 132' 132'

Total Fluid: 35,000 rpm

Fps: 404.7148/730.7978

SPs: 859.08/404.7148

HP: 132' 132'

BP: 132' 132'

Gravty: .39

13-30-15-45

PF: BOB 15' 30' 45'

FF: No blow, no return

Rec: 315' MW(67%W,

33%N)

Rate: 60' MW(67%W,