KOLAR Document ID: 1515959

Confident	tiality Re	equested:
Yes	No	

KANSAS CORPORATION COMMISSION OIL & GAS CONSERVATION DIVISION

Form ACO-1 January 2018 Form must be Typed Form must be Signed All blanks must be Filled

WELL COMPLETION FORM

WELL	HISTORY	- DESCRIPTION	OF WELL	& I FASE
	III JIONI	- DESCRIF HOR		a LLASL

OPERATOR: License #	API No.:
Name:	Spot Description:
Address 1:	
Address 2:	Feet from Dorth / South Line of Section
City: State: Zip:+	Feet from East / West Line of Section
Contact Person:	Footages Calculated from Nearest Outside Section Corner:
Phone: ()	
CONTRACTOR: License #	GPS Location: Lat:, Long:
Name:	(e.g. xx.xxxxx) (e.gxxx.xxxxx)
Wellsite Geologist:	Datum: NAD27 NAD83 WGS84
Purchaser:	County:
Designate Type of Completion:	Lease Name: Well #:
New Well Re-Entry Workover	Field Name:
	Producing Formation:
Gas DH EOR	Elevation: Ground: Kelly Bushing:
	Total Vertical Depth: Plug Back Total Depth:
CM (Coal Bed Methane)	Amount of Surface Pipe Set and Cemented at: Feet
Cathodic Other (Core, Expl., etc.):	Multiple Stage Cementing Collar Used?
If Workover/Re-entry: Old Well Info as follows:	If yes, show depth set: Feet
Operator:	If Alternate II completion, cement circulated from:
	feet depth to:w/sx cmt.
Original Comp. Date: Original Total Depth:	
Deepening Re-perf. Conv. to EOR Conv. to SWD	Drilling Fluid Management Plan
Plug Back Liner Conv. to GSW Conv. to Producer	(Data must be collected from the Reserve Pit)
	Chloride content: ppm Fluid volume: bbls
Commingled Permit #:	Dewatering method used:
Dual Completion Permit #:	
SWD Permit #:	Location of fluid disposal if hauled offsite:
EOR Permit #:	Operator Name:
GSW Permit #:	Lease Name: License #:
Spud Date or Date Reached TD Completion Date or	QuarterSecTwpS. R East West
Spud Date or Date Reached TD Completion Date or Recompletion Date Recompletion Date	County: Permit #:

AFFIDAVIT

I am the affiant and I hereby certify that all requirements of the statutes, rules and regulations promulgated to regulate the oil and gas industry have been fully complied with and the statements herein are complete and correct to the best of my knowledge.

Submitted Electronically

KCC Office Use ONLY				
Confidentiality Requested				
Date:				
Confidential Release Date:				
Wireline Log Received Drill Stem Tests Received				
Geologist Report / Mud Logs Received				
UIC Distribution				
ALT I II III Approved by: Date:				

KOLAR Document ID: 1515959

Operator Nar	ne:			Lease Name:	Well #:
Sec	Twp	S. R	East West	County:	

Page Two

INSTRUCTIONS: Show important tops of formations penetrated. Detail all cores. Report all final copies of drill stems tests giving interval tested, time tool open and closed, flowing and shut-in pressures, whether shut-in pressure reached static level, hydrostatic pressures, bottom hole temperature, fluid recovery, and flow rates if gas to surface test, along with final chart(s). Attach extra sheet if more space is needed.

Final Radioactivity Log, Final Logs run to obtain Geophysical Data and Final Electric Logs must be emailed to kcc-well-logs@kcc.ks.gov. Digital electronic log files must be submitted in LAS version 2.0 or newer AND an image file (TIFF or PDF).

Drill Stem Tests Taken (Attach Additional Sh	acate)	Y	′es 🗌 No			og Formatio	n (Top), Depth a	and Datum	Sample
Samples Sent to Geolo			⁄es 🗌 No	1	Name	Э		Тор	Datum
Cores Taken Electric Log Run Geologist Report / Mud List All E. Logs Run:		□ Y □ Y	Yes ☐ No Yes ☐ No Yes ☐ No						
		Rep	CASING ort all strings set-c] Ne	w Used rmediate, productio	on. etc.		
Purpose of String	Size Hole Drilled	Siz	ze Casing et (In O.D.)	Weight Lbs. / Ft.		Setting Depth	Type of Cement	# Sacks Used	Type and Percent Additives
[ADDITIONAL	CEMENTING /	SQU	EEZE RECORD			
Purpose:	Depth Top Bottom	Туре	e of Cement	# Sacks Use	d		Type and	Percent Additives	
Protect Casing Plug Back TD Plug Off Zone									
 Did you perform a hydra Does the volume of the Was the hydraulic fracture 	total base fluid of the	hydraulic fr	acturing treatment		-	☐ Yes ns? ☐ Yes ☐ Yes	No (If No, s	kip questions 2 ar kip question 3) ill out Page Three	
Date of first Production/Inj Injection:	jection or Resumed Pr	oduction/	Producing Meth	iod:		Gas Lift 🗌 O	ther <i>(Explain)</i>		
Estimated Production Per 24 Hours	Oil	Bbls.	Gas	Mcf	Wate	er Bb	ls.	Gas-Oil Ratio	Gravity
DISPOSITIO	N OF GAS:		Ν	IETHOD OF COM	MPLE	TION:		PRODUCTIC Top	DN INTERVAL: Bottom
Vented Sold (If vented, Subn	Used on Lease		Open Hole		-	·	nit ACO-4)	юр	Bollom
	foration Perform Top Botto		Bridge Plug Type	Bridge Plug Set At		Acid,		ementing Squeezend of Material Used)	
TUBING RECORD:	Size:	Set At:		Packer At:					

Form	ACO1 - Well Completion
Operator	RJ Energy, LLC
Well Name	BADER 23
Doc ID	1515959

Casing

Purpose Of String	Size Hole Drilled	Size Casing Set	Weight	Setting Depth	Type Of Cement		Type and Percent Additives
Surface	9.875	7	17	40	portland	5	
Production	5.875	2.875	6.5	1012	portland	125	

HAMMERSON CORPORATION

PO BOX 189 Gas. KS 66742

.

Invoice

Date	Invoice #
3/19/2020	16124

Bill To R.J. ENERGY LLC 22082 NE NEOSHO RD GARNETT, KS 66032

		P.O. No.	Terms	Project
			Due on receipt	
Quantity	Description		Rate	Ampunt
125 1.2 125 1.25 1.25 1.25 1.30 1.5 125 125 1	WELL MUD (S8.00 PER SACK) Bader 23 Ticket = TRUCKING (S50 PER HOUR) WELL MUD (S8.00 PER SACK) Bader 121 Ticket TRUCKING (S50 PER HOUR) WELL MUD (S8.00 PER SACK) Haney 7A Ticket TRUCKING (S50 PER HOUR) WELL MUD (S8.00 PER SACK) Bader 111 Ticket TRUCKING (S50 PER HOUR) WELL MUD (S8.00 PER SACK) Haney 6A Ticket TRUCKING (S50 PER HOUR) SALES TAX	=16116 & =16117 =16121 & =16122 =16130 & =16131		8.00 50.00 8.00 50.0

R

RJ Energy

22082 NE Neosho Rd Garnett. Kansas 66032

Bader 23

4	soil	4	
25	clay/gravel	29	
101	shale	130	
17	lime	147	
13	shale	160	
38	lime	198	
80	shale	278	
13	lime	291	
9	shale	300	
116	lime	416	
48	shale	464	
63	lime	527	
6	shale	533	
50	lime	583	
180	shale	763	
12	lime	775	
70	shale	845	
27	lime	872	
19	shale	891	
5	lime	896	
16	shale	912	
6	lime	918	
6	shale	924	
5	lime	929	
36	shale	965	
12	bkn sand	977	good show
41	shale	1018	T.D.

Start	3-6-20
Finish	3-10-20

Set 40'of 7" w/5sxs Ran 1012.2' of 2 ⁷/₈ cemented to the surface 125sxs