

**Notice:** Fill out COMPLETELY and return to Conservation Division at the address below within 60 days from plugging date.

KANSAS CORPORATION COMMISSION  
OIL & GAS CONSERVATION DIVISION

**WELL PLUGGING RECORD**

K.A.R. 82-3-117

Form CP-4

March 2009

**Type or Print on this Form**  
**Form must be Signed**  
**All blanks must be Filled**

OPERATOR: License #: \_\_\_\_\_  
 Name: \_\_\_\_\_  
 Address 1: \_\_\_\_\_  
 Address 2: \_\_\_\_\_  
 City: \_\_\_\_\_ State: \_\_\_\_\_ Zip: \_\_\_\_\_ + \_\_\_\_\_  
 Contact Person: \_\_\_\_\_  
 Phone: ( \_\_\_\_\_ ) \_\_\_\_\_  
 Type of Well: (Check one)  Oil Well  Gas Well  OG  D&A  Cathodic  
 Water Supply Well  Other: \_\_\_\_\_  SWD Permit #: \_\_\_\_\_  
 ENHR Permit #: \_\_\_\_\_  Gas Storage Permit #: \_\_\_\_\_  
 Is ACO-1 filed?  Yes  No If not, is well log attached?  Yes  No  
 Producing Formation(s): List All (If needed attach another sheet)  
 \_\_\_\_\_ Depth to Top: \_\_\_\_\_ Bottom: \_\_\_\_\_ T.D. \_\_\_\_\_  
 \_\_\_\_\_ Depth to Top: \_\_\_\_\_ Bottom: \_\_\_\_\_ T.D. \_\_\_\_\_  
 \_\_\_\_\_ Depth to Top: \_\_\_\_\_ Bottom: \_\_\_\_\_ T.D. \_\_\_\_\_

API No. 15 - \_\_\_\_\_  
 Spot Description: \_\_\_\_\_  
 \_\_\_\_\_ - \_\_\_\_\_ - \_\_\_\_\_ - \_\_\_\_\_ Sec. \_\_\_\_\_ Twp. \_\_\_\_\_ S. R. \_\_\_\_\_  East  West  
 \_\_\_\_\_ Feet from  North /  South Line of Section  
 \_\_\_\_\_ Feet from  East /  West Line of Section  
 Footages Calculated from Nearest Outside Section Corner:  
 NE  NW  SE  SW  
 County: \_\_\_\_\_  
 Lease Name: \_\_\_\_\_ Well #: \_\_\_\_\_  
 Date Well Completed: \_\_\_\_\_  
 The plugging proposal was approved on: \_\_\_\_\_ (Date)  
 by: \_\_\_\_\_ (KCC District Agent's Name)  
 Plugging Commenced: \_\_\_\_\_  
 Plugging Completed: \_\_\_\_\_

Show depth and thickness of all water, oil and gas formations.

Oil, Gas or Water Records		Casing Record (Surface, Conductor & Production)			
Formation	Content	Casing	Size	Setting Depth	Pulled Out

Describe in detail the manner in which the well is plugged, indicating where the mud fluid was placed and the method or methods used in introducing it into the hole. If cement or other plugs were used, state the character of same depth placed from (bottom), to (top) for each plug set.

Plugging Contractor License #: \_\_\_\_\_ Name: \_\_\_\_\_  
 Address 1: \_\_\_\_\_ Address 2: \_\_\_\_\_  
 City: \_\_\_\_\_ State: \_\_\_\_\_ Zip: \_\_\_\_\_ + \_\_\_\_\_  
 Phone: ( \_\_\_\_\_ ) \_\_\_\_\_  
 Name of Party Responsible for Plugging Fees: \_\_\_\_\_  
 State of \_\_\_\_\_ County, \_\_\_\_\_, ss.  
 \_\_\_\_\_  Employee of Operator or  Operator on above-described well,  
 (Print Name)

being first duly sworn on oath, says: That I have knowledge of the facts statements, and matters herein contained, and the log of the above-described well is as filed, and the same are true and correct, so help me God.

**Submitted Electronically**





**CEMENT TREATMENT REPORT**

Customer: L & P Enterprises	Well: Heeler W2, W3, W11, W10, W9, A-5	Ticket: EP1237
City, State: Paola Ks.	County: Mi., Ks.	Date: 1/14/2021
Field Rep: Kevin Wiseman	S-T-R: NW 8-17-22	Service: Plug

Downhole Information	
Hole Size:	in
Hole Depth:	ft
Casing Size:	2 7/8 in
Casing Depth:	700-750 ft
Tubing / Liner:	in
Depth:	ft
Tool / Packer:	
Tool Depth:	ft
Displacement:	bbls

Calculated Slurry - Lead	
Blend:	
Weight:	ppg
Water / Sx:	gal / sx
Yield:	ft <sup>3</sup> / sx
Annular Bbls / Ft.:	bbs / ft.
Depth:	ft
Annular Volume:	0.0 bbls
Excess:	
Total Slurry:	0.0 bbls
Total Sacks:	#DIV/0! sx

Calculated Slurry - Tail	
Blend:	
Weight:	ppg
Water / Sx:	gal / sx
Yield:	ft <sup>3</sup> / sx
Annular Bbls / Ft.:	bbs / ft.
Depth:	ft
Annular Volume:	0 bbls
Excess:	
Total Slurry:	0.0 bbls
Total Sacks:	#DIV/0! sx

TIME	RATE	PSI	STAGE BBLs	TOTAL BBLs	REMARKS
9:00 AM		400.0	-	-	W2 2 7/8 723' Established injection rate. Mixed and pumped 30 sacks H-Plug cement with 10# cottonseed hulls. Well pressured to 1200 PSI. Cleaned and closed valve. Left casing full to surface.
		1,200.0			
9:30 AM		400.0	-	-	W3 2 7/8 723' Established injection rate. Mixed and pumped 30 sacks H-Plug cement with 10# cottonseed hulls. Well pressured to 1200 PSI. Cleaned and closed valve. Left casing full to surface.
		1,200.0			
10:00 AM		200.0	-	-	W11 2 7/8 730' Established circulation down 1" at well TD. Mixed and pumped 25 sacks H-Plug cement. Circulated cement to surface. Pulled 1" out of well. Topped off with 5 more sacks cement. 30 sacks total
11:00 AM		400.0	-	-	W10 2 7/8 713' Established injection rate. Mixed and pumped 30 sacks H-Plug cement with 10# cottonseed hulls. Well pressured to 1200 PSI. Cleaned and closed valve. Left casing full to surface.
		1,200.0			
11:30 AM		400.0	-	-	W9 2 7/8 716' Established injection rate. Mixed and pumped 30 sacks H-Plug cement with 10# cottonseed hulls. Well pressured to 1200 PSI. Cleaned and closed valve. Left casing full to surface.
		1,200.0			
12:00 PM		400.0	-	-	A-5 4 1/2 750' Established injection rate. Mixed and pumped 45 sacks H-Plug cement with 20# cottonseed hulls. Well pressured to 1200 PSI. Cleaned and closed valve. Left casing full to surface.
		1,200.0			

CREW		UNIT	SUMMARY		
Cementer:	Alan Mader	90	Average Rate	Average Pressure	Total Fluid
Pump Operator:	Mark Foltz	238	#DIV/0! bpm	745 psi	- bbls
Bulk #1:	Casey Kennedy	110			
Bulk #2:	Pat Sanborn	246			