_ WELL ID_

KOLAR DOC ID _

WATER WELL RECORD (WWC-5)

OCATION OF WATER WELL						Original I	Recor	d Co	rrection	Chang	e in We	l Use
Latitude	Longitude			Section	Township	R	lange	E W	Fraction	1/4	1/4	1/4
Datum	Elevation			County	<u> </u>							
WATER WELL OWNER		l	WELL	NATER US	 			NEAREST S	OURCE OF	POTENTIAL C	ONTAMIN	IATION
Name								Source:				
Business			COMP	LETION				Distance		Direction	n	
Dustriess					. 1 . 11			from well:		from we	ll:	
Address					ted well:		ft.	Source descriptio	n.			
			1 -	•	water encountered: (2) ft.;	•						
Well location					(2) it.; (4) dry well							
								from well:		Direction from we	n ll:	
at owner's address			Static water level in well: ft. measured below land surface					Source description:				
CONSTRUCTION				(mm/dd/y				No not	ential cour	ce of contami	nation	
CONSTRUCTION			measured above land surface					No potential source of contamination within 100 feet.				
Borehole interval: Borehole diameter:			on (mm/dd/yy):				=	PERMIT & ID NUMBERS (AS REQUIRED)				
fromtoft.		in.			gpm			DIATE 4	ali anti co Ni			
fromto ft.			Water		ft. after		•	1).: Code:		
Casing height above land sur		in.	D		pumping Yes No	gpm		KDHE / EPA Project Code:				
If casing height is less that has a variance been appr		s No	Pump	installed:	Yes No			Site Name: KDHE UIC Class V Form Completed: Yes No				
*variance not required fo			Water well disinfected? Yes No						s No Perm			
or environmental remediation wells			Date disinfected (mm/dd/yy):			_	Lease Name & Well #:					
Casing type:			A au : 6	er, if knowr						# of dewater		
Blank casing interval:		ft.										
Blank casing diameter:				LOGIC LOG		NITED\/A.I.C						
Casing joints:lbs			FROI	и то	LITHOLOGY	NIERVALS	'					
Wall thickness or gauge r												
Blank casing interval:												
Blank casing diameter:												
Casing joints:												
Weight:lbs												
Wall thickness or gauge r	10.:											
Grout interval:ft. to	ft											
Grout material:												
Grout interval: ft. to												
Grout material:			сомм	ENTS								
Screen / perforation material:												
Screen / perforation opening			CONTE	RACTOR'S	OR LANDOWNER	S CERTIFIC	ATION					
Screen / perforation intervals			This	water well	was constructe	d reco	onstru	cted p	oursuant to	the stated w	ater well	
Fromft. to			contr	actor's lice	ense and was con	npleted on		·	I certify th	nat this recor	d is true	to
Slot size unit _			the b	est of my l	knowledge and b	elief. This v	vater v	well record	was compl	eted on		
From ft. to			unde	r the busii	ness name of							,
Slot size unit _			Kans	as Water V	Vell Contractor's	License No	o	uı	nder the au	thority of th	e designa	ited
Gravel pack intervals:	Cmar1 - '				ed in K.A.R. 28-3					•	_	
Gravel pack not used:		in	-		son at its submitt	•	٥				-	
From ft. to Gravel pack not used:					VATER WELL OW		ain one	e for vour rec	ords. Fee of	\$5.00 for each	constructe	d well
From ft. to		in		· · · · · · · · · · · · · · · · · · ·				EALTH AND				
710m n. to	11.			Bureau	of Water, Geology (7			Jackson St., S A. 82a-1212		peka KS 66612	2-1367	

Form	WWC5.2 - Water Well Record
Doc ID	1635892
Well Owner	J Archer Farms
Contractor	Double J Energy

Lithology

From	То	Lithology Intervals
0	1	clay
1	10	cobbles,fine to medium
10	20	limestone,fractured,clayey,whi te,hard
20	26	limestone,unweathered,gray,h ard
26	30	limestone,unweathered,grayis h,white,hard
30	50	limestone,unweathered,hard
50	54	shale,unweathered,soft
54	75	limestone,unweathered,gray,h ard
75	180	limestone,unweathered,whitei sh,gray,hard
180	285	limestone,unweathered,gray,s ee attached log

Sheet1

Log:

0	1 clay	
1	10 overburden	
10	20 Limestone	white
20	26 Limestone	gray
26	30 Limestone	Gray-white
30	50 Limestone	
50	54 shale	
54	75 Limestone	gray
75	180 Limestone	white gray
180	285 Limestone	gray
285	290 shale	green
285	295 Limestone	white
295	320 Limestone	gray
320	325 lime/chert	
325	335 Limestone	gray black
335	360 Limestone	white
360	380 Limestone	gray
380	385 chert	black white
385	395 Limestone	gray
395	410 lime/chert	gray
410	445 Limestone	white
445	460 Limestone	gray
460	465 chert	
465	520 Limestone	gray
520	565 Limestone	white
565	615 Limestone	gray white
615	660 lime/chert	gray white
660	670 Limestone	brown
670	675 lime/chert	brown white
675	710 Limestone	gray
710	740 lime sandy	gray brown
740	760 lime/chert	gray black
760	780 lime/chert	brown
780	800 Limestone	gray
800	820 lime/chert	gray white
820	840 Limestone	gray brown
840	845 lime/chert	gray
845	860 Limestone	gray