

Notice: Fill out COMPLETELY and return to Conservation Division at the address below within 60 days from plugging date.

KANSAS CORPORATION COMMISSION
OIL & GAS CONSERVATION DIVISION

WELL PLUGGING RECORD

K.A.R. 82-3-117

Form CP-4

March 2009

Type or Print on this Form
Form must be Signed
All blanks must be Filled

OPERATOR: License #: _____
 Name: _____
 Address 1: _____
 Address 2: _____
 City: _____ State: _____ Zip: _____ + _____
 Contact Person: _____
 Phone: (_____) _____
 Type of Well: (Check one) Oil Well Gas Well OG D&A Cathodic
 Water Supply Well Other: _____ SWD Permit #: _____
 ENHR Permit #: _____ Gas Storage Permit #: _____
 Is ACO-1 filed? Yes No If not, is well log attached? Yes No
 Producing Formation(s): List All (If needed attach another sheet)
 _____ Depth to Top: _____ Bottom: _____ T.D. _____
 _____ Depth to Top: _____ Bottom: _____ T.D. _____
 _____ Depth to Top: _____ Bottom: _____ T.D. _____

API No. 15 - _____
 Spot Description: _____
 _____ - _____ - _____ - _____ Sec. _____ Twp. _____ S. R. _____ East West
 _____ Feet from North / South Line of Section
 _____ Feet from East / West Line of Section
 Footages Calculated from Nearest Outside Section Corner:
 NE NW SE SW
 County: _____
 Lease Name: _____ Well #: _____
 Date Well Completed: _____
 The plugging proposal was approved on: _____ (Date)
 by: _____ (KCC District Agent's Name)
 Plugging Commenced: _____
 Plugging Completed: _____

Show depth and thickness of all water, oil and gas formations.

Oil, Gas or Water Records		Casing Record (Surface, Conductor & Production)			
Formation	Content	Casing	Size	Setting Depth	Pulled Out

Describe in detail the manner in which the well is plugged, indicating where the mud fluid was placed and the method or methods used in introducing it into the hole. If cement or other plugs were used, state the character of same depth placed from (bottom), to (top) for each plug set.

Plugging Contractor License #: _____ Name: _____
 Address 1: _____ Address 2: _____
 City: _____ State: _____ Zip: _____ + _____
 Phone: (_____) _____
 Name of Party Responsible for Plugging Fees: _____
 State of _____ County, _____, ss.
 _____ Employee of Operator or Operator on above-described well,
 (Print Name)

being first duly sworn on oath, says: That I have knowledge of the facts statements, and matters herein contained, and the log of the above-described well is as filed, and the same are true and correct, so help me God.

Submitted Electronically

GRESSEL OIL FIELD SERVICE

POST OFFICE BOX 438
 HAYSVILLE, KS 67060
 (316) 524-1225
 FAX (316) 524-1027

Invoice

BURRTON, KS ● GREAT BEND, KS ● HAYS, KS ●
 (620) 463-5161 (620) 793-3366 (785) 628-3220

**INVOICE NUMBER:
 L1911-IN**

BILL TO:
DARRAH OIL COMPANY LLC
PO BOX 2786
WICHITA, KS 67202-2786

LEASE: PICKETT #6

DATE	ORDER	SALESMAN	ORDER DATE	PURCHASE ORDER	SPECIAL INSTRUCTIONS	
04/30/2022	1911		04/26/2022	PICKETT #6	NET 30	
QUANTITY	U/M	ITEM NO./DESCRIPTION		D/C	PRICE	EXTENSION
		RIG UP UNDER POLE CAT, SET CIBP AT 2430', RIG UP DUMP BAILER, MAKE 1 RUN, TEAR DOWN.				
1.00	EACH	SET UP WIRELINE		0.00	800.00	800.00
1.00	EACH	CAST IRON BRIDGE PLUG		0.00	850.00	850.00
2,430.00	EACH	SET CIBP		0.00	0.22	534.60
1.00	EACH	DUMP BAILER		0.00	288.90	288.90
REMIT TO: P.O. BOX 438 HAYSVILLE, KS 67060		LOG		Net Invoice: 2,473.50 BUTCO Sales Tax: 160.78 Invoice Total: 2,634.28		
RECEIVED BY _____		NET 30 DAYS				

There will be a charge of 1.5% (18% annual rate) on all accounts over 30 days past due.
 Gressel Oil Field Service reserves a security interest in the goods sold until the same are paid for in full and reserve all the rights of a secured party under the Uniform Commercial Code.

FIELD WORK ORDER, INVOICE AND CONTRACT

1911



Field Service, LLC

P.O. BOX 438
Haysville, KS 67060
(316) 524-1225 • FAX (316) 524-1027

Date <u>April 26 2002</u>	Charge To: <u>Danah Oil</u>	Lease and Well No. <u>Pickett # 4</u>
Operator <u>Greg Hill</u>	Address	Field
Customer's T.O.	City & State	Legal Description
T.O.	Fluid Level <u>175'</u>	Casing Size <u>4 1/2</u>
Zero	Type Fluid in Hole <u>Production</u>	Casing Wt. <u>NA</u>
	Elevation <u>NA</u>	Casing Depth <u>2101</u>
		Sec. <u>4</u> Twp. <u>25</u> Rng. <u>5E</u>
		County <u>Burton</u>
		State <u>Ks</u>

- The authorized agent and representative of the owner agrees to the following general terms and conditions of services to be rendered or which have been rendered:
- (1) All accounts are due and must be paid within 30 days from the date of services of Gressel Oil Field Service, Inc., and should these terms not be observed, interest at the rate of 18% per annum will be charged from the date of the services.
 - (2) Because of the uncertain conditions and hazards existing in a well which are beyond the control of Gressel Oil Field Service, Inc., it is understood and agreed by the parties hereto that Gressel Oil Field Service, Inc. cannot guarantee the results of its efforts and its services and will not be held responsible for personal or property damage in the performance of its services.
 - (3) Should any Gressel Oil Field Service, Inc. instruments or equipment be lost or damaged in the performance of the operations requested, the customer agrees to make every reasonable effort to recover the same, and to reimburse Gressel Oil Field Service, Inc. for the value of the items which cannot be recovered, or the cost of repairing damage to items recovered.
 - (4) The customer certifies that he has the full right and authority to order such work on such well and that the well in which the work is to be performed by Gressel Oil Field Service, Inc. is in proper and suitable condition for the performance of said work and that Gressel Oil Field Service, Inc. is merely working under the directions of the customer.
 - (5) The customer agrees to pay any and all taxes, fees and charges placed on services rendered by Gressel Oil Field Service, Inc. by governmental requirements including city, county, state and federal taxes and fees or reimburse Gressel Oil Field Service, Inc. for such taxes and fees paid to said agencies.
 - (6) No employee is authorized to alter the terms or conditions of this agreement between Gressel Oil Field Service, Inc. and the customer.
 - (7) I certify that the services have been performed by Gressel Oil Field Service, Inc. under my directions and control, and that all zones perforated were designated by me and all depth measurements were checked and approved.
 - (8) It is further stipulated and agreed to between the parties hereto that this agreement shall not become effective until the same is approved by Gressel Oil Field Service, Inc., in Harvey County, Kansas, and that the venue of any action, either in law or equity to enforce the terms of the same is agreed by the parties hereto to be in Harvey County, Kansas.

Dated in Burton, Kansas, this 26th day of April 2002

CUSTOMER

AUTHORIZED AGENT AND REPRESENTATIVE
GRESSSEL OIL FIELD SERVICE, INC.

OFFICER

WORK PERFORMED	PRICING
Perforated With <u>NA</u> as Follows:	SET UP: \$
From _____ ft. to _____ ft. _____ Shots	PERFORATING: 1st _____ Shots \$
From _____ ft. to _____ ft. _____ Shots	Next _____ Shots @ \$ _____ Ea. \$
From _____ ft. to _____ ft. _____ Shots	Next _____ Shots @ \$ _____ Ea. \$
From _____ ft. to _____ ft. _____ Shots	LOGGING: Logging Chg. _____ ft @ \$ _____ ft. \$
From _____ ft. to _____ ft. _____ Shots	BRIDGE PLUG: Type <u>Alpha 1</u> Depth <u>2430</u> \$
From _____ ft. to _____ ft. _____ Shots	CEMENT LOCATOR SURVEY: \$
<u>Run up under Polk Cat set OBP 2430 Run up dump barrels make 1 run tear down</u>	<u>Did's Bid - 7/10 cost 2473.00</u>
	SUB TOTAL \$
	TAX \$
	TOTAL \$

Mike's Testing & Salvage Inc.

DBA Kelso Well Service

P.O. Box 467

Chase, KS 67524

Invoice

Date	Invoice #
12/14/2022	18549

Bill To
Darrah Oil Company LLC 125 N. Market Street Suite 1425 Wichita, Kansas 67202

P.O. No.	County	Lease
Felix - Rig #1	Butler	Pickett #6

Qty	Description	Rate	Amount
15	Hours Rig Time	265.00	3,975.00T
	Casing Cutter	500.00	500.00T
1	Night Out of Town	300.00	300.00T
	11-29-22 Moved rig to location, rigged up for casing, ran bailer to 500'. Pushed wood plug to 300' down 4-1/2" casing, dumped 2 sacks cement on top of plug with bailer. Backhoe dug out cellar and pit, cut casing @280', not loose. 8 Hours		
	11-30-22 Cut casing loose @260', laid down 4-1/2" casing. Tore down rig and moved off. 7 Hours Not Plugged		
	Sales Tax	6.75%	322.31

Total	\$5,097.31
--------------	------------

Dispatch (316) 522-4949
 Dorado (316) 320-5000
 Office (316) 522-8454



300033469



PLANT	TICKET TIME	DATE	ORDER #	TRUCK	DRIVER	TIME DUE	TICKET #
		12/08					
CUSTOMERS INFO				DELIVERY ADDRESS INSTRUCTIONS			

JOHN DARRAH
 HWY 77
 Slump 8.00

FROM NORTH OF EL DORADO EXIT THE TURNPIKE GO
 NORTH ON HWY 77 TO NORTH OF WALTERS
 PUMPKIN PATCH GO WEST TO THE RIG TO JOB

PURCHASE ORDER	PROJECT #	PROJECT DESC.	MAP PAGE	PREV TRUCK #	SLUMP	USAGE
	1001	EASTERN KANSAS			8.00	
LOAD QTY.	PRODUCT	DESCRIPTION	ORDERED	DELIVERED	UNIT PRICE	AMOUNT
9.00 yd	JY3500	SLURRY MIX	9.00	9.00	\$169.00	1,521.00
1.00 EA	350FSD	Fuel Surcharge MIX	0.00		\$21.00	\$21.00
9.00 /y	WS	WINTER SERVICE CHARGE	0.00		\$5.00	\$45.00

LEAVE PLANT	ARRIVE JOB SITE	START DISCHARGE	FINISH DISCHARGE	ARRIVE PLANT	SUBTOTAL	AMOUNT
					\$103.16	

CAUTION: FRESHLY MIXED CONCRETE MAY CAUSE SKIN IRRITATION OR CHEMICAL BURNS.
 AVOID CONTACT WITH SKIN WHERE POSSIBLE AND WASH EXPOSED SKIN AREAS PROMPTLY WITH WATER. IF ANY CONCRETE MIXTURES GET INTO EYES, RINSE IMMEDIATELY AND REPEATEDLY WITH WATER AND GET PROMPT MEDICAL ATTENTION.
KEEP OUT OF REACH OF CHILDREN • SEE REVERSE SIDE FOR MSDS SHEET

NOTICE: EXCESSIVE UNLOADING TIME
 • A HOLDING CHARGE OF \$1.50 PER MINUTE WILL BE INCLUDED FOR EACH TRUCK HELD ON THE JOB SITE FOR MORE THAN 60 MINUTES.
 • IN CONSIDERATION OF OUR MAKING DELIVERY ACROSS THE STREET CURB, AT YOUR REQUEST, CUSTOMER AGREES TO BE RESPONSIBLE FOR ALL DAMAGE DONE TO SIDEWALKS, DRIVEWAYS, BUILDINGS, GROUNDS, ETC. CUSTOMER ACKNOWLEDGES RECEIPT OF THE ABOVE MATERIALS IN APPROVED CONDITION.

IMPORTANT: PURCHASER ASSUMES FULL RESPONSIBILITY FOR STRENGTH, SLUMP AND QUALITY OF CONCRETE WHEN WATER OR OTHER MATERIALS ARE ADDED ON THE JOB SITE AT THE REQUEST OF THE CUSTOMER.

OUT SIDE TEMP.	TOTAL	
	OTHER CHARGES	
	ADDITIONAL TAX	
	GRAND TOTAL	1690.16
WATER ADDED ON JOB AT REQUEST OF CONSIGNEE	GALS. WATER	INT.
TEST TAKEN	SLUMP / AIR / CYLS.	PER ASTM SPECS. YES NO

ACCEPTED BY: _____
 PURCHASER'S SIGNATURE, HIS AGENT, OR HIS EMPLOYEE'S SIGNATURE CONSTITUTES AN AGREEMENT WITH THE ABOVE TERMS AND CONDITIONS.

DRIVER REMARKS: _____

Walters 'B' 18

300033469

AE Charge 12/09

MATERIAL SAFETY DATA SHEET

(Only Applicable Data Provided for Each Section)

SECTION I
 Manufacturer's Name, Concrete Materials Company
 Address: See Reverse Side
 Emergency Telephone Number, See Reverse Side
 Trade Names
 3Cao S102 (cement), 2Cao S102 (cement), 3Cao A1203 (cement),
 4Cao A1203 (cement), Casp4 2H2O, Traces Cao, MGD, K2504, No 2504
 Chemical Family:
 SECTION II - HAZARDOUS INGREDIENTS, Cement and possible traces of hexavalent chromium.
 SECTION III - PHYSICAL DATA
 Specific Gravity: 1.9 to 2.4
 Appearance and Odor: Gray plastic flowable, granular mud, odorless
 SECTION IV - FIRE AND EXPLOSION HAZARD DATA: N/A, all sections
 SECTION V - HEALTH HAZARD DATA
 TLV: None
 Effects of Overexposure:
 Dry skin and possible alkali burns (cement dermatitis).
 Also possible traces of hexavalent chromium.
 Emergency First Aid Procedures:
 Irrigate eyes with water. Wash affected areas of the body with soap and water.
 SECTION VI - REACTIVITY DATA
 Stability: Unstable
 X
 Conditions to Avoid:
 Product sets and hardens in 2 to 5 hours
 and is no longer hazardous
 Will Not Occur
 X
 SECTION VII - SPILL OR LEAK PROCEDURES
 Polymerization
 Waste Disposal Method: Once hardened, material can be disposed of as common waste.
 Steps to be Taken in Case Material is Released or Spilled: Spill does not increase hazard.
 SECTION VIII - SPECIAL PROTECTION INFORMATION
 Protective Gloves: Yes
 Eye Protection: Yes, when placement methods cause splashing.
 Use barrier creams, gloves, boots, and clothing to protect skin
 from prolonged contact with plastic concrete.
 SECTION IX - SPECIAL PRECAUTIONS
 Other Protective Equipment:
 Precautions to be Taken in Handling and Storage: See above.
 Other Precautions: Immediately after working with concrete, workers should shower with soap and water.

SECTION I	SECTION II	SECTION III	SECTION IV	SECTION V	SECTION VI	SECTION VII	SECTION VIII	SECTION IX
Manufacturer's Name, Concrete Materials Company	3Cao S102 (cement), 2Cao S102 (cement), 3Cao A1203 (cement), 4Cao A1203 (cement), Casp4 2H2O, Traces Cao, MGD, K2504, No 2504	Specific Gravity: 1.9 to 2.4	Appearance and Odor: Gray plastic flowable, granular mud, odorless	TLV: None	Stability: Unstable	Spill or Leak Procedures: Polymerization	Special Protection Information: Protective Gloves: Yes	Special Precautions: Other Protective Equipment:

SECTION X	SECTION XI	SECTION XII	SECTION XIII	SECTION XIV	SECTION XV	SECTION XVI	SECTION XVII	SECTION XVIII
Other Precautions: Immediately after working with concrete, workers should shower with soap and water.	Precautions to be Taken in Handling and Storage: See above.	Other Protective Equipment:	Protective Gloves: Yes	Eye Protection: Yes, when placement methods cause splashing.	Use barrier creams, gloves, boots, and clothing to protect skin from prolonged contact with plastic concrete.	SECTION IX - SPECIAL PRECAUTIONS	SECTION VIII - SPECIAL PROTECTION INFORMATION	SECTION VII - SPILL OR LEAK PROCEDURES

SECTION I
 Manufacturer's Name, Concrete Materials Company
 Address: See Reverse Side
 Emergency Telephone Number, See Reverse Side
 Trade Names
 3Cao S102 (cement), 2Cao S102 (cement), 3Cao A1203 (cement),
 4Cao A1203 (cement), Casp4 2H2O, Traces Cao, MGD, K2504, No 2504
 Chemical Family:
 SECTION II - HAZARDOUS INGREDIENTS, Cement and possible traces of hexavalent chromium.
 SECTION III - PHYSICAL DATA
 Specific Gravity: 1.9 to 2.4
 Appearance and Odor: Gray plastic flowable, granular mud, odorless
 SECTION IV - FIRE AND EXPLOSION HAZARD DATA: N/A, all sections
 SECTION V - HEALTH HAZARD DATA
 TLV: None
 Effects of Overexposure:
 Dry skin and possible alkali burns (cement dermatitis).
 Also possible traces of hexavalent chromium.
 Emergency First Aid Procedures:
 Irrigate eyes with water. Wash affected areas of the body with soap and water.
 SECTION VI - REACTIVITY DATA
 Stability: Unstable
 X
 Conditions to Avoid:
 Product sets and hardens in 2 to 5 hours
 and is no longer hazardous
 Will Not Occur
 X
 SECTION VII - SPILL OR LEAK PROCEDURES
 Polymerization
 Waste Disposal Method: Once hardened, material can be disposed of as common waste.
 Steps to be Taken in Case Material is Released or Spilled: Spill does not increase hazard.
 SECTION VIII - SPECIAL PROTECTION INFORMATION
 Protective Gloves: Yes
 Eye Protection: Yes, when placement methods cause splashing.
 Use barrier creams, gloves, boots, and clothing to protect skin
 from prolonged contact with plastic concrete.
 SECTION IX - SPECIAL PRECAUTIONS
 Other Protective Equipment:
 Precautions to be Taken in Handling and Storage: See above.
 Other Precautions: Immediately after working with concrete, workers should shower with soap and water.

400063487

Dispatch (316) 522-4949
El Dorado (316) 320-5000
Office (316) 522-8454



PLANT	TICKET TIME	DATE	ORDER #	TRUCK	DRIVER	TIME DUE	TICKET #
4	7:28	12/19/05	6	665	SCOTT	8:27	28731

CUSTOMERS INFO DELIVERY ADDRESS INSTRUCTIONS

JOHN DARRAH
HWY 77 AND
PLAN ON USING THE SAME TRUCK
HYW 77 & NW110TH (DEGRAEF) GO WEST ON N/SIDE
LOOK FOR RIG

PURCHASE ORDER	PROJECT #	PROJECT DESC.	MAP PAGE	PREV TRUCK #	SLUMP	USAGE
PAID CREDIT 1004	1004	EASTERN KANSASVARIO			8.00	OTHER

LOAD QTY.	PRODUCT	DESCRIPTION	ORDERED	DELIVERED	UNIT PRICE	AMOUNT
6.00 yd	JY3500	SLURRY MIX	15.00	6.00	\$169.00	1,014.00
1.00 EA	350FSC	Fuel Surcharge RMX	0.00		\$21.00	\$21.00
6.00 /y	WS	WINTER SERVICE CHARGE	0.00		\$5.00	\$30.00

LEAVE PLANT	ARRIVE JOB SITE	START DISCHARGE	FINISH DISCHARGE	ARRIVE PLANT	SUBTOTAL
		12/05			TAX

CAUTION: FRESHLY MIXED CONCRETE MAY CAUSE SKIN IRRITATION OR CHEMICAL BURNS.
AVOID CONTACT WITH SKIN WHERE POSSIBLE AND WASH EXPOSED SKIN AREAS PROMPTLY WITH WATER. IF ANY CONCRETE MIXTURES GET INTO EYES, RINSE IMMEDIATELY AND REPEATEDLY WITH WATER AND GET PROMPT MEDICAL ATTENTION.
KEEP OUT OF REACH OF CHILDREN • SEE REVERSE SIDE FOR MSDS SHEET

NOTICE: EXCESSIVE UNLOADING TIME
• A HOLDING CHARGE OF \$1.50 PER MINUTE WILL BE INCLUDED FOR EACH TRUCK HELD ON THE JOB SITE FOR MORE THAN 60 MINUTES.
• IN CONSIDERATION OF OUR MAKING DELIVERY ACROSS THE STREET CURB, AT YOUR REQUEST, CUSTOMER AGREES TO BE RESPONSIBLE FOR ALL DAMAGE DONE TO SIDEWALKS, DRIVEWAYS, BUILDINGS, GROUNDS, ETC. CUSTOMER ACKNOWLEDGES RECEIPT OF THE ABOVE MATERIALS IN APPROVED CONDITION.

IMPORTANT: PURCHASER ASSUMES FULL RESPONSIBILITY FOR STRENGTH, SLUMP AND QUALITY OF CONCRETE WHEN WATER OR OTHER MATERIALS ARE ADDED ON THE JOB SITE AT THE REQUEST OF THE CUSTOMER.

OUT SIDE TEMP.	TOTAL	\$1,065.00	
	OTHER CHARGES	\$69.23	
	ADDITIONAL TAX	\$1,134.23	
	GRAND TOTAL	1,134.23	
WATER ADDED ON JOB AT REQUEST OF CONSIGNEE	GALS. WATER	GALS. WATER	GALS. WATER
	INT.	INT.	INT.
TEST TAKEN	SLUMP / AIR / CYLS.	PER ASTM SPECS.	YES NO

ACCEPTED BY: _____
PURCHER'S SIGNATURE, HIS AGENT, OR HIS EMPLOYEE'S SIGNATURE CONSTITUTES AN AGREEMENT WITH THE ABOVE TERMS AND CONDITIONS.

DRIVER REMARKS: _____

400063487

AE Charge 12/19

MATERIAL SAFETY DATA SHEET

(Only Applicable Data Provided for Each Section)

SECTION I	
Manufacturer's Name: Concrete Materials Company Address: See Reverse Side	Emergency Telephone Number: See Reverse Side Trade Names:
3CaO SiO ₂ (cement), 2CaO SiO ₂ (cement), 3CaO A12O ₃ (cement) 4CaO A12O ₃ (cement), CaSO ₄ 2H ₂ O, Traces CaO, MgO, K ₂ SO ₄ , Na ₂ SO ₄	
Chemical Family: SECTION II - HAZARDOUS INGREDIENTS: Cement and possible traces of hexavalent chromium.	
SECTION III - PHYSICAL DATA	
Specific Gravity: 1.9 to 2.4	Solubility in Water: 0.1 to 1.0%
Appearance and Odor: Gray, plastic, flowable, granular, mud, odorless	
SECTION IV - FIRE AND EXPLOSION HAZARD DATA: N.A. all sections	
SECTION V - HEALTH HAZARD DATA	
TLV: None	Effects of Overexposure: Dry skin and possible alkali burns (cement dermatitis). Also possible traces of hexavalent chromium.
Emergency First Aid Procedures: Irrigate eyes with water. Wash affected areas of the body with soap and water.	
SECTION VI - REACTIVITY DATA	
Stability	Conditions to Avoid: Product sets and hardens in 2 to 8 hours, and is no longer hazardous
Unstable X	Hazardous Polymerization Will Not Occur X
SECTION VII - SPILL OR LEAK PROCEDURES	
Steps to be Taken in Case Material is Released or Spilled: Spill does not increase hazard.	
Waste Disposal Method: Once hardened, material can be disposed of as common waste.	
SECTION VIII - SPECIAL PROTECTION INFORMATION	
Protective Gloves: Yes	Eye Protection: Yes, when placement methods cause splashing. Use barrier creams, gloves, boots, and clothing to protect skin from prolonged contact with plastic concrete.
Other Protective Equipment:	
SECTION IX - SPECIAL PRECAUTIONS	
Precautions to be Taken in Handling and Storage: See above.	
Other Precautions: Immediately after working with concrete, workers should shower with soap and water.	

[Faint, illegible text and markings, possibly bleed-through from the reverse side of the page]

[Faint, illegible text and markings, possibly bleed-through from the reverse side of the page]

Dispatch (316) 522-4949
 El Dorado (316) 320-5000
 Office (316) 522-8454



400063488

PLANT	TICKET TIME	DATE	ORDER #	TRUCK	DRIVER	TIME DUE	TICKET #
4	7:37	12/19/22	21	665	SCOTT	8:30	4028732

CUSTOMERS INFO

DELIVERY ADDRESS INSTRUCTIONS

CMC HWY 77 & NW110TH (DEGRAFF) GO WEST ON N/SIDE LOOK FORRIG

HWY 77 — NO CHARGE

Slump 8.00

PURCHASE ORDER	PROJECT #	PROJECT DESC.	MAP PAGE	PREV TRUCK #	SLUMP	USAGE
	20323	WASTE / TEST LOADS			8.00	HOLE

LOAD QTY.	PRODUCT	DESCRIPTION	ORDERED	DELIVERED	UNIT PRICE	AMOUNT
3.00 yd	JY3500	SLURRY MIX	3.00	3.00		
1.00 EA	350FSC	Fuel Surcharge RMX	0.00			
3.00 /y	WS	WINTER SERVICE CHARGE	0.00			

LEAVE PLANT	ARRIVE JOB SITE	START DISCHARGE	FINISH DISCHARGE	ARRIVE PLANT	SUBTOTAL
		12/19			TAX

CAUTION: FRESHLY MIXED CONCRETE MAY CAUSE SKIN IRRITATION OR CHEMICAL BURNS. AVOID CONTACT WITH SKIN WHERE POSSIBLE AND WASH EXPOSED SKIN AREAS PROMPTLY WITH WATER. IF ANY CONCRETE MIXTURES GET INTO EYES, RINSE IMMEDIATELY AND REPEATEDLY WITH WATER AND GET PROMPT MEDICAL ATTENTION. **KEEP OUT OF REACH OF CHILDREN • SEE REVERSE SIDE FOR MSDS SHEET**

NOTICE: EXCESSIVE UNLOADING TIME
 • A HOLDING CHARGE OF \$1.50 PER MINUTE WILL BE INCLUDED FOR EACH TRUCK HELD ON THE JOB SITE FOR MORE THAN 60 MINUTES.
 • IN CONSIDERATION OF OUR MAKING DELIVERY ACROSS THE STREET CURB, AT YOUR REQUEST, CUSTOMER AGREES TO BE RESPONSIBLE FOR ALL DAMAGE DONE TO SIDEWALKS, DRIVEWAYS, BUILDINGS, GROUNDS, ETC. CUSTOMER ACKNOWLEDGES RECEIPT OF THE ABOVE MATERIALS IN APPROVED CONDITION.

IMPORTANT: PURCHASER ASSUMES FULL RESPONSIBILITY FOR STRENGTH, SLUMP AND QUALITY OF CONCRETE WHEN WATER OR OTHER MATERIALS ARE ADDED ON THE JOB SITE AT THE REQUEST OF THE CUSTOMER.

OUT SIDE TEMP.	TOTAL	OTHER CHARGES	ADDITIONAL TAX
	GRAND TOTAL		
WATER ADDED ON JOB AT REQUEST OF CONSIGNEE	GALS. WATER	GALS. WATER	GALS. WATER
	INT.	INT.	INT.
TEST TAKEN	SLUMP / AIR / CYLS.	PER ASTM SPECS.	YES NO

ACCEPTED BY: _____
 PURCHER'S SIGNATURE, HIS AGENT, OR HIS EMPLOYEE'S SIGNATURE CONSTITUTES AN AGREEMENT WITH THE ABOVE TERMS AND CONDITIONS.

DRIVER REMARKS: _____

400063488

Truck	Driver	Disp	Ticket Num	Batch	Date	
665	1231708	4028732		7:37	12/19/22	
Load Size	Mix Code	Seq				
3.00 CYDS	JY3500	D1				
Material	Design Qty	Required	Batched	% Var	% Moisture	Actual Mat
CEMASHGV	1598 lb	4794 lb	4795 lb	0.02%		4795 lb
WATER	128.0 gl	384.0 gl	384.0 gl	0.00%		384.0 gl
Actual	Num 1	Manual	7:37:4			
Load Total:	7999 lb	Design W/C:	0.668	Water/Cement:	0.668 A	
Design Water:	384.0 gl	Actual Water:	384.0 gl	To Add:	0.0 gl	
Slump: 8 in	Trim:	0.00 gl	Batch Time	7:40 AM		

MATERIAL SAFETY DATA SHEET

(Only Applicable Data Provided for Each Section)

SECTION I Manufacturer's Name: Concrete Materials Company Address: See Reverse Side		Emergency Telephone Number: See Reverse Side Trade Names:	
Chemical Family:		3CaO SiO ₂ (cement), 2CaO SiO ₂ (cement), 3CaO A12O ₃ (cement) 4CaO A12O ₃ (cement), CaSO ₄ 2H ₂ O, Traces CaO, MgO, K ₂ SO ₄ , Na ₂ SO ₄	
SECTION II - HAZARDOUS INGREDIENTS: Cement and possible traces of hexavalent chromium.			
SECTION III - PHYSICAL DATA		Solubility in Water: 0.1 to 1.0%	
Specific Gravity: 1.9 to 2.4		Appearance and Odor: Gray, plastic, flowable, granular, mud, odorless	
SECTION IV - FIRE AND EXPLOSION HAZARD DATA: N.A. all sections			
SECTION V - HEALTH HAZARD DATA			
TLV: None	Effects of Overexposure:		Dry skin and possible alkali burns (cement dermatitis). Also possible traces of hexavalent chromium.
Emergency First Aid Procedures:		Irrigate eyes with water. Wash affected areas of the body with soap and water.	
SECTION VI - REACTIVITY DATA			
Stability	Unstable X	Conditions to Avoid:	Product sets and hardens in 2 to 8 hours, and is no longer hazardous
	Hazardous Polymerization		Will Not Occur X
SECTION VII - SPILL OR LEAK PROCEDURES			
Steps to be Taken in Case Material is Released or Spilled: Spill does not increase hazard.			
Waste Disposal Method: Once hardened, material can be disposed of as common waste.			
SECTION VIII - SPECIAL PROTECTION INFORMATION			
Protective Gloves: Yes	Eye Protection: Yes, when placement methods cause splashing. Use barrier creams, gloves, boots, and clothing to protect skin from prolonged contact with plastic concrete.		
Other Protective Equipment:			
SECTION IX - SPECIAL PRECAUTIONS			
Precautions to be Taken in Handling and Storage: See above.			
Other Precautions: Immediately after, working with concrete, workers should shower with soap and water.			

	<p style="text-align: center;">SECTION X - ADDITIONAL INFORMATION</p> <p style="text-align: center;">This section is intentionally left blank for additional information.</p>
--	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

	<p style="text-align: center;">SECTION XI - ADDITIONAL INFORMATION</p> <p style="text-align: center;">This section is intentionally left blank for additional information.</p>
--	--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Dispatcher (316) 522-4949
 El Dorado (316) 320-5000
 Office (316) 522-8454



400063491

PLANT	TICKET TIME	DATE	ORDER #	TRUCK	DRIVER	TIME DUE	TICKET #
	10:00	12/19/22	6	507	STEVE DOLLS	10:59	009735

JOHN DARRAH HYW 77 & NW110TH(DEGRAFF) GO WEST ON N/SIDE
 LOOK FOR RIG

HWY 77 AND
 PLAN ON USING THE SAME TRUCK

PURCHASE ORDER	PROJECT #	PROJECT DESC.	MAP PAGE	PREV TRUCK #	SLUMP	USAGE
PAID CREDIT 1004		EASTERN KANSASVARIO		665	8.00	OTHER

LOAD QTY.	PRODUCT	DESCRIPTION	ORDERED	DELIVERED	UNIT PRICE	AMOUNT
6.00 yd	JY3500	SLURRY MIX	12.00	12.00	\$169.00	1,014.00
1.00 EA	350FSC	Fuel Surcharge RMX	0.00		\$21.00	\$21.00
6.00 /y	WS	WINTER SERVICE CHARGE	0.00		\$5.00	\$30.00

LEAVE PLANT	ARRIVE JOB SITE	START DISCHARGE	FINISH DISCHARGE	ARRIVE PLANT	SUBTOTAL
		12/19			

CAUTION: FRESHLY MIXED CONCRETE MAY CAUSE SKIN IRRITATION OR CHEMICAL BURNS.
 AVOID CONTACT WITH SKIN WHERE POSSIBLE AND WASH EXPOSED SKIN AREAS PROMPTLY WITH WATER. IF ANY CONCRETE MIXTURES GET INTO EYES, RINSE IMMEDIATELY AND REPEATEDLY WITH WATER AND GET PROMPT MEDICAL ATTENTION.
KEEP OUT OF REACH OF CHILDREN • SEE REVERSE SIDE FOR MSDS SHEET

NOTICE: EXCESSIVE UNLOADING TIME
 • A HOLDING CHARGE OF \$1.50 PER MINUTE WILL BE INCLUDED FOR EACH TRUCK HELD ON THE JOB SITE FOR MORE THAN 60 MINUTES.
 • IN CONSIDERATION OF OUR MAKING DELIVERY ACROSS THE STREET CURB, AT YOUR REQUEST, CUSTOMER AGREES TO BE RESPONSIBLE FOR ALL DAMAGE DONE TO SIDEWALKS, DRIVEWAYS, BUILDINGS, GROUNDS, ETC. CUSTOMER ACKNOWLEDGES RECEIPT OF THE ABOVE MATERIALS IN APPROVED CONDITION.

IMPORTANT: PURCHASER ASSUMES FULL RESPONSIBILITY FOR STRENGTH, SLUMP AND QUALITY OF CONCRETE WHEN WATER OR OTHER MATERIALS ARE ADDED ON THE JOB SITE AT THE REQUEST OF THE CUSTOMER.

OUT SIDE TEMP.	TOTAL	\$1,065.00				
	OTHER CHARGES	\$69.23				
	ADDITIONAL TAX	\$1,134.23				
	GRAND TOTAL	1134.23				
WATER ADDED ON JOB AT REQUEST OF CONSIGNEE	GALS. WATER	INT.	GALS. WATER	INT.	GALS. WATER	INT.
TEST TAKEN	SLUMP / AIR / CYLS.	PER ASTM SPECS.	YES	NO		

ACCEPTED BY: _____
 PURCHER'S SIGNATURE, HIS AGENT, OR HIS EMPLOYEE'S SIGNATURE CONSTITUTES AN AGREEMENT WITH THE ABOVE TERMS AND CONDITIONS.

DRIVER REMARKS: _____

400063491

AE Change 12/19

MATERIAL SAFETY DATA SHEET

(Only Applicable Data Provided for Each Section)

SECTION I		Manufacturer's Name: Concrete Materials Company		Emergency Telephone Number: See Reverse Side	
Address: See Reverse Side				Trade Names:	
Chemical Family:		3CaO SiO ₂ (cement), 2CaO SiO ₂ (cement), 3CaO A12O ₃ (cement)			
SECTION II - HAZARDOUS INGREDIENTS: Cement and possible traces of hexavalent chromium.		4CaO A12O ₃ (cement), CaSO ₄ 2H ₂ O, Traces Cao, MgO, K ₂ SO ₄ , Na ₂ SO ₄			
SECTION III - PHYSICAL DATA					
Specific Gravity: 1.9 to 2.4		Solubility in Water: 0.1 to 1.0%			
Appearance and Odor: Gray plastic, flowable, granular, mud, odorless					
SECTION IV - FIRE AND EXPLOSION HAZARD DATA: N.A. all sections					
SECTION V - HEALTH HAZARD DATA					
TLV: None		Effects of Overexposure:		Dry skin and possible alkali burns (cement dermatitis). Also possible traces of hexavalent chromium.	
Emergency First Aid Procedures:		Irrigate eyes with water. Wash affected areas of the body with soap and water.			
SECTION VI - REACTIVITY DATA					
Stability	Unstable X	Conditions to Avoid:		Product sets and hardens in 2 to 8 hours, and is no longer hazardous	
	Hazardous Polymerization			Will Not Occur X	
SECTION VII - SPILL OR LEAK PROCEDURES					
Steps to be Taken in Case Material is Released or Spilled: Spill does not increase hazard.					
Waste Disposal Method: Once hardened, material can be disposed of as common waste.					
SECTION VIII - SPECIAL PROTECTION INFORMATION					
Protective Gloves: Yes		Eye Protection: Yes, when placement methods cause splashing. Use barrier creams, gloves, boots, and clothing to protect skin from prolonged contact with plastic concrete.			
Other Protective Equipment:					
SECTION IX - SPECIAL PRECAUTIONS					
Precautions to be Taken in Handling and Storage: See above.					
Other Precautions: Immediately after working with concrete, workers should shower with soap and water.					

GRAND TOTAL	WATER	WATER	WATER	WATER	WATER
11.845	1.000	1.000	1.000	1.000	1.000
11.845	1.000	1.000	1.000	1.000	1.000

WICHITA KANSAS 67218

F.O. BOX 18304

CONCRETE MATERIALS COMPANY

Dispatch (316) 522-4949
 El Dorado (316) 320-5000
 Office (316) 522-8454



400063494



PLANT	TICKET TIME	DATE	ORDER #	TRUCK	DRIVER	TIME DUE	TICKET #
4	13:03	12/19/22	46	665	SCOTT WATSON	14:03	028738

CUSTOMERS INFO

DELIVERY ADDRESS INSTRUCTIONS

JOHN DARRAH FROM NORTH OF EL DORADO EXIT THE TURNPIKE GO NORTH ON HWY 77 TOWARD NORTH OF WALTERS PUMPKIN PATCH GO A MILE NORTH OF 110 FOLLOW PLAN ON USING THE SAME TRUCK THE LEASE ROAD

PURCHASE ORDER	PROJECT #	PROJECT DESC.	MAP PAGE	PREV TRUCK #	SLUMP	USAGE
PAID CREDIT	1004	EASTERN KANSAS VARIO			8.00	OTHER

LOAD QTY.	PRODUCT	DESCRIPTION	ORDERED	DELIVERED	UNIT PRICE	AMOUNT
5.00 yd	JY3500	SLURRY MIX	5.00	5.00	\$169.00	\$845.00
1.00 EA	350FSC	Fuel Surcharge RMX	0.00		\$21.00	\$21.00
5.00 /y	WS	WINTER SERVICE CHARGE	0.00		\$5.00	\$25.00

LEAVE PLANT	ARRIVE JOB SITE	START DISCHARGE	FINISH DISCHARGE	ARRIVE PLANT	SUBTOTAL

OUT SIDE TEMP.	TAX	\$891.00
	TOTAL	\$57.92
	OTHER CHARGES	\$948.92
	ADDITIONAL TAX	
	GRAND TOTAL	948.98

CAUTION: FRESHLY MIXED CONCRETE MAY CAUSE SKIN IRRITATION OR CHEMICAL BURNS. AVOID CONTACT WITH SKIN WHERE POSSIBLE AND WASH EXPOSED SKIN AREAS PROMPTLY WITH WATER. IF ANY CONCRETE MIXTURES GET INTO EYES, RINSE IMMEDIATELY AND REPEATEDLY WITH WATER AND GET PROMPT MEDICAL ATTENTION. **KEEP OUT OF REACH OF CHILDREN • SEE REVERSE SIDE FOR MSDS SHEET**

NOTICE: EXCESSIVE UNLOADING TIME
 • A HOLDING CHARGE OF \$1.50 PER MINUTE WILL BE INCLUDED FOR EACH TRUCK HELD ON THE JOB SITE FOR MORE THAN 60 MINUTES.
 • IN CONSIDERATION OF OUR MAKING DELIVERY ACROSS THE STREET CURB, AT YOUR REQUEST, CUSTOMER AGREES TO BE RESPONSIBLE FOR ALL DAMAGE DONE TO SIDEWALKS, DRIVEWAYS, BUILDINGS, GROUNDS, ETC. CUSTOMER ACKNOWLEDGES RECEIPT OF THE ABOVE MATERIALS IN APPROVED CONDITION.

IMPORTANT: PURCHASER ASSUMES FULL RESPONSIBILITY FOR STRENGTH, SLUMP AND QUALITY OF CONCRETE WHEN WATER OR OTHER MATERIALS ARE ADDED ON THE JOB SITE AT THE REQUEST OF THE CUSTOMER.

WATER ADDED ON JOB AT REQUEST OF CONSIGNEE	GALS. WATER	GALS. WATER	GALS. WATER
	INT.	INT.	INT.
TEST TAKEN	SLUMP / AIR / CYLS.	PER ASTM SPECS.	YES NO

ACCEPTED BY: _____
 PURCHER'S SIGNATURE, HIS AGENT, OR HIS EMPLOYEE'S SIGNATURE CONSTITUTES AN AGREEMENT WITH THE ABOVE TERMS AND CONDITIONS.

DRIVER REMARKS: _____

400063494

AE Charge 12/19

MATERIAL SAFETY DATA SHEET

(Only Applicable Data Provided for Each Section)

SECTION I	
Manufacturer's Name: Concrete Materials Company Address: See Reverse Side	Emergency Telephone Number: See Reverse Side Trade Names:
Chemical Family: 3CaO SiO ₂ (cement), 2CaO SiO ₂ (cement), 3CaO A12O ₃ (cement) 4CaO A12O ₃ (cement), CaSO ₄ 2H ₂ O, Traces CaO, MgO, K ₂ SO ₄ , Na ₂ SO ₄	
SECTION II - HAZARDOUS INGREDIENTS: Cement and possible traces of hexavalent chromium.	
SECTION III - PHYSICAL DATA	
Specific Gravity: 1.9 to 2.4	Solubility in Water: 0.1 to 1.0%
Appearance and Odor: Gray, plastic, flowable, granular, mud, odorless	
SECTION IV - FIRE AND EXPLOSION HAZARD DATA: N.A. all sections	
SECTION V - HEALTH HAZARD DATA	
TLV: None	Effects of Overexposure: Dry skin and possible alkali burns (cement dermatitis). Also possible traces of hexavalent chromium.
Emergency First Aid Procedures:	Irrigate eyes with water. Wash affected areas of the body with soap and water.
SECTION VI - REACTIVITY DATA	
Stability	Unstable X
Conditions to Avoid: Product sets and hardens in 2 to 8 hours, and is no longer hazardous	
Hazardous Polymerization	
Will Not Occur X	
SECTION VII - SPILL OR LEAK PROCEDURES	
Steps to be Taken in Case Material is Released or Spilled: Spill does not increase hazard.	
Waste Disposal Method: Once hardened, material can be disposed of as common waste.	
SECTION VIII - SPECIAL PROTECTION INFORMATION	
Protective Gloves: Yes	Eye Protection: Yes, when placement methods cause splashing. Use barrier creams, gloves, boots, and clothing to protect skin from prolonged contact with plastic concrete.
Other Protective Equipment:	
SECTION IX - SPECIAL PRECAUTIONS	
Precautions to be Taken in Handling and Storage: See above.	
Other Precautions: Immediately after working with concrete, workers should shower with soap and water.	

AF CHM-12/11

REVERSE SIDE

CONCRETE MATERIALS COMPANY

P.O. BOX 16200

WICHITA, KANSAS 67218

Dispatch (316) 522-4949
 El Dorado (316) 320-5000
 Office (316) 522-8454



400063497



PLANT	TICKET TIME	DATE	ORDER #	TRUCK	DRIVER	TIME DUE	TICKET #
4	8:16	12/20/22	37	653	GARY HURLEY	8:52	4028741

CUSTOMERS INFO

DELIVERY ADDRESS INSTRUCTIONS

JOHN DARRAH

BLUESTEM AND SEBOTH GO WEST TOLICKTIEG

BLUESTEM AND BOTH

Slump 8.00

PURCHASE ORDER	PROJECT #	PROJECT DESC.	MAP PAGE	PREV TRUCK #	SLUMP	USAGE
PAID CREDIT	1004	EASTERN KANSASVARIO			8.00	OTHER
LOAD QTY.	PRODUCT	DESCRIPTION	ORDERED	DELIVERED	UNIT PRICE	AMOUNT

5.00 yd	JY3500	SLURRY MIX	5.00	5.00	\$169.00	\$845.00
1.00 EA	350FSC	Fuel Surcharge RMX	0.00		\$21.00	\$21.00
5.00 /y	WS	WINTER SERVICE CHARGE	0.00		\$5.00	\$25.00

LEAVE PLANT	ARRIVE JOB SITE	START DISCHARGE	FINISH DISCHARGE	ARRIVE PLANT	SUBTOTAL

TAX	\$891.00
TOTAL	\$57.92
OTHER CHARGES	\$948.92
ADDITIONAL TAX	
GRAND TOTAL	948.92

CAUTION: FRESHLY MIXED CONCRETE MAY CAUSE SKIN IRRITATION OR CHEMICAL BURNS.
 AVOID CONTACT WITH SKIN WHERE POSSIBLE AND WASH EXPOSED SKIN AREAS PROMPTLY WITH WATER. IF ANY CONCRETE MIXTURES GET INTO EYES, RINSE IMMEDIATELY AND REPEATEDLY WITH WATER AND GET PROMPT MEDICAL ATTENTION.
KEEP OUT OF REACH OF CHILDREN • SEE REVERSE SIDE FOR MSDS SHEET

NOTICE: EXCESSIVE UNLOADING TIME
 • A HOLDING CHARGE OF \$1.50 PER MINUTE WILL BE INCLUDED FOR EACH TRUCK HELD ON THE JOB SITE FOR MORE THAN 60 MINUTES.
 • IN CONSIDERATION OF OUR MAKING DELIVERY ACROSS THE STREET CURB, AT YOUR REQUEST, CUSTOMER AGREES TO BE RESPONSIBLE FOR ALL DAMAGE DONE TO SIDEWALKS, DRIVEWAYS, BUILDINGS, GROUNDS, ETC. CUSTOMER ACKNOWLEDGES RECEIPT OF THE ABOVE MATERIALS IN APPROVED CONDITION.

IMPORTANT: PURCHASER ASSUMES FULL RESPONSIBILITY FOR STRENGTH, SLUMP AND QUALITY OF CONCRETE WHEN WATER OR OTHER MATERIALS ARE ADDED ON THE JOB SITE AT THE REQUEST OF THE CUSTOMER.

WATER ADDED ON JOB AT REQUEST OF CONSIGNEE	GALS. WATER	GALS. WATER	GALS. WATER
	INT.	INT.	INT.
TEST TAKEN	SLUMP / AIR / CYLS.	PER ASTM SPECS.	YES NO

ACCEPTED BY: _____
 PURCHER'S SIGNATURE, HIS AGENT, OR HIS EMPLOYEE'S SIGNATURE CONSTITUTES AN AGREEMENT WITH THE ABOVE TERMS AND CONDITIONS.

DRIVER REMARKS: _____

400063497

Pending on 12/20

MATERIAL SAFETY DATA SHEET

(Only Applicable Data Provided for Each Section)

SECTION I	
Manufacturer's Name: Concrete Materials Company Address: See Reverse Side	Emergency Telephone Number: See Reverse Side Trade Names:
Chemical Family: 3CaO SiO ₂ (cement), 2CaO SiO ₂ (cement), 3CaO A12O ₃ (cement) 4CaO A12O ₃ (cement), CaSO ₄ 2H ₂ O, Traces CaO, MgO, K ₂ SO ₄ , Na ₂ SO ₄	
SECTION II - HAZARDOUS INGREDIENTS: Cement and possible traces of hexavalent chromium.	
SECTION III - PHYSICAL DATA	
Specific Gravity: 1.9 to 2.4	Solubility in Water: 0.1 to 1.0%
Appearance and Odor: Gray plastic, flowable, granular, mud, odorless	
SECTION IV - FIRE AND EXPLOSION HAZARD DATA: N.A. all sections	
SECTION V - HEALTH HAZARD DATA	
TLV: None	Effects of Overexposure: Dry skin and possible alkali burns (cement dermatitis). Also possible traces of hexavalent chromium.
Emergency First Aid Procedures: Irrigate eyes with water. Wash affected areas of the body with soap and water.	
SECTION VI - REACTIVITY DATA	
Stability	Unstable X
Conditions to Avoid:	Product sets and hardens in 2 to 8 hours, and is no longer hazardous
Hazardous Polymerization	Will Not Occur X
SECTION VII - SPILL OR LEAK PROCEDURES	
Steps to be Taken in Case Material is Released or Spilled: Spill does not increase hazard.	
Waste Disposal Method: Once hardened, material can be disposed of as common waste.	
SECTION VIII - SPECIAL PROTECTION INFORMATION	
Protective Gloves: Yes	Eye Protection: Yes, when placement methods cause splashing. Use barrier creams, gloves, boots, and clothing to protect skin from prolonged contact with plastic concrete.
Other Protective Equipment:	
SECTION IX - SPECIAL PRECAUTIONS	
Precautions to be Taken in Handling and Storage: See above.	
Other Precautions: Immediately after working with concrete, workers should shower with soap and water.	

<p style="font-size: 2em; opacity: 0.5;">5P31P</p>	<p style="font-size: 2em; opacity: 0.5;">REMARKS</p>
----------------------------------------------------	------------------------------------------------------

4006197

WILKINSON

P.O. BOX 10504

CONCRETE MATERIALS COMPANY

AJ's Services, LLC
PO Box 1118
El Dorado, KS 67042
316-322-0000
contact@ajsservices.net
www.AJsServices.net



INVOICE

BILL TO

Darrah Oil Company, L.L.C.
PO Box 2786
Wichita, KS 67202

INVOICE # 23877

DATE 12/20/2022

DUE DATE 01/19/2023

TERMS Net 30

LOCATION

Pickett #6

DATE	ACTIVITY	WORK PERFORMED	QTY	RATE	AMOUNT
12/19/2022	Pulling Unit	DTL, rigged up, rigged up sand pump, bailed water down, cemented top plug, rigged down, DTNL	2	225.00	450.00T
12/19/2022	Bailer Tool	Bailer Tool	1	75.00	75.00

Pulling Unit Crew
Op: George
H: Mikey
H: Jeremiah

SUBTOTAL 525.00
TAX 29.25
TOTAL 554.25
BALANCE DUE **\$554.25**