KOLAR Document ID: 1679340

**Notice:** Fill out COMPLETELY and return to Conservation Division at the address below within 60 days from plugging date.

### KANSAS CORPORATION COMMISSION OIL & GAS CONSERVATION DIVISION

#### WELL PLUGGING RECORD K.A.R. 82-3-117

Form CP-4
March 2009
Type or Print on this Form
Form must be Signed
All blanks must be Filled

OPERATOR: License #:			APIN	No. 15			
Name:							
Address 1:				Sec			
				Feet fron			
City:	State	:		Feet fron			
Contact Person:			Foota	ages Calculated from Nea	rest Outside Section Corner:		
Phone: ( )				NE NW	SE SW		
Type of Well: (Check one) Oil Well Gas Well OG D&A Cathodic  Water Supply Well Other: SWD Permit #:  ENHR Permit #: Gas Storage Permit #:  Is ACO-1 filed? Yes No If not, is well log attached? Yes No				County: Well #: Well #: The plugging proposal was approved on: (Date			
Producing Formation(s):	List All (If needed attach a	another sheet)	by:		(KCC <b>District</b> Agent's Name)		
De	epth to Top:	Bottom: T.D	Plugo	ring Commenced:			
De	epth to Top:	Bottom: T.D	"	, ,			
De	epth to Top:	Bottom:T.D		,g • •p. • . • . • . • . • . • . • .			
	ss of all water, oil and gas	s formations.					
	Water Records			(Surface, Conductor & Prod			
Formation	Content	Casing	Size	Setting Depth	Pulled Out		
		plugged, indicating where the			nods used in introducing it into the hole. If		
Plugging Contractor Lice	ense #:		Name:				
Address 1:			Address 2:				
City:			State	:			
Phone: ( )							
Name of Party Responsi	ible for Plugging Fees:						
State of	Co	unty,	, SS.				
				Employee of Operator of	or Operator on above-described well,		
	(Print Na			=pio,oo oi opoiatoi o	operator on above described well,		

being first duly sworn on oath, says: That I have knowledge of the facts statements, and matters herein contained, and the log of the above-described well is as filed, and the same are true and correct, so help me God.

### AJ's Services, LLC

PO Box 1118 El Dorado, KS 67042 316-322-0000 contact@ajsservices.net www.AJsServices.net

# AJs Services

### **INVOICE**

**BILL TO** 

Darrah Oil Company, L.L.C.

PO Box 2786 Wichita, KS 67202 INVOICE # 23866

**DATE** 12/19/2022 **DUE DATE** 01/18/2023

TERMS Net 30

### **LOCATION**

Janzen B2 Inj

DATE	ACTIVITY	WORK PERFORMED		QTY	RATE	AMOUNT	
12/16/2022	Pulling Unit	DTL, set plug at 260' with sand of sand ontop of plug, dump ba cement, rigged down, DTNL		5	225.00	1,125.00T	
12/16/2022	Sand Line Tool	Sand Tool Rental		1	200.00	200.00	
12/16/2022	Bailer Tool	Bailer Tool		1	200.00	200.00	
Pulling Unit Crev	N	SUBT	OTAL			1,525.00	
Op: George		TAX				73.13	
H: Mikey		TOTA	TOTAL		1,598.13		
H: Jeremiah		BALA	NCE DUE	\$1,598.13			

### Mike's Testing & Salvage Inc.

DBA Kelso Well Service P.O. Box 467 Chase, KS 67524

# Invoice

Date	Invoice #
12/14/2022	18544

Bill To	
Darrah Oil Company LLC	
125 N. Market Street	
Suite 1425	
Wichita, Kansas 67202	

P.O. No.	County	Lease	
Felix - Rig#1	Butler	Janzen	

Qty	Description	Rate	Amount
	Hours Rig Time Casing Cutter Night Out of Town	265.00 500.00 300.00	500.00T
	Moved to location, set in rig and rigged up, ran in bailer, T.D. @2550', sanded off bottom to 2400', dumped 4 sacks cement with bailer. Dug out cellar and pit, set in floor and rigged up, pulled 16" of stretch. Cut casing loose @1830'. 8 Hrs.  12-8-22  Laid down casing, bailed surface down to 250', tore down rig and moved off. 5 Hours Not Plugged  Sales Tax	6.75%	286.54
	in the second se		
		44	T 8 7 47 4 4 140

Total

\$4,531.54

### AJ's Services, LLC

PO Box 1118 El Dorado, KS 67042 316-322-0000 contact@ajsservices.net www.AJsServices.net



### **INVOICE**

**BILL TO** 

Darrah Oil Company, L.L.C.

PO Box 2786 Wichita, KS 67202 **INVOICE #** 23879

**DATE** 12/20/2022 **DUE DATE** 01/19/2023

TERMS Net 30

### **LOCATION**

Janzen B2 Inj

DATE	ACTIVITY	WORK PERFORMED	QTY	RATE	AMOUNT	
12/19/2022	Pulling Unit	DTL, rigged up, rigged up sand pum water down, cemented top plug, rigg DTNL		225.00	450.00T	
12/19/2022	Bailer Tool	Bailer Tool	1	75.00	75.00	
Pulling Unit Crev		SUBTOTA	 \L		525.00	
Op: George		TAX			29.25	
H: Mikey		TOTAL			554.25	
H: Jeremiah		BALANCE	DUE	\$	554.25	



300033469



ANT ORDER # TICKET # TIME DUE DELIVERY ADDRESS INSTRUCTIONS URCHASE ORDER PROJECT # PROJECT DESC MAP PAGE PREV TRUCK # SLUMP USAGE LOAD QTY. PRODUCT DESCRIPTION ORDERED DELIVERED UNIT PRICE 9.00 9.00 \$169.00 \$5.00 ARRIVE JOB SITE ARRIVE PLANT \$103.16 SUBTOTAL TAX TOTAL OUT SIDE TEMP. CAUTION: FRESHLY MIXED CONCRETE MAY CAUSE SKIN IRRITATION OR CHEMICAL BURNS. OTHER CHARGES AVOID CONTACT WITH SKIN WHERE POSSIBLE AND WASH EXPOSED SKIN AREAS PROMPTLY ADDITIONAL TAX WITH WATER. IF ANY CONCRETE MIXTURES GET INTO EYES, RINSE IMMEDIATELY AND REPEATEDLY WITH WATER AND GET PROMPT MEDICAL ATTENTION. 690. 6 KEEP OUT OF REACH OF CHILDREN . SEE REVERSE SIDE FOR MSDS SHEET GRAND TOTAL NOTICE: EXCESSIVE UNLOADING TIME · A HOLDING CHARGE OF \$1.50 PER MINUTE WILL BE INCLUDED FOR EACH TRUCK HELD ON THE JOB SITE FOR MORE THAN 60 MINUTES. WATER GALS GALS GALS ADDED ON WATER WATER WATER · IN CONSIDERATION OF OUR MAKING DELIVERY ACROSS THE STREET CURB, AT YOUR JOB AT REQUEST REQUEST, CUSTOMER AGREES TO BE RESPONSIBLE FOR ALL DAMAGE DONE TO SIDEWALKS, OF CONSIGNEE INT DRIVEWAYS, BUILDINGS, GROUNDS, ETC. CUSTOMER ACKNOWLEDGES RECEIPT OF THE ABOVE MATERIALS IN APPROVED CONDITION. TEST SLUMP / AIR CYLS. PER ASTM YES NO PURCHASER ASSUMES FULL RESPONSIBILITY FOR STRENGTH, SLUMP AND QUALITY OF CON-TAKEN PORTANT: SPECS CRETE WHEN WATER OR OTHER MATERIALS ARE ADDED ON THE JOB SITE AT THE REQUEST CCEPTED DRIVER REMARKS:

PURCHASER S SIGNATURE, HIS AGENT, OR HIS EMPLOYEE S SIGNATURE CONSTITUTES AN AGREEMENT WITH THE ABOVE TERMS AND CONDITIONS.

Wolfers B18

300033469

AE Churrose 12/09

### (Only Applicable Data Provided for Each Section) MATERIAL SAFETY DATA SHEET

Other Protective Equipment: from prolonged contact with plastic concrete.

SECTION IX. - SPECIAL PRECAUTIONS
Precautions to be Taken in Handling and Storage. See above.

Other Precautions: immediately after, working with concrete, workers should shower with soap and water Use barrier creams, gloves, boots, and clothing to protect skin from prolonged contact with plastic concrete. Hazardous
Polymerization
Polymerization
SECTION VII - SPILL OR LEAK PROCEDURES
Waste Disposal Method, Once hadened, malenal can be disposed of as common waste.
SECTION VIII - SPECIAL PROTECTION INFORMATION
Protective Cloves: Yes
| Eye Protective Town Weste. | Eye Protection: Yes, when placement and the protective Cloves: Yes | Eye Protective Cloves: Yes | Eye Protection: Yes, when placement and the protective Equipment. and is no longer hazardous
Will Not Occur TLV None Effects of Overexposure: Also possible traces of hexavalent chromium. Emergency First Aid Procedures: Imgate eyes with water. Wash affected areas of the body with scap and water. Appearance and Odor. Gray pleatic, flowable, granular, mud, odorfess SECTION W. FITHE AND EXPLOSION HAZARD DATA: N.A. all sections SECTION V. HEALTH HAZARD DATA. Chemical Family.

Germent), SCao Sioz (cement), SCao Sioz (cement)

0

Dispatch (316) 522-4949 El Dorac (316) 320-5000 Office (316) 522-8454



PLANT TICKET TIME DATE ORDER# DRIVER TICKET# CUSTOMERS INFO PROJECT # MAP PAGE PREV TRUCK # SLUMP USAGE LOAD QTY. DESCRIPTION ORDERED UNIT PRICE AMOUNT WINTER SERVICE CHARGE FINISH DISCHARGE START DISCHARGE ARRIVE PLANT SUBTOTAL TAX TOTAL OUT SIDE TEMP CAUTION: FRESHLY MIXED CONCRETE MAY CAUSE SKIN IRRITATION OR CHEMICAL BURNS. OTHER CHARGES 1.134.23 AVOID CONTACT WITH SKIN WHERE POSSIBLE AND WASH EXPOSED SKIN AREAS PROMPTLY ADDITIONAL TAX WITH WATER. IF ANY CONCRETE MIXTURES GET INTO EYES, RINSE IMMEDIATELY AND RE-PEATEDLY WITH WATER AND GET PROMPT MEDICAL ATTENTION. KEEP OUT OF REACH OF CHILDREN . SEE REVERSE SIDE FOR MSDS SHEET GRAND TOTAL NOTICE: EXCESSIVE UNLOADING TIME · A HOLDING CHARGE OF \$1.50 PER MINUTE WILL BE INCLUDED FOR EACH TRUCK HELD WATER GALS ON THE JOB SITE FOR MORE THAN 60 MINUTES. GALS GALS ADDED ON WATER WATER WATER · IN CONSIDERATION OF OUR MAKING DELIVERY ACROSS THE STREET CURB, AT YOUR JOB AT REQUEST REQUEST, CUSTOMER AGREES TO BE RESPONSIBLE FOR ALL DAMAGE DONE TO SIDEWALKS, OF CONSIGNEE DRIVEWAYS, BUILDINGS, GROUNDS, ETC. CUSTOMER ACKNOWLEDGES RECEIPT OF THE ABOVE MATERIALS IN APPROVED CONDITION.

ACCEPTED

OF THE CUSTOMER

BY

PURCHER'S SIGNATURE, HIS AGENT, OR HIS EMPLOYEE'S SIGNATURE CONSTITUTES AN AGREEMENT WITH THE ABOVE TERMS AND CONDITIONS.

IMPORTANT: PURCHASER ASSUMES FULL RESPONSIBILITY FOR STRENGTH, SLUMP AND QUALITY OF CON-

CRETE WHEN WATER OR OTHER MATERIALS ARE ADDED ON THE JOB SITE AT THE REQUEST

400063487

PER ASTM

SPECS

YES NO

AE Charge 12/19

TEST

TAKEN

DRIVER

REMARKS:

SLUMP / AIR

/ CYLS

SECTION I	10 10 10 10 10 10 10 10 10 10 10 10 10 1
Manufacturer s Name: Concrete Materials Company	Emergency Telephone Number: See Reverse Side
Address: See Reverse Side	Trade Names:
	Cao Slo2 (cement), 3Cao A1203 (cement)
	4 2H2O, Traces Cao, MgO, K2SO4, Na 2SO4
SECTION II - HAZARDOUS INGREDIENTS: Cement and possible traces of hexavalent chromium.	
SECTION III- PHYSICAL DATA	
Specific Gravity: 1,9 to 2,4	Solubility in Water: 0.1 to 1.0%
Appearance and Odor: Gray, plastic, flowable, granular, mud, odorless	
SECTION IV- FIRE AND EXPLOSION HAZARD DATA: N.A. all sections	
SECTION V - HEALTH HAZARD DATA	
	in and possible alkali burns (cement dermatitis).
	ossible traces of hexavalent chromium.
Emergency First Aid Procedures: Irrigate eyes with water. Wash affected areas of the body with	soap and water.
SECTION VI - REACTIVITY DATA	
Unstable Produc	at sets and hardens in 2 to 8 hours,
Stability X Conditions to Avoid: and is	no longer hazardous
Hazardous Will Not 0	Occur
Polymerization X	
SECTION VII - SPILL OR LEAK PROCEDURES	
Steps to be Taken in Case Material is Released or Spilled: Spill does not increase hazard.	
Waste Disposal Method: Once hardened, material can be disposed of as common waste.	
SECTION VIII - SPECIAL PROTECTION INFORMATION	
Protective Gloves: Yes Eye Protection: Yes, when placement methods	cause splashing.
Use barrier creams, gloves, boots, and clothing	to protect skin
Other Protective Equipment: from prolonged contact with plastic concrete.	
SECTION IX - SPECIAL PRECAUTIONS	
Precautions to be Taken in Handling and Storage: See above.	
Other Precautions: Immediately after, working with concrete, workers should shower with soap and we	ater.

Dispate (216) 522-4949 El Dorado (316) 320-5000 Office (316) 522-8454



PLANT	TICKET TIME	DATE	ORDER#	TRUCK	DRIVER	TIME OF THE	IE DUE	TICKET#	
4	7:37	12/19	A house has been do	665	SCOTT A	almanne	8:30	40287	32
	NAME OF TAXABLE PARTY.	CUSTOMERS IN					DRESS INSTRUCT		
				TYW ZZ & NE		RAFF) G	D WEST	ON	
			Accommodel .	VISIDE LOOP	FORRIG				
	7 NO	CHARGE							
PURCHASE ORD	and the second second	PROJECT#	PROJECT DES	SC.	MAP PAGE	PREV	TRUCK# SLU	UMP US.	AGE
		20323	WASTE	/ TEST LOA	ns I		A	00 H	
LOAD QTY.	PRO	DUCT	DESCRIPT		ORDERED		DELIVERED	UNIT PRICE AMOI	
3.1	00 yd J	1Y3500	. SLURRY N	MIX malanta water	3.00	3.00			
		50FSC		charge RMX			Color Color		
3.1	00 / 4 . 4	18	WINTER S	BERVICE CHA	ARGE 0.00				
LEAVE PL	ANT AF	RRIVE JOB SITE	START DISCHARGE	FINISH DISCHARG	GE ARRIVE PLA	ANT SUBTO	AL		
			15/00			TAX			
					OUT SIDE T	TEMP. TOTAL			
CAUTION:			Y CAUSE SKIN IRRITATIO				CHARGES		
	WITH WATER. IF	ANY CONCRETE MIX	OSSIBLE AND WASH EXPO TURES GET INTO EYES, F	RINSE IMMEDIATELY AND		ADDITIO	ONAL TAX		
			OMPT MEDICAL ATTENTION  OREN • SEE REVERSE		EET			G	_
NOTICE:	EXCESSIVE UNLO	DADING TIME				GRAN	D TOTAL	TIM	16
		FOR MORE THAN 60	ER MINUTE WILL BE INCLUI MINUTES.	DED FOR EACH TRUCK HI	WATER		GALS.	GALS.	GALS.
			KING DELIVERY ACROSS T			UEST > -	WATER	WATER	WATER
			RESPONSIBLE FOR ALL DA			NEE (	INT.	INT.	INT
	ABOVE MATERIAL	S IN APPROVED CO	NDITION.		TEST		, ,		
MPORTANT:			SIBILITY FOR STRENGTH,			SLL	IMP / AIR /	CYLS. PER ASTI SPECS.	M YES NO
	OF THE CUSTOM		ERIALS ARE ADDED ON TH	E JOB SITE AT THE REQU	EST L			New York Control of the Control of t	
ACCEPTED			-1		DRIVER				
BY:				(7)	REMARKS				
PURCHER'	S SIGNATURE, HIS ABOVE TERMS AN		PLOYEE'S SIGNATURE CO	DNSTITUTES AN AGREEM	IENT		SERVICE TO		
- win ine	ALOVE TERINO AN	D CONDITIONS.							

400063488

% Moisture

SECTION I		10 10 10 10 10 10 10 10 10 10 10 10 10 1					
Manufacturer s Name: Concrete Materials Compa	ny	Emergency Telephone Number: See Reverse Side					
Address: See Reverse Side		Trade Names:					
		2 (cement), 2Cao Sio2 (cement), 3Cao A1203 (cement)					
Chemical Family:		ement), Caso4 2H2O, Traces Cao, MgO, K2SO4, Na 2SO4					
SECTION II - HAZARDOUS INGREDIENTS: Ceme	nt and possible traces of hexavalent chro	chromium.					
SECTION III- PHYSICAL DATA	KIN AND						
Specific Gravity: 1.9 to 2.4		Solubility in Water: 0.1 to 1.0%					
Appearance and Odor: Gray, plastic, flowable, gran							
SECTION IV- FIRE AND EXPLOSION HAZARD DA	TA: N.A. all sections						
SECTION V - HEALTH HAZARD DATA							
		Dry skin and possible alkali burns (cement dermatitis).					
TLV: None Effects of Overexposure		Also possible traces of hexavalent chromium.					
	es with water. Wash affected areas of the	the body with soap and water.					
SECTION VI - REACTIVITY DATA							
Unstable	CONTRACTOR OF THE PROPERTY OF	Product sets and hardens in 2 to 8 hours,					
Stability X	Conditions to Avoid:	and is no longer hazardous					
Hazardous		Will Not Occur					
Polymerizati	on	X					
SECTION VII - SPILL OR LEAK PROCEDURES							
Steps to be Taken in Case Material is Released or S							
Waste Disposal Method: Once hardened, material							
SECTION VIII - SPECIAL PROTECTION INFORMA							
Protective Gloves: Yes	Eye Protection: Yes, when placement						
Use barrier creams, gloves, boots, and clothing to protect skin							
Other Protective Equipment: from prolonged contact with plastic concrete.							
SECTION IX - SPECIAL PRECAUTIONS							
Precautions to be Taken in Handling and Storage: S							
Other Precautions: Immediately after, working with	concrete, workers should shower with so	soap and water.					

Dispate (316) 522-4949 El Dorado 320-5000 Office (316) 522-8454



PLANT ICKET TIME DATE ORDER# DRIVER TICKET # DELIVERY ADDRESS INSTRUCTIONS

HUHASE	ONDEN	PHOJECI#	PHOJECT DESC.		WAFFAGE	FREV TRUCK #	SLUWF	USAGE	
PAI	D CREDIT	1004	EASTERN	KANSASVARIO		665	8.00	OTHER	
LOAD QT	Y. PF	RODUCT	DESCRIPTION		ORDERED	DELIVERED	UNIT PRICE	AMOUNT	
					THE ROBERT OF PURPLE			TO SET IN	
	F ChiCh and	TVDEOG C	LIDDY MIN		0 00 10	000 43	CC COCK 1	COLLA COLCA	

6.00 yd JY	/3500 SLI	JRRY MIX	12.	00 12.0	0 \$16	9.00 1.0	114.00
1.00 EA 35	MFSC Fae	1 Surcharge F	RMX Ø.	(10)	\$2:	1.00 1	21.00
6.00 /y WS	Win	TER SERVICE O	CHARGE Ø.	00	\$	5.00	30.00

LEAVE PLANT		ARRIVE JOB SITE	START DISCHARGE	FINISH DISCHARGE	ARRIVE PLANT	SUBTOTAL		
			21/12/109			TAX	\$1,065.00	
					OUT SIDE TEMP.	TOTAL	\$69.23	
CAUTION:	FRESHLY	MIXED CONCRETE MA	AY CAUSE SKIN IRRITATION	OR CHEMICAL BURNS.		OTHER CHARGES	\$1,134.23	
	AVOID CON	TACT WITH SKIN WHERE	POSSIBLE AND WASH EXPOSI	ED SKIN AREAS PROMPTLY		ADDITIONAL TAX	Pig Inter Ed	
WITH WATER. IF ANY CONCRETE MIXTURES GET INTO EYES, RINSE IMMEDIATELY AND RE- PEATEDLY WITH WATER AND GET PROMPT MEDICAL ATTENTION.						1		
						1(34,23	100	
KEEP OUT OF REACH OF CHILDREN . SEE REVERSE SIDE FOR MSDS SHEET						GRAND TOTAL	1177,45	
NOTICE:	EXCESSIVE UNLOADING TIME				GRAND TOTAL			
			PER MINUTE WILL BE INCLUDE	D FOR EACH TRUCK HELD	WATER	GALS.	GALS. GAL	c
	ON THE JC	B SITE FOR MORE THAN	60 MINUTES.		ADDED ON	WATER	WATER WAT	2000
	·INCO	NSIDERATION OF OUR M.	AKING DELIVERY ACROSS TH	E STREET CURB, AT YOUR	JOB AT REQUEST	>		-
	REQUEST,	CUSTOMER AGREES TO B	E RESPONSIBLE FOR ALL DAM	AGE DONE TO SIDEWALKS,	OF CONSIGNEE	/ INT.	INT.	INT.
DRIVEWAYS, BUILDINGS, GROUNDS, ETC. CUSTOMER ACKNOWLEDGES RECEIPT OF THE						(		-

TEST

TAKEN

DRIVER REMARKS:

ABOVE MATERIALS IN APPROVED CONDITION. IMPORTANT: PURCHASER ASSUMES FULL RESPONSIBILITY FOR STRENGTH, SLUMP AND QUALITY OF CON-

CRETE WHEN WATER OR OTHER MATERIALS ARE ADDED ON THE JOB SITE AT THE REQUEST

ACCEPTED BY:

PURCHER'S SIGNATURE, HIS AGENT, OR HIS EMPLOYEE'S SIGNATURE CONSTITUTES AN AGREEMENT WITH THE ABOVE TERMS AND CONDITIONS.

400063491

PER ASTM YES NO SPECS.

SLUMP AIR CYLS.

SECTION I	\$246 \( \delta \( \delta \) (1) (2)								
Manufacturer s Name: Concrete Materials Company Emergency Telephone Number: See Reverse Sid	e								
Address: See Reverse Side Trade Names:									
3CaO Sio2 (cement), 2Cao Sio2 (cement), 3Cao A1203 (cement)									
Chemical Family: 4Cao A1203 (cement), Caso4 2H2O, Traces Cao, MgO, K2SO4, Na 2SO4									
SECTION II - HAZARDOUS INGREDIENTS: Cement and possible traces of hexavalent chromium.									
SECTION III- PHYSICAL DATA									
Specific Gravity: 1.9 to 2.4 Solubility in Water: 0.1 to 1.0%									
Appearance and Odor: Gray, plastic, flowable, granular, mud, odorless									
SECTION IV- FIRE AND EXPLOSION HAZARD DATA: N.A. all sections									
SECTION V - HEALTH HAZARD DATA									
Dry skin and possible alkali burns (cement dermatitis).									
TLV: None Effects of Overexposure: Also possible traces of hexavalent chromium.									
Emergency First Aid Procedures: Irrigate eyes with water. Wash affected areas of the body with soap and water.									
SECTION VI - REACTIVITY DATA									
Unstable Product sets and hardens in 2 to 8 hours,	FEOR SAME								
Stability X Conditions to Avoid: and is no longer hazardous									
Hazardous Will Not Occur									
Polymerization X									
SECTION VII - SPILL OR LEAK PROCEDURES									
Steps to be Taken in Case Material is Released or Spilled: Spill does not increase hazard.									
Waste Disposal Method: Once hardened, material can be disposed of as common waste.									
SECTION VIII - SPECIAL PROTECTION INFORMATION									
Protective Gloves: Yes Eye Protection: Yes, when placement methods cause splashing.									
	se barrier creams, gloves, boots, and clothing to protect skin								
	from prolonged contact with plastic concrete.								
SECTION IX - SPECIAL PRECAUTIONS									
Precautions to be Taken in Handling and Storage: See above.  Other Precautions: Immediately after working with concrete workers should shower with soan and water.									

Dispatch (316) 522-4949 El Dorado (316) 320-5000 Office (316) 522-8454





PLANT TICKET TIME DATE ORDER# DRIVER TICKET# DELIVERY ADDRESS INSTRUCTIONS NORTH ON HWY 77TORD NORTH OF WALTERS PUMPKIN PATCHGO A MILE NORTH OF 110 FORLOW PREV TRUCK # SLUMP USAGE PURCHASE ORDER PROJECT # PROJECT DESC AMOUNT Fuel Surcharge RMX LEAVE PLANT START DISCHARGE ARRIVE PLANT ARRIVE JOB SITE SUBTOTAL TAX TOTAL \$57.92 OUT SIDE TEMP. CAUTION: FRESHLY MIXED CONCRETE MAY CAUSE SKIN IRRITATION OR CHEMICAL BURNS. OTHER CHARGES AVOID CONTACT WITH SKIN WHERE POSSIBLE AND WASH EXPOSED SKIN AREAS PROMPTLY ADDITIONAL TAX WITH WATER, IF ANY CONCRETE MIXTURES GET INTO EYES, RINSE IMMEDIATELY AND RE-PEATEDLY WITH WATER AND GET PROMPT MEDICAL ATTENTION. 949.98 KEEP OUT OF REACH OF CHILDREN . SEE REVERSE SIDE FOR MSDS SHEET NOTICE: EXCESSIVE UNLOADING TIME **GRAND TOTAL** · A HOLDING CHARGE OF \$1.50 PER MINUTE WILL BE INCLUDED FOR EACH TRUCK HELD WATER GALS GALS GALS ON THE JOB SITE FOR MORE THAN 60 MINUTES. ADDED ON WATER WATER WATER · IN CONSIDERATION OF OUR MAKING DELIVERY ACROSS THE STREET CURB, AT YOUR JOB AT REQUEST REQUEST, CUSTOMER AGREES TO BE RESPONSIBLE FOR ALL DAMAGE DONE TO SIDEWALKS, DRIVEWAYS, BUILDINGS, GROUNDS, ETC. CUSTOMER ACKNOWLEDGES RECEIPT OF THE ABOVE MATERIALS IN APPROVED CONDITION. OF CONSIGNEE TEST SLUMP / AIR / CYLS. PER ASTM YES IMPORTANT: PURCHASER ASSUMES FULL RESPONSIBILITY FOR STRENGTH, SLUMP AND QUALITY OF CON-TAKEN SPECS CRETE WHEN WATER OR OTHER MATERIALS ARE ADDED ON THE JOB SITE AT THE REQUEST DRIVER ACCEPTED BY: REMARKS:

400063494

AE Charge 12/19

WITH THE ABOVE TERMS AND CONDITIONS.

PURCHER'S SIGNATURE, HIS AGENT, OR HIS EMPLOYEE'S SIGNATURE CONSTITUTES AN AGREEMENT

SECTION I  Manufacturer s Name: Concrete Materials Company Address: See Reverse Side  3CaO Sio2 (cement), 2Cao Sio2 (cement), 3Cao A1203 (cement) Chemical Family: 4Cao A1203 (cement), Caso4 2H2O, Traces Cao, MgO, K2SO4, Na 2SO4 SECTION III- PHYSICAL DATA Specific Gravity: 1.9 to 2.4  Appearance and Odor: Gray, plastic, flowable, granular, mud, odorless SECTION IV- FIRE AND EXPLOSION HAZARD DATA: N.A. all sections						
Address: See Reverse Side  Trade Names:  Chemical Family:  Chemical Family:  4Cao A1203 (cement), Caso4 2H2O, Traces Cao, MgO, K2SO4, Na 2SO4  SECTION II - HAZARDOUS INGREDIENTS: Cement and possible traces of hexavalent chromium.  SECTION III- PHYSICAL DATA  Specific Gravity: 1.9 to 2.4  Appearance and Odor: Gray, plastic, flowable, granular, mud, odorless						
3CaO Sio2 (cernent), 2Cao Sio2 (cernent), 3Cao A1203 (cernent) 4Cao A1203 (cernent), 3Cao A1203 (cernent) 4Cao A1203 (cernent), 2Cao Sio2 (cernent), 3Cao A1203 (cernent) 4Cao A1203 (cernent), 2Cao A1203 (cernent) 4Cao A1203 (cernent), 2Cao A1203 (cernent) 5CECTION III - HAZARDOUS INGREDIENTS: Cernent and possible traces of hexavalent chromium.  SECTION III - PHYSICAL DATA Specific Gravity: 1.9 to 2.4  Appearance and Odor: Gray, plastic, flowable, granular, mud, odorless						
Chemical Family:  4Cao A1203 (cement), Caso4 2H2O, Traces Cao, MgO, K2SO4, Na 2SO4  SECTION III - HAZARDOUS INGREDIENTS; Cement and possible traces of hexavalent chromium.  SECTION IIII - PHYSICAL DATA  Specific Gravity: 1.9 to 2.4  Appearance and Odor: Gray, plastic, flowable, granular, mud, odorless						
SECTION II - HAZARDOUS INGREDIENTS: Cement and possible traces of hexavalent chromium.  SECTION III: PHYSICAL DATA  Specific Gravity: 1.9 to 2.4  Appearance and Odor: Gray, plastic, flowable, granular, mud, odorless						
SECTION III- PHYSICAL DATA  Specific Gravity: 1.9 to 2.4  Appearance and Odor: Gray, plastic, flowable, granular, mud, odorless  Solubility in Water: 0.1 to 1.0%						
Specific Gravity: 1.9 to 2.4  Appearance and Odor: Gray, plastic, flowable, granular, mud, odorless  Solubility in Water: 0.1 to 1.0%						
Appearance and Odor: Gray, plastic, flowable, granular, mud, odorless						
SECTION IV. FIRE AND EXPLOSION HAZARD DATA: N.A. all sections						
SECTION V - HEALTH HAZARD DATA						
Dry skin and possible alkali burns (cement dermatitis).						
TLV: None Effects of Overexposure: Also possible traces of hexavalent chromium.						
Emergency First Aid Procedures: Irrigate eyes with water. Wash affected areas of the body with soap and water.						
SECTION VI - REACTIVITY DATA						
Unstable Product sets and hardens in 2 to 8 hours,						
Stability X Conditions to Avoid: and is no longer hazardous						
Hazardous Will Not Occur						
Polymerization X						
SECTION VII - SPILL OR LEAK PROCEDURES						
Steps to be Taken in Case Material is Released or Spilled: Spill does not increase hazard.						
Waste Disposal Method: Once hardened, material can be disposed of as common waste.						
SECTION VIII - SPECIAL PROTECTION INFORMATION						
Protective Gloves: Yes Eye Protection: Yes, when placement methods cause splashing.						
Use barrier creams, gloves, boots, and clothing to protect skin						
Other Protective Equipment: from prolonged contact with plastic concrete.						
SECTION IX - SPECIAL PRECAUTIONS						
Precautions to be Taken in Handling and Storage: See above.						
Other Precautions: Immediately after, working with concrete, workers should shower with soap and water.						

Dispatch (316) 522-4949 El Dorado (316) 320-5000 Office (316) 522-8454





TIME DUE TICKET# PLANT DATE ORDER# TRUCK TICKET TIME CUSTOMERS INFO DELIVERY ADDRESS INSTRUCTIONS PURCHASE ORDER PROJECT # MAP PAGE PREV TRUCK # PRODUCT DESCRIPTION UNIT PRICE AMOUNT LOAD QTY. ORDERED DELIVERED \$169.00 Fuel Smethanne RMX \$5.00 \$25.00 LEAVE PLANT ARRIVE JOB SITE START DISCHARGE FINISH DISCHARGE ARRIVE PLANT TAX \$891.00 TOTAL OUT SIDE TEMP. CAUTION: FRESHLY MIXED CONCRETE MAY CAUSE SKIN IRRITATION OR CHEMICAL BURNS. OTHER CHARGES AVOID CONTACT WITH SKIN WHERE POSSIBLE AND WASH EXPOSED SKIN AREAS PROMPTLY ADDITIONAL TAX WITH WATER. IF ANY CONCRETE MIXTURES GET INTO EYES, RINSE IMMEDIATELY AND RE-PEATEDLY WITH WATER AND GET PROMPT MEDICAL ATTENTION 948.92 KEEP OUT OF REACH OF CHILDREN . SEE REVERSE SIDE FOR MSDS SHEET GRAND TOTAL NOTICE: EXCESSIVE UNLOADING TIME • A HOLDING CHARGE OF \$1.50 PER MINUTE WILL BE INCLUDED FOR EACH TRUCK HELD ON THE JOB SITE FOR MORE THAN 60 MINUTES. WATER GALS GALS ADDED ON WATER WATER WATER · IN CONSIDERATION, OF OUR MAKING DELIVERY ACROSS THE STREET CURB, AT YOUR JOB AT REQUEST REQUEST, CUSTOMER AGREES TO BE RESPONSIBLE FOR ALL DAMAGE DONE TO SIDEWALKS, DRIVEWAYS, BUILDINGS, GROUNDS, ETC. CUSTOMER ACKNOWLEDGES RECEIPT OF THE ABOVE MATERIALS IN APPROVED CONDITION. INT. OF CONSIGNEE INT TEST SLUMP / AIR / CYLS. IMPORTANT: PURCHASER ASSUMES FULL RESPONSIBILITY FOR STRENGTH, SLUMP AND QUALITY OF CON-PER ASTM YES TAKEN SPECS CRETE WHEN WATER OR OTHER MATERIALS ARE ADDED ON THE JOB SITE AT THE REQUEST OF THE CUSTOMER ACCEPTED DRIVER REMARKS:

PURCHER'S SIGNATURE, HIS AGENT, OR HIS EMPLOYEE'S SIGNATURE CONSTITUTES AN AGREEMENT WITH THE ABOVE TERMS AND CONDITIONS.

400063497

Parking or 12/20

		(0,)	cable Data	oriada for Each occitori,		
SECTION I					4216-202-3151	
Manufacturer s Na	me: Concrete Materials Comp	pany	1000	Emergency Telephone Number: See Reverse Side		
Address: See Reven	se Side			Trade Names:		
	THE RESERVE OF THE PARTY OF THE	3Ca(	O Sio2 (cement), 2Cao Sio2	2 (cement), 3Cao A1203 (cement)	HAT BY THE	
Chemical Family:				, Traces Cao, MgO, K2SO4, Na 2SO4		
		nent and possible traces of hexava	alent chromium.			
SECTION III- PHYS	ICAL DATA					
Specific Gravity: 1.9 to 2.4 Solubility in Water: 0.1 to 1.			Solubility in Water: 0.1 to 1.0%			
	or: Gray, plastic, flowable, gra					
	AND EXPLOSION HAZARD D	DATA: N.A. all sections				1
SECTION V - HEAL	TH HAZARD DATA					
				ossible alkali burns (cement dermatitis).		
TLV: None	Effects of Overexposur			races of hexavalent chromium.		200
Emergency First Aid		yes with water. Wash affected are	as of the body with soap ar	nd water.		
SECTION VI - REAC						
	Unstable		Product sets ar			
Stability	X	Conditions to Avoid:	and is no longe			
	Hazardou		Will Not Occur			
	Polymeriza	ation	X			
	LOR LEAK PROCEDURES					
		Spilled: Spill does not increase h				
		can be disposed of as common	waste.			-
	CIAL PROTECTION INFORM		Name of the last o			
Protective Gloves: Yes Eye Protection: Yes, when placement methods cause splashing.						
011 - 5 - 1 - 1 - 5		Use barrier creams, gloves, t		ct skin		
Other Protective Equ		from prolonged contact with p	plastic concrete.			
	CIAL PRECAUTIONS					-
	ken in Handling and Storage:					_
Other Precautions:	immediately after, working wit	th concrete, workers should showe	er with soap and water.			