

**Notice:** Fill out COMPLETELY and return to Conservation Division at the address below within 60 days from plugging date.

KANSAS CORPORATION COMMISSION  
OIL & GAS CONSERVATION DIVISION

Form CP-4  
March 2009

Type or Print on this Form  
Form must be Signed  
All blanks must be Filled

WELL PLUGGING RECORD  
K.A.R. 82-3-117

OPERATOR: License #: \_\_\_\_\_  
 Name: \_\_\_\_\_  
 Address 1: \_\_\_\_\_  
 Address 2: \_\_\_\_\_  
 City: \_\_\_\_\_ State: \_\_\_\_\_ Zip: \_\_\_\_\_ + \_\_\_\_\_  
 Contact Person: \_\_\_\_\_  
 Phone: ( \_\_\_\_\_ ) \_\_\_\_\_  
 Type of Well: (Check one)  Oil Well  Gas Well  OG  D&A  Cathodic  
 Water Supply Well  Other: \_\_\_\_\_  SWD Permit #: \_\_\_\_\_  
 ENHR Permit #: \_\_\_\_\_  Gas Storage Permit #: \_\_\_\_\_  
 Is ACO-1 filed?  Yes  No If not, is well log attached?  Yes  No  
 Producing Formation(s): List All (If needed attach another sheet)  
 \_\_\_\_\_ Depth to Top: \_\_\_\_\_ Bottom: \_\_\_\_\_ T.D. \_\_\_\_\_  
 \_\_\_\_\_ Depth to Top: \_\_\_\_\_ Bottom: \_\_\_\_\_ T.D. \_\_\_\_\_  
 \_\_\_\_\_ Depth to Top: \_\_\_\_\_ Bottom: \_\_\_\_\_ T.D. \_\_\_\_\_

API No. 15 - \_\_\_\_\_  
 Spot Description: \_\_\_\_\_  
 \_\_\_\_\_ - \_\_\_\_\_ - \_\_\_\_\_ - \_\_\_\_\_ Sec. \_\_\_\_\_ Twp. \_\_\_\_\_ S. R. \_\_\_\_\_  East  West  
 \_\_\_\_\_ Feet from  North /  South Line of Section  
 \_\_\_\_\_ Feet from  East /  West Line of Section  
 Footages Calculated from Nearest Outside Section Corner:  
 NE  NW  SE  SW  
 County: \_\_\_\_\_  
 Lease Name: \_\_\_\_\_ Well #: \_\_\_\_\_  
 Date Well Completed: \_\_\_\_\_  
 The plugging proposal was approved on: \_\_\_\_\_ (Date)  
 by: \_\_\_\_\_ (KCC District Agent's Name)  
 Plugging Commenced: \_\_\_\_\_  
 Plugging Completed: \_\_\_\_\_

Show depth and thickness of all water, oil and gas formations.

Oil, Gas or Water Records		Casing Record (Surface, Conductor & Production)			
Formation	Content	Casing	Size	Setting Depth	Pulled Out

Describe in detail the manner in which the well is plugged, indicating where the mud fluid was placed and the method or methods used in introducing it into the hole. If cement or other plugs were used, state the character of same depth placed from (bottom), to (top) for each plug set.

Plugging Contractor License #: \_\_\_\_\_ Name: \_\_\_\_\_  
 Address 1: \_\_\_\_\_ Address 2: \_\_\_\_\_  
 City: \_\_\_\_\_ State: \_\_\_\_\_ Zip: \_\_\_\_\_ + \_\_\_\_\_  
 Phone: ( \_\_\_\_\_ ) \_\_\_\_\_  
 Name of Party Responsible for Plugging Fees: \_\_\_\_\_  
 State of \_\_\_\_\_ County, \_\_\_\_\_, ss.  
 \_\_\_\_\_  Employee of Operator or  Operator on above-described well,  
 (Print Name)

being first duly sworn on oath, says: That I have knowledge of the facts statements, and matters herein contained, and the log of the above-described well is as filed, and the same are true and correct, so help me God.

Submitted Electronically



MATERIAL SAFETY DATA SHEET

MANUFACTURER: Daniels Ready Mix

IN CASE OF EMERGENCY CALL: 620-221-9060

IDENTITY OF MATERIAL: READY MIXED CONCRETE

HAZARDOUS INGREDIENTS: AQUEOUS MIXTURE OF CALCIUM SILICATES, ALUMINATES, AND FERRITES, PORTLAND AND BLENDED CEMENTS:

3CaO.S10 (CAS 12768-85-3)

2CaO.S10 (CAS 10034-77-2)

3CaO.A1.O (CAS 23042-78-3)

4CaO.A1.FE.O (CAS 12058-35-8)

CaSO<sub>4</sub>.H<sub>2</sub>O (CAS 7778-18-9) PLUS TRACES OF CaO, MgO, K<sub>2</sub>SO<sub>4</sub> & Na<sub>2</sub>SO<sub>4</sub>

OTHER INGREDIENTS: CONCRETE AGGREGATES, INERT GRAVEL SAND AND ROCK.

AD MIXTURES: MAY INCLUDE FLY ASH, GRANULATED SLAG, AND VERY SMALL AMOUNTS OF ORGANIC AND INORGANIC MATERIALS WHICH HAVE NO EFFECT ON THE HAZARDS ASSOCIATED WITH USE OF PRODUCT.

PHYSICAL/CHEMICAL CHARACTERISTICS:

BOILING POINT: N/A

VAPOR PRESSURE: N/A

VAPOR DENSITY: N/A

SPECIFIC GRAVITY: +/- 2.30

FIRE/EXPLOSION DATA: N/A

REACTIVITY DATA: STABLE

MELTING POINT: N/A

EVAPORATION RATE: N/A

SOLUBILITY: SIGHT (0.01 TO 1%)

APPEARANCE & ODOR: GRAY, PLASTIC, FLOWABLE, GRANULAR MUD, ODORLESS

HAZARDOUS POLYMERIZATION: NONE

HEALTH HAZARD DATA

ROUTES OF ENTRY: INHALATION: N/A SKIN: YES INGESTION: N/A

ACUTE HEALTH HAZARDS: CONTACT DERMATITIS AND/OR SEVERE

BURNS POSSIBLE WITH PROLONGED OR REPEATED CONTACT WITH UNPROTECTED SKIN WHEN PRODUCT IS IN THE UNHARDENED STATE.

CHRONIC HEALTH HAZARDS: HYPERSENSITIVE INDIVIDUALS MAY

DEVELOP AN ALLERGIC DERMATITIS WITH REPEATED CONTACT WITH

PRODUCT IN THE UNHARDENED STATE.

CARCINOGENICITY: NONE KNOWN

SIGNS/SYMPTOMS OF OVEREXPOSURE: IRRITATION AND/OR BURNING OF SKIN OR EYES.

PRECAUTIONS FOR SAFETY HANDLING & USE: USE PROPER TOOLS

AND EQUIPMENT. RUBBER BOOTS, RUBBER GLOVES AND PROTECTIVE

CLOTHING COVERING ARMS AND LEGS SHOULD BE WORN. PERSONS

WITH SENSITIVE SKIN SHOULD TAKE EXTRA PROTECTIVE PRECAUTIONS

EMERGENCY AND FIRST AID PROCEDURES

CONTACT WITH EYES: IMMEDIATELY FLUSH EYES WITH COPIOUS

AMOUNTS OF WATER AND CONSULT A PHYSICIAN.

CONTACT WITH SKIN: THOROUGHLY WASH AFFECTED AREA WITH SOAP

AND WATER. A PHYSICIAN SHOULD BE CONSULTED FOR SEVERE

BURNS OR PERSISTENT IRRITATION.

THE INFORMATION HEREIN IS GIVEN IN GOOD FAITH AND IS BASED ON

KNOWLEDGE BELIEVED TO BE RELIABLE. NO WARRANTY, EXPRESSED

OR IMPLIED, IS GIVEN REGARDING THE ACCURACY OF THIS DATA OR

THE RESULTS OBTAINED FROM THE USE THEREOF.

**WARNING: INJURIOUS TO EYES: CAUSES SKIN IRRITATION: READ THIS WARNING BEFORE USING: CONTAINS PORTLAND CEMENT.**

Contact with wet, unhardened concrete, mortar, cement or cement mixtures can cause skin irritation, severe chemical burns or serious eye damage. Avoid contact with eyes and skin. Wear waterproof gloves, a fully buttoned, long-sleeve shirt, full length trousers and tight-fitting eye protection when working with these materials. If you have to stand in wet concrete, use waterproof boots that are tight at the top and high enough to keep concrete from flowing into them. If you are finishing concrete, wear kneepads to protect your knees. Wash wet concrete, mortar, cement or cement mixtures from your skin with fresh, clean water immediately after contact. Indirect contact through clothing can be as serious as direct contact, so promptly rinse wet concrete, mortar, cement or cement mixtures from clothing. Seek immediate medical attention if you have persistent or severe discomfort. In case of eye contact, flush with plenty of water for at least 15 minutes. Consult a physician immediately. KEEP OUT OF REACH OF CHILDREN. USER AGREES TO CONVEY THIS WARNING TO ALL PERSONS WHOM MAY USE OR COME INTO CONTACT WITH WET (UNHARDENED) CONCRETE, MORTAR, AND CEMENT OR CEMENT MIXTURES.

**CRYSTALLINE SILICA CARCINOGENIC POTENTIAL:** Concrete frequently contains crystalline silica in concentrations greater than 6.1 percent, principally contributed by the aggregates. Respirable crystalline silica is classified by the International Agency for Research on Cancer as a known human carcinogen and by the National Toxicology Program as "reasonably anticipated to be a carcinogen". Crystalline silica in wet concrete is not respirable and does not pose a hazard when the concrete is in its plastic or unhardened state. Once concrete has hardened, airborne dust generated by grinding, sawing, drilling, breaking, etc., can lead to potentially hazardous exposures to workers and appropriate respiratory protection precautions should be taken.