

Notice: Fill out COMPLETELY and return to Conservation Division at the address below within 60 days from plugging date.

**KANSAS CORPORATION COMMISSION
OIL & GAS CONSERVATION DIVISION
WELL PLUGGING RECORD
K.A.R. 82-3-117**

Form CP-4
March 2009
**Type or Print on this Form
Form must be Signed
All blanks must be Filled**

OPERATOR: License #: _____
 Name: _____
 Address 1: _____
 Address 2: _____
 City: _____ State: _____ Zip: _____ + _____
 Contact Person: _____
 Phone: (_____) _____
 Type of Well: (Check one) Oil Well Gas Well OG D&A Cathodic
 Water Supply Well Other: _____ SWD Permit #: _____
 ENHR Permit #: _____ Gas Storage Permit #: _____
 Is ACO-1 filed? Yes No If not, is well log attached? Yes No
 Producing Formation(s): List All (If needed attach another sheet)
 _____ Depth to Top: _____ Bottom: _____ T.D. _____
 _____ Depth to Top: _____ Bottom: _____ T.D. _____
 _____ Depth to Top: _____ Bottom: _____ T.D. _____

API No. 15 - _____
 Spot Description: _____
 _____ - _____ - _____ - _____ Sec. _____ Twp. _____ S. R. _____ East West
 _____ Feet from North / South Line of Section
 _____ Feet from East / West Line of Section
 Footages Calculated from Nearest Outside Section Corner:
 NE NW SE SW
 County: _____
 Lease Name: _____ Well #: _____
 Date Well Completed: _____
 The plugging proposal was approved on: _____ (Date)
 by: _____ (KCC District Agent's Name)
 Plugging Commenced: _____
 Plugging Completed: _____

Show depth and thickness of all water, oil and gas formations.

Oil, Gas or Water Records		Casing Record (Surface, Conductor & Production)			
Formation	Content	Casing	Size	Setting Depth	Pulled Out

Describe in detail the manner in which the well is plugged, indicating where the mud fluid was placed and the method or methods used in introducing it into the hole. If cement or other plugs were used, state the character of same depth placed from (bottom), to (top) for each plug set.

Plugging Contractor License #: _____ Name: _____
 Address 1: _____ Address 2: _____
 City: _____ State: _____ Zip: _____ + _____
 Phone: (_____) _____
 Name of Party Responsible for Plugging Fees: _____
 State of _____ County, _____, ss.
 _____ Employee of Operator or Operator on above-described well,
 (Print Name)

being first duly sworn on oath, says: That I have knowledge of the facts statements, and matters herein contained, and the log of the above-described well is as filed, and the same are true and correct, so help me God.

Submitted Electronically



DANIELS READY MIX
 2016 COUNTRY CLUB ROAD
 P.O. BOX 842 - WINFIELD, KANSAS 67156
 PHONE: (620) 221-9060 - FAX: (620) 221-7525

No. 50979

B # 3

PLANT	LOAD TIME	DATE	ACCOUNT	CYLINDERS TAKEN	TRUCK	DRIVER	CONTROL NUMBER
						James	50979

PURCHASE ORDER	SALES ORDER	TAX	CREDIT	ORDERED	DELIVERED	UNIT PRICE	SLUMP	AMOUNT
3.50 yd	DTL SLUR 1 18SN 60/40 HD CHEM			3.50	3.50	50.00		175.00
1.00 yd	DELIVERY CHARGE			1.00	1.00	50.00		50.00
1.00 yd	SHORT 3.25 SHORT LOAD			1.00	1.00	150.00		150.00
				SUB TOTAL				200.00
				TAX				13.00
				TOTAL				213.00
				PREVIOUS TOTAL				213.00
				GRAND TOTAL				213.00

BY ACCEPTANCE OF THIS LOAD, THE PROPERTY OWNER, CONTRACTOR, SUB CONTRACTOR AND FINISHER AGREE TO THE FOLLOWING STATEMENTS (1-6).

- Customer assumes responsibility for a suitable roadway from the public highway to point of delivery and is liable for any damages to or by Seller's truck after leaving the highway.
- WARNING: CAUTION:** Freshly mixed cement, mortar, concrete or grout may cause skin injury. Avoid contact with skin where possible and wash exposed areas promptly with water. If any cement mixtures get into eyes, rinse immediately and repeatedly with water and get prompt medical attention. **KEEP OUT OF REACH OF CHILDREN.**
- This concrete contains correct water content for strength of mix indicated. We do not assume responsibility for strength test when water is added after truck leaves our plant.
- This concrete conforms to ASTM # 94. No change is herewith authorized.

- We do not guarantee the finished results obtained from this load of concrete. Too many factors not under our control can affect the ultimate results.
- KANSAS LIEN LAW INFORMATION**
 (from K.S.A. 60-1103a)(b)(1))
 Notice to Owners: If you pay the contractor for work or equipment, material, or supplies delivered without having received from the contractor a waiver of lien by all subcontractors, or other evidence of payment to all subcontractors, a lien may be filed against your property by a subcontractor. You may request from the contractor a list of all subcontractors. If you received notice of filing a lien statement by a subcontractor, you may withhold from the contractor the amount claimed in the subcontractor's statement pending resolution of the dispute.

TERMS: Invoices due on 10th of the month. A FINANCE CHARGE of 2% per Month, which is an Annual Rate of 24% will be charged on all accounts not paid by the following billing date.
 *Customer agrees to pay reasonable attorney and/or collection fees should it become necessary to refer this bill for collection.

Rec'd by _____ Gallons Water Added at Customers Request

MATERIAL SAFETY DATA SHEET

MANUFACTURER: Daniels Ready Mix

CASE OF EMERGENCY CALL: 620-221-9060

IDENTITY OF MATERIAL: READY MIXED CONCRETE

HAZARDOUS INGREDIENTS: AQUEOUS MIXTURE OF CALCIUM SILICATES, ALUMINATES, AND FERRITES, PORTLAND AND BLENDED CEMENTS:

3CaO.S10 (CAS 12168-85-3)

2CaO.S10 (CAS 10034-77-2)

3CaO.A1:O (CAS 23042-78-3)

4CaO.A1.FE:O (CAS 12058-35-8)

CaSO₄.H₂O (CAS 7778-18-9) PLUS TRACES OF CaO, MgO, K₂SO₄ & Na₂SO₄

OTHER INGREDIENTS: CONCRETE AGGREGATES, INERT GRAVEL SAND AND ROCK.

AD MIXTURES: MAY INCLUDE FLY ASH, GRANULATED SLAG, AND VERY SMALL AMOUNTS OF ORGANIC AND INORGANIC MATERIALS WHICH HAVE NO EFFECT ON THE HAZARDS ASSOCIATED WITH USE OF PRODUCT.

PHYSICAL/CHEMICAL CHARACTERISTICS:

BOILING POINT: N/A

VAPOR PRESSURE: N/A

VAPOR DENSITY: N/A

SPECIFIC GRAVITY: +/- 2.30

FIRE/EXPLOSION DATA: N/A

REACTIVITY DATA: STABLE

MELTING POINT: N/A

EVAPORATION RATE: N/A

SOLUBILITY: SLIGHT (0.01 TO 1%)

APPEARANCE & ODOR: GRAY, PLASTIC, FLOWABLE, GRANULAR

MUD, ODORLESS

HAZARDOUS POLYMERIZATION: NONE

HEALTH HAZARD DATA

ROUTES OF ENTRY: INHALATION: N/A SKIN: YES INGESTION: N/A

ACUTE HEALTH HAZARDS: CONTACT DERMATITIS AND/OR SEVERE BURNS POSSIBLE WITH PROLONGED OR REPEATED CONTACT WITH UNPROTECTED SKIN WHEN PRODUCT IS IN THE UNHARDENED STATE.

CHRONIC HEALTH HAZARDS: HYPERSENSITIVE INDIVIDUALS MAY DEVELOP AN ALLERGIC DERMATITIS WITH REPEATED CONTACT WITH PRODUCT IN THE UNHARDENED STATE.

CARCINOGENICITY: NONE KNOWN

SIGNS/SYMPTOMS OF OVEREXPOSURE: IRRITATION AND/OR BURNING OF SKIN OR EYES.

PRECAUTIONS FOR SAFETY HANDLING & USE: USE PROPER TOOLS AND EQUIPMENT. RUBBER BOOTS, RUBBER GLOVES AND PROTECTIVE CLOTHING COVERING ARMS AND LEGS SHOULD BE WORN. PERSONS WITH SENSITIVE SKIN SHOULD TAKE EXTRA PROTECTIVE PRECAUTIONS

EMERGENCY AND FIRST AID PROCEDURES

CONTACT WITH EYES: IMMEDIATELY FLUSH EYES WITH COPIOUS AMOUNTS OF WATER AND CONSULT A PHYSICIAN.

CONTACT WITH SKIN: THOROUGHLY WASH AFFECTED AREA WITH SOAP AND WATER. A PHYSICIAN SHOULD BE CONSULTED FOR SEVERE BURNS OR PERSISTENT IRRITATION.

THE INFORMATION HEREIN IS GIVEN IN GOOD FAITH AND IS BASED ON KNOWLEDGE BELIEVED TO BE RELIABLE. NO WARRANTY, EXPRESSED OR IMPLIED, IS GIVEN REGARDING THE ACCURACY OF THIS DATA OR THE RESULTS OBTAINED FROM THE USE THEREOF.

WARNING: INJURIOUS TO EYES: CAUSES SKIN IRRITATION: READ THIS WARNING BEFORE USING: CONTAINS PORTLAND CEMENT.

Contact with wet, unhardened concrete, mortar, cement or cement mixtures can cause skin irritation, severe chemical burns or serious eye damage. Avoid contact with eyes and skin. Wear waterproof gloves, a fully buttoned, long-sleeve shirt, full length trousers and tight-fitting eye protection when working with these materials. If you have to stand in wet concrete, use waterproof boots that are tight at the top and high enough to keep concrete from flowing into them. If you are finishing concrete, wear kneepads to protect knees. Wash wet concrete, mortar, cement or cement mixtures from your skin with fresh, clean water immediately after contact. Indirect contact through clothing can be as serious as direct contact, so promptly rinse wet concrete, mortar, cement or cement mixtures from clothing. Seek immediate medical attention if you have persistent or severe discomfort. In case of eye contact, flush with plenty of water for at least 15 minutes. Consult a physician immediately. KEEP OUT OF REACH OF CHILDREN. USER AGREES TO CONVEY THIS WARNING TO ALL PERSONS WHOM MAY USE OR COME INTO CONTACT WITH WET (UNHARDENED) CONCRETE, MORTAR, AND CEMENT OR CEMENT MIXTURES.

CRYSTALLINE SILICA CARCINOGENIC POTENTIAL: Concrete frequently contains crystalline silica in concentrations greater than 0.1 percent, principally contributed by the aggregates. Respirable crystalline silica is classified by the International Agency for Research on Cancer as a known human carcinogen and by the National Toxicology Program as "reasonably anticipated to be a carcinogen". Crystalline silica in wet concrete is not respirable and does not pose a hazard when the concrete is in its plastic or unhardened state. Once concrete has hardened, airborne dust generated by grinding, sawing, drilling, breaking, etc., can lead to potentially hazardous exposures to workers and appropriate respiratory protection precautions should be taken.