

Form	ACO1 - Well Completion
Operator	S & K Oil Production, Inc.
Well Name	PAGE I 17
Doc ID	1732348

Casing

Purpose Of String	Size Hole Drilled	Size Casing Set	Weight	Setting Depth	Type Of Cement	Number of Sacks Used	Type and Percent Additives
Surface	9.875	7	0	20	one	5	0
Production	5.875	2.875	0	712	one	80	0

McGOWN

DRILLING, INC.

Mound City, KS

620.224.7406

Well #				Casing			
S&K Oil Production Inc.				Surface		Longstring	
Page I17				Size:	7 "	Size:	2 7/8 "
API #: 15-011-24756 S-T-R: 18-25-22E				Tally:	20.0 '	Tally:	712.4 '
County: Bourbon Date: 8/28/2023				Cement:	5 sx	Bit:	5 7/8 "
				Bit:	9 7/8 "	Date:	8/29/2023
Top	Base	Formation		Top	Base	Formation	
0	2	soil		667	684	sand	
2	12	clay		684	690	blk sand	
12	14	shale		690		shale	
14	31	lime					
31	33	blk shale					
33	36	lime					
36	43	shale					
43	59	lime					
59	61	shale					
61	64	lime					
64	114	shale					
114	118	lime					
118	215	shale					
215	235	lime					
235	272	shale					
272	277	sand	hard grey dry				
277	301	sandy shale					
301	322	shale					
322	345	lime					
345	362	shale					
362	370	lime					
370	378	shale					
378	380	lime					
380	389	shale					
389	403	lime					
403	412	shale					
#REF!			Fort Scott				
412	417	lime					
417	430	shale					
430	431	sand	good odor, slight bleed,				
431	335	sand & sandy sh	good odor, slight bleed,				
335	445	sandy shale					
445	528	shale					
528	530	lime					
530	554	shale					
554	555	coal					
555	667	shale					
			Total Depth:	716			

*Cement by S&K Oil Prod.
80 SXS.*

Float Equipment

Qty	Size	
1	2 7/8	Float Shoe
3	2 7/8	Centralizers
1	2 7/8	Casing clamp

Sand / Core Detail

Core #1:	Core #2:
Core #3:	Core #4:
667	680
680	682
682	684

good odor, heavy bleed, dk brown sand
good odor, good bleed blk sand
good odor, slight bleed blk sand

TOP