

Form	ACO1 - Well Completion
Operator	S & K Oil Production, Inc.
Well Name	GEORGE I 1
Doc ID	1735302

Casing

Purpose Of String	Size Hole Drilled	Size Casing Set	Weight	Setting Depth	Type Of Cement	Number of Sacks Used	Type and Percent Additives
Surface	9.875	7	6	20	one	5	0
Production	5.875	2.875	6	652	one	75	0

McGOWN

DRILLING, INC.

Mound City, KS
620.224.7406

Well #				Casing																							
S&K Oil Production George# 11				<table border="1"> <thead> <tr> <th colspan="2">Surface</th> <th colspan="2">Longstring</th> </tr> </thead> <tbody> <tr> <td>Size:</td> <td>7 "</td> <td>Size:</td> <td>2 7/8 "</td> </tr> <tr> <td>Tally:</td> <td>20.0 '</td> <td>Tally:</td> <td>652.8 '</td> </tr> <tr> <td>Cement:</td> <td>5 sx</td> <td>Bit:</td> <td>5 7/8 "</td> </tr> <tr> <td>Bit:</td> <td>9 "</td> <td>Date:</td> <td>8/17/2023</td> </tr> </tbody> </table>				Surface		Longstring		Size:	7 "	Size:	2 7/8 "	Tally:	20.0 '	Tally:	652.8 '	Cement:	5 sx	Bit:	5 7/8 "	Bit:	9 "	Date:	8/17/2023
Surface		Longstring																									
Size:	7 "	Size:	2 7/8 "																								
Tally:	20.0 '	Tally:	652.8 '																								
Cement:	5 sx	Bit:	5 7/8 "																								
Bit:	9 "	Date:	8/17/2023																								
API #:	011-24752	S-T-R:																									
County:	Bourbon	Date:	8/15/2023																								
Top	Base	Formation		Top	Base	Formation																					
0	2	soil rocks		630	634	sand&sandy shale	slight odor																				
2	5	lime		634		shale																					
5	9	clay																									
9	18	lime																									
18	23	shale																									
23	26	lme																									
26	79	shale																									
79	84	lime																									
84	160	shale																									
160	165	lime																									
165	187	shale																									
#REF!																											
187	198	lime																									
198	202	shale																									
202	205	lime																									
205	239	shale																									
239	245	lime																									
245	281	shale																									
281	281	lime																									
281	288	shale																									
288	305	lime																									
305	330	shale																									
330	331	lime																									
331	337	shale																									
337	340	lime																									
340	350	shale																									
350	363	lime																									
363	372	shale																									
372	375	lime	Fort Scott																								
375	398	shale																									
398	340	sand	slight odor																								
340	345	sandy shale																									
345	488	shale																									
488	489	lime																									
489	614	shale																									
614	618	sand shale																									
618	630	sand																									
Total Depth:				656																							

*Cemented by S&K Oil Prod
75 Sxs.*

Float Equipment

Qty	Size	
1	2 7/8	Float Shoe
3	2 7/8	Centralizers
1	2 7/8	Casing clamp

Sand / Core Detail

Core #1:	Core #2:
Core #3:	Core #4:
618	620
620	622
622	628
628	630

slight odor, light brown sand
good odor, good bleed
good odor, heavy bleed
good odor, fair bleed, blk sand