

Form	ACO1 - Well Completion
Operator	TDR Construction, Inc.
Well Name	MOLDENHAUER 1A
Doc ID	1956939

Casing

Purpose Of String	Size Hole Drilled	Size Casing Set	Weight	Setting Depth	Type Of Cement	Number of Sacks Used	Type and Percent Additives
Surface	12	8.625	12	20	Portland	5	50/50 POZ
Production	6.75	3.5	8	806	Class A	109	50/50 POZ 2% Bentonite

TDR Construction, Inc.
(913) 710-5400
Wellsville, KS

Well Information S. Moldenhauer 1A API# 15-059-27536 County: Franklin		Sec/Twp/Rge 32/15/21 Commenced Spuding: 4/22/06	Casing <table border="1"> <tr> <td></td> <td>Surface</td> <td>Production</td> </tr> <tr> <td>Size:</td> <td>8-5/8"</td> <td>3-1/2"</td> </tr> <tr> <td>Depth:</td> <td>20'</td> <td>806.1'</td> </tr> <tr> <td>Cement:</td> <td>5 sacks</td> <td></td> </tr> <tr> <td>Drill Size:</td> <td>12"</td> <td>6-3/4"</td> </tr> </table> Completed Drilling 4/23/06		Surface	Production	Size:	8-5/8"	3-1/2"	Depth:	20'	806.1'	Cement:	5 sacks		Drill Size:	12"	6-3/4"
	Surface	Production																
Size:	8-5/8"	3-1/2"																
Depth:	20'	806.1'																
Cement:	5 sacks																	
Drill Size:	12"	6-3/4"																
Elevation 1010' Distance From South Line 4331' East Line 3319'	Baffle 774.3' Float 806.1' TD 820'																	

WELL LOG

Thickness of Strata	Formation	Total Depth
0-12	Soil/Clay	12
52	Shale	64
26	Lime	90
8	Shale	98
11	Lime	109
3	Shale	112
21	Lime	133
36	Shale	169
20	Lime	189
80	Shale	269
26	Lime	295
11	Shale	306
9	Lime	315
41	Shale	356
1	Lime	357
15	Shale	372
9	Lime	381
2	Shale	383
14	Lime	397
8	Shale	405
23	Lime	428
4	Shale	432
5	Lime	437
3	Shale	440
6	Lime	446
177	Shale	623
6	Lime	629
40	Shale	669
4	Lime	673
16	Shale	689
1	Lime	690
28	Shale	718

718

[illegible]

