

DRILLERS LOG

8-15-26W⁸¹

#1 Richard Norton

NW NW NW
Sec. 8-15S-26W
Gold Cty, Ks.

State Geologist Stanley
WICHITA BRANCH

Company: Palomino Petroleum

Contractor: BEREDCO INC.

Comm: 12/16/82

Comp.: 12/21/82

Casing: Set 8 jts., new 24#, 8-5/8" @ 328' w/ 275 sks 60-40 Pozmix, 2% Gel, 3% CC.
Did Circ. PD @ 12:25AM 12/16/82 by Allied.

Set 104 jts., new 14#, 5 1/2" @ 4160' w/ 200 sks 60-40 Pozmix, 2% Gel, 10% Salt
PD @ 10:30 PM 12/21/82 by Allied.

FORMATION

FROM

TO

Sand, Post Rock, Shale	0'	331'	
Shale	331'	800'	
Shale & Sand	800'	1575'	
Shale & Anhydrite	1575'	2070'	Anhydrite 1749-1787'
Shale & Lime	2070'	2490'	
Lime & Shale	2490'	3265'	
Shale	3265'	3297'	
Lime & Shale	3297'	4166'	

TOTAL ROTARY DEPTH 4166'

STATE OF KANSAS

SS:

COUNTY OF SEDGWICK

I certify that this is a true and correct copy of the above log as shown by the drilling reports.

BEREDCO

[Signature]

RECEIVED
STATE CORPORATION COMMISSION

MAR 16 1983

CONSERVATION DIVISION
Wichita, Kansas

Subscribed and sworn to before me this 28th day of December, 1982.

Cheryl L. Benoit

