


Company - WILSON OIL COMPANY
Farm - Robinson No. 9

SEC. 17 T. 25 R5E
NE N1 SW

Total Depth. 2553'
Comm. 9-16-48 Comp. 10-9-48
Shot or Treated.
Contractor. R. J. Wixson Drlg. Company
Issued. 10-30-48

County. Butler
KANSAS



CASING:
12 1/2" 230' 8 1/2" 1945'
10" 1470' 5 1/2" 2537'

Elevation. 1390 Ind

Production. Est 25 bbls.

Figures Indicate Bottom of Formations.

cellar	8	shale	1250
shale	25	lime	1255
lime	40	shale	1260
gravel NFW 40-45'	45	lime	1270
lime	150	shale	1285
shale	170	lime	1295
lime	185	shale	1305
shale	230	lime	1325
lime	245	shale	1340
slate	255	lime	1415
lime	270	SO 1395-1400'	
slate and shells	315	shale	1470
shale	325	lime	1510
lime	335	shale	1515
shale	345	lime	1540
lime	355	shale	1565
shale and shells	375	lime	1575
lime	390	shale	1675
shale	400	lime	1680
lime	410	shale	1715
shale	435	lime	1725
lime	450	shale	1775
shale	465	lime	1920
lime	475	6BWP 1875-1880'	
shale	480	shale	2070
lime	500	lime	2210
lime brkn	525	shale	2220
LBVPH 515-525'		lime	2240
lime	535	shale	2315
shale	545	lime	2325
shale and shells	560	shale	2365
slate	645	lime	2375
shale	675	shale	2400
lime	680	lime	2420
shale	695	shale	2425
lime	700	lime	2450
sand SSO 705-10'	715	shale	2515
shale	725	red rock	2525
sand	740	chert	2552
shale	765	chert	2553
lime broken	785	total depth	
shale	850		
lime	875		
shale	885		
lime	940		
shale	1050		
lime	1060		
shale	1075		
lime	1090		
shale	1125		
lime brkn	1135		
shale	1150		
lime	1195		
shale	1215		
lime	1220		
shale	1225		
lime	1235		