


WELL LOG BUREAU--KANSAS GEOLOGICAL SOCIETY
508 East Murdock, Wichita, Kansas

Company- WILSON PRODUCTION CO.
Farm- Robinson "A" No. 14

SEC. 17 T. 25 R. 5E
NW NW SE

Total Depth. 2536
Comm. 8-30-55 Comp. 9-27-55
Shot or Treated.
Contractor. R. P. Baker Drilling Co.
Issued. 11-26-55

County Butler
KANSAS



CASING:
15 1/2 91' pulled 8 in. 2276' pulled Elevation. _____
13 3/8 865' pulled 7 in. 2486' w/ 35 sx cmt. Production. 25 BOPD
10 in. 1671' pulled

Figures Indicate Bottom of Formations.

cellar	8	shale	1100
lime	15	lime	1105
shale	30	shale	1140
lime, HFW 50-65	80	lime	1165
shale	100	shale	1185
lime	140	lime	1205
shale	175	shale	1220
lime	180	lime, 1 1/2 BW 1230	1245
shale	185	shale	1255
red rock	190	lime	1270
lime	210	shale	1275
shale	215	lime	1290
lime	235	shale	1295
red rock	240	lime	1305
shale	245	shale	1310
lime	250	lime, 1 BW 1335	1380
shale	295	shale	1425
lime	310	lime	1490
shale	340	shale	1633
lime	350	lime	1645
shale	365	shale	1670
lime	375	lime	1680
shale	380	shale	1734
red rock	385	lime, 1/2 BW 1785 & 1845	1897
lime	405	shale	2010
shale	415	lime	2020
lime	420	shale	2044
shale	435	lime, 1/2 BW 2070	2148
lime	440	shale	2150
shale	470	lime	2200
lime	475	shale	2275
shale, 1/2 BW	495	lime	2290
lime,	515	shale	2359
shale	525	lime	2385
lime	530	shale	2390
shale	535	lime	2400
lime	540	shale	2440
shale	625	lime	2442
shale & shells	658	shale	2460
lime	670	lime	2464
shale	681	shale	2475
lime	690	chat	2536
sand	697	Total Depth	
shale	718	TOPS:	
sand	725	Lansing	1734
shale	825	Kansas City	2024
shells	840	Mississippi chat	2475
lime	850		
shale	865	Core from 690-700, sand 691-697,	
lime	870	oil stain 692 1/2-695, core 715-731,	
shale	880	sand 718-725, no oil stain, no free	
lime	910	oil in either. Drill from 2486-	
shale	960	2525, 12 hr. test 4 bailers oil.	
lime	965	Drill from 2525-2536, FU 400' over	
shale	1040	night, no water.	
lime	1045		
shale	1050		
lime	1075		