


Company - THE TEXAS COMPANY
 Farm - L. W. Robinson No. 31

SEC. 17 T. 25 R. 5E
 NE SW NE

Total Depth. 2485'
 Comm. 10-18-44 Comp. 11-17-44
 Shot or Treated.
 Contractor. Wixson Drlg. Co.
 Issued. 2-17-45 Cable O-2485

County. Butler
 KANSAS



CASING:
 15 1/8" 195' P 7" 2483' Cem.
 12 1/8" 880' P
 10 3/4" 1660' P

Elevation. _____

Production. 162 BO in 12 hrs.
 no wtr. pmpg.

Figures Indicate Bottom of Formations.

cellar	7	lime	1230
clay	10	shale	1235
lime	20	lime	1255
clay	30	shale	1260
shale	45	lime	1270
shale & shells	100	shale	1320
lime	120	lime brkn	1350
shale & shells	130	shale	1400
lime	150	lime	1480
shale	155	shale	1500
red rock	165	lime	1505
lime	176	shale	1540
shale	185	lime	1555
lime	200	shale-	1620
red rock	210	lime	1630
lime	215	shale	1645
shale	230	red rock	1650
shale & shells	290	lime	1670
shale	300	red rock	1675
lime	315	shale	1720
lime	320	lime	1865
shale	350	shale	2000
red rock	355	lime	2095
lime brkn	410	shale	2100
shale	425	lime	2135
lime	430	shale	2140
shale	450	slate	2145
lime	460	lime	2170
lime brkn	510	shale	2225
shale	520	lime	2235
lime	535	shale	2270
shale	550	lime	2280
shale	560	shale	2305
lime	565	lime	2355
shale	590	shale	2370
lime	605	red rock	2375
shale & shells	682	shale	2476
sand	692	lime	2485
shale	725	Total Depth.	
lime sdy	735		
shale	785		
lime sdy	800		
lime	830		
shale & shells	845		
lime	905		
lime	910		
shale	935		
lime	940		
shale	985		
lime	990		
shale	995		
lime	1010		
shale	1025		
lime	1050		
shale	1100		
lime	1135		
shale	1145		
lime	1175		
shale	1185		
lime	1200		
shale	1220		

Tops:
 K. C. 2000'
 Viola 2483'

Acidized w/500 gals.,
 pumped 41 bbls in 3 hrs.