


18-25-5E

ADAIR-MORTON  
 Robison No. 4.

SEC. 18 T. 25 R. 5 E  
 SW SE NE

Total Depth. 2906'  
 Comm. 9-8-43 Comp. 10-19-43  
 Shot or Treated.  
 Contractor.  
 Issued. 11-6-43

County. Butler



CASING: Elevation.  
 15 1/2" 245' 10" 1720' 7" 2655'  
 12 1/2" 946' 8" 2148' UR 2662' Production. Dry

Figures Indicate Bottom of Formations.

cellar	8	lime	1115	13 BWP 70-80
red rock	12	shale	1120	6 BWP 685-90
clay	45	lime	1135	3 BWP 1380-90
shale	70	shale	1205	2 BWP 1860-70
lime	80	lime	1235	3 BWP 1910-20
shale	100	shale	1245	HPW 2655
lime	110	lime	1275	
shale	115	shale	1290	
lime bkn	130	lime	1305	
shale	145	shale	1325	
lime	160	lime	1340	
shale	185	lime	1340	
lime	200	shale	1345	
shale	235	lime	1360	
red rock	240	shale	1375	
shale	243	lime	1450	
lime	255	shale	1510	
shale	265	lime	1550	
lime	280	shale	1555	
shale	290	lime	1585	
red rock	295	shale	1645	
lime	300	lime	1670	
shale	305	shy shale	1680	
lime	320	shale	1720	
shale	330	lime	1725	
lime	335	shale	1815	
shale	365	lime	1910	
lime	370	sand	1920	
shale	375	lime	1980	
lime	385	shale	2145	
shale	395	lime	2245	
lime	415	shale	2250	
shale	420	lime	2290	
lime	430	shale	2300	
shale	435	lime	2305	
lime	460	shale	2375	
shale	470	lime	2380	
lime	475	shale	2385	
shale	525	lime	2395	
lime	535	shale	2410	
shale	545	red rock	2415	
lime	580	shale	2425	
shale & shells	610	lime	2440	
shale	675	shale	2465	
lime	680	shale & shells	2500	
shale	685	shale	2570	
sand	690	lime	2575	
lime	700	shale	2580	
shale	730	lime	2585	
lime	735	shale shy	2590	
shale	805	red rock	2595	
lime	815	shale shy	2600	
shale	855	red rock	2605	
lime	865	lime	2635	
shale	875	shale shy	2645	
lime	885	lime	2790	
shale	895	shale	2882	
lime	925	lime	2906	
shale	935	Total Depth.		
lime	985			
shale	1095			