


Company- WARD A. MCGINNIS
 Farm- Crites No. 1

SEC. 19 T. 28 R. 16E
 NW SE NW

Total Depth. 1173 = 1169 Gr. Meas.
 Comm. 9-30-53 Comp. 11-11-53
 Shot or Treated.

County Wilson
 KANSAS



Contractor. Ward A. McGinnis
 Issued. 1-29-55 (CABLE TOOLS)

CASING:

7" 665
 5" 810

Elevation. _____

Production. Abd.

Figures Indicate Bottom of Formations.

| | |
|-------------------|-----------------------|
| surface | 5 |
| shale | 68 |
| lime | 103 |
| shale | 210 |
| lime broken | 235 |
| shale | 245 |
| lime | 252 |
| shale | 268 |
| lime broken | 275 |
| lime | 360 |
| shale | 365 |
| lime broken | 425 |
| lime | 489 |
| shale | 568 |
| lime | 580 |
| shale | 685 |
| lime | 690 |
| shale | 693 |
| lime | 740 |
| shale | 749 |
| lime sdy Os. | 755 |
| lime | 769 |
| shale | 773 |
| lime | 787 |
| shale | 795 |
| lime sandy water | 809 |
| HFW 815-915 | |
| shale | 960 |
| shale sandy | 990 |
| gas 965 good | |
| More gas 990-1058 | |
| sand | 1001 |
| Coring 1001-22 | |
| shale sandy | 1048 |
| S.O. 1038-48 | |
| Cored 1048-58 | |
| shale sandy | 1070 |
| shale | 1080 |
| sand | 1128 |
| 5 BW 1092-1100 | |
| shale | 1133 |
| HFW 1100-20 | |
| sand | 1138 |
| shale | 1155 |
| lime Miss. | 1173 = 1169 Gr. Meas. |
| Total depth | |