


Company - BEAUMONT PETRO. CO.
Farm - Amanda S. Nelson No. 1SEC. 20 T. 28 R. 8 E
NE c NETotal Depth. 3037' PB 2735'
Comm. 6-24-44 Comp. 7-31-44
Shot or Treated.
Contractor. Beaumont Petro. Co.
Issued. 12-16-44County. Butler
KANSAS

CASING:

12 1/8" 895'P 7" 2176'P
10 3/4" 1281'P 5 1/2" 2728' Cem
8 5/8" 1430'P UR 1493'P

Elevation. _____

Production. Dry

Figures Indicate Bottom of Formations.

floor to surface	2	shale	1055	shale	2140	1/2 BW	730-35
cellar	8	1065=1066 SLM		lime	2165	1/2 BW	1040
clay	14	lime	1070	shale	2181	HFW	1417-22
lime	40	shale	1095	lime blk &		1 1/2 BW	1645-50
red rock	50	lime	1125	shale	2200	2 BW	1720-30
lime	60	shale	1130	shale sdy	2240	3 BW	2075
shale	70	lime	1155	shale	2270		
lime	75	shale	1185	lime	2275	Show Oil	2143-50
shale	80	lime	1200	shale	2285		
lime	120	shale	1225	lime	2290	8-31-44 1000 Gals	
shale & lime		shale & lime		shale & sand	2305	Acid-No Results	
shells	155	shells	1255	shale	2325		
lime	170	shale	1265	red rock	2327	GAS	
shale	190	lime	1284	shale	2330	None	
lime	240	shale	1300	lime	2365		
shale	245	lime	1325	shale	2375		
red rock	250	shale	1335	sand	2390		
lime	280	red rock	1345	shale	2395		
shale & lime		lime	1365	lime	2457		
shells	330	shale	1400	shale	2465		
lime	350	sand	1428	lime	2475		
shale	355	shale sdy	1445	shale	2510		
lime	360	shale	1450	lime	2515		
shale	405	lime	1455	shale	2520		
lime	410	shale	1460	lime	2525		
shale	425	shale & sand	1470	shale	2630		
lime	430	lime	1475	shale sdy	2650		
shale	450	sand	1485	shale	2725		
lime	485	shale	1490	shale & sand	2734		
shale	580	sand	1495	chert & oil			
lime	585	shale sdy	1520	2735=2731 SLM			
shale	595	shale	1555	lime brwn S.O.	2733		
lime	610	lime	1559	lime Brwn			
shale	630	shale	1635	No Oil	2746		
lime	635	lime	1645	lime brwn S.O.	2746-49		
shale	650	sand	1650	lime brwn	2873		
lime	655	lime sdy	1655	lime hd	2905		
shale	665	lime hd	1665	lime blk	2958		
lime	685	lime wh	1680	lime gry	2965		
shale	690	lime	1720	lime	2979		
lime	750	sand & lime	1730	shale	2990		
shale	760	lime	1835	lime blk	2995		
lime	765	shale	1840	shale	3023		
shale	790	lime	1845	shale & lime	3026		
lime	795	slate wh	1855	lime blk	3030		
shale	825	shale	1895	lime sdy	HFW 3037		
lime	855	shale & lime		Total Depth			
shale	865	shells	1980				
lime	875	lime	1990	P.B. 2735			
shale	880	shale	1995				
880=860 SLM		1995=1995 SLM					
lime	865	lime	2100	Form. Tops:			
shale	965	shale blk	2108	KC	1980 SLM		
lime	990	lime & sand	2115	Miss	2730 SLM		
shale	1000	lime gry	2130				
lime	1040	lime	2133				