

K. T. WOODMAN
RES. PHONE 733-0418
OFF. PHONE 265-7650
WICHITA, KANSAS

D. J. IANNITTI
PHONE 792-2921
GREAT BEND, KANSAS

WOODMAN & IANNITTI DRILLING COMPANY
Rotary Drilling Contractors

1022 UNION CENTER
150 N. MAIN
WICHITA, KANSAS 67202

August 29, 1983

Company: Southern States Oil Company
Farm: #8 Stremel
Location: NE SE SW
Section: 19-16S-16W
County: Rush
Contractor: Woodman & Iannitti Drilling Company
Total Depth: 3578'
Comm: 8-17-83
Comp: 8-26-83
Casing: 8-5/8" 24# set @ 288.62' w/175 sx. Common,
3% CC, 2% Gel
5-1/2" 14# set @ 3577' w/150 sx. 60/40 Pozmix,
500 gallons Mud Sweep

Figures Indicate Bottom Formations:

123	Surface Soil, Post Rock & Shale
288	Shale & Sand
784	Shale & Sand
1091	Red Bed
1127	Anhydrite
1270	Shale
1700	Shale & Sand
2049	Shale & Lime
2264	Lime & Shale
2414	Shale & Lime
2578	Shale & Lime
2742	Lime & Shale
2930	Shale & Lime
3045	Shale & Lime
3148	Lime & Shale
3166	Shale & Lime
3200	K.C.
3286	Lime
3310	Shale & Lime
3330	K.C.
3355	Lime
3379	Shale & Lime
3345	K.C.
3481	K.C.
3528	K.C.
3578	K.C.

I certify the above to be a true and correct copy of the drillers log to the best of my knowledge and belief.

WOODMAN & IANNITTI DRILLING COMPANY

K. T. Woodman
K.T. Woodman, Partner

19-16-16W

Geological Survey
BRANCH



WOODMAN-IANNITTI DRILLING CO.

19-16-160

Date 8-25-83

Company Southern States Oil Company

Lease Stremel

Well No. 8

Legal Description NE SE SW

Well Depth 3578'

State Geological Survey
WICHITA BRANCH

SURFACE INFORMATION

Depth Set 288.62' Size and Weight of Casing 8-5/8" x 24#

Number of Sacks 175 Type of Cement Common

Additives in Cement 3%CC, 2% Gel

Cementing Company Sun Oilwell Cementing

IF CASING IS RUN

Depth Set 3577' Size and Weight of Casing 5 1/2" x 14#

Number of Sacks 150 Type of Cement 60/40 Pozmix

Additives in Cement 500 gallons Mud Sweep

Cementing Company Sun Oilwell Cementing

IF WELL IS PLUGGED

Depth of Each Plug and Number of Sacks on Each

Type of Cement

Cement Additives

Cementing Company

