

# K. G. S. LIBRARY

## KANSAS DRILLERS LOG

COMPANY Ram Petroleum Corporation

SEC. 1 T. 16S R. 20W

FARM Watson

NO. 2

LOC. C-NW SE NE

COUNTY Rush

ROTARY TOTAL DEPTH 3,688'

COMM. July 20, 1980

COMP. July 30, 1980

CONTRACTOR H-30, INC. (Rig #2)

ISSUED August 5, 1980

CASING

10 3/4"

8 5/8" Set at 1,293' cemented w/500 sxs cement

5 1/2"

4 1/2" Set at 3,687' cemented w/150 sxs cement

ELEVATION 2,078' K.B.

FIGURES INDICATE BOTTOM OF FORMATIONS

Sand and Shale	275'
Shale	730'
Sand	953'
Shale and Red Bed	1,260'
Shale	1,277'
Anhydrite	1,320'
Shale	2,330'
Lime and Shale	2,540'
Shale and Lime	2,795'
Shale	3,120'
Shale and Lime	3,315'
Lime	3,400'
Lime and Shale	3,465'
Lime	3,686'
Rotary Total Depth	3,688'

I hereby certify the above and foregoing to be a true and correct log of the above described well as shown by the drilling reports.

H-30, INC.

*Dean Britting*  
 \_\_\_\_\_  
 Dean Britting

State of Kansas )  
 ) ss:  
 County of Sedgwick )