


49421

THE PURE OIL CO.
H. D. Stevenson No. 10.

SEC. 5 T. 24 R. 14E
CSL SW NW NE
140°N SL 2731°E WL 1257°S NL
745°W EL

Total Depth. 1739'
Comm. 11-12-37 Comp. 12-8-37
Shot or Treated. 3000 Gals.
Contractor.
Issued. 1-8-38

County. Woodson



CASING:
12 $\frac{1}{2}$ " 15'6"
10 " 884'
65/8" 1709'

Elevation.

Production. 35 Bbls.

Figures Indicate Bottom of Formations.

soil	3	lime	1230
yellow clay & gravel	18	shale	1260
lime	23	sand	1270
shale	45	lime	1280
lime	50	shale	1310
lime	55	lime	1315
shale	65	shale	1708
lime	70	reduced 10" hole to	
shale	80	8" at 1675'	
lime	85	chat	1709
shale	146	lime	1739
lime	155	1 gal. oil- 2 gals.	
shale	210	wtr 1735-1738	
lime	225	SLM at 1739	
shale	250	Total Depth.	
lime	268		
shale	325	1st 24 hrs prod. none before shot.	
sand 2 BW	340	1st 24 hrs prod. 35 bbls. after shot.	
shale	409		
lime	425		
shale	586		
lime	622		
4 BWPH 599-605			
shale	626		
lime	688		
shale	695		
lime HFW 810	852		
shale	857		
lime	872		
shale	875		
red rock	878		
shale	910		
lime	980		
shale	985		
sdv lime	995		
lime	1045		
shale	1165		
lime	1170		
shale	1175		
lime	1195		
shale	1200		
sand	1205		
shale	1214		