

WELL LOG BUREAU—KANSAS GEOLOGICAL SOCIETY
 508 East Murdock, Wichita, Kansas

Company KEWANEE OIL CO.
 Farm-Froelich "F" No. 3

SEC. 34 T. 12 R. 16W
 SE NE NE

930' fr NL, 330' fr EL, NE/4

Total Depth. 3529

Comm. 7-31-54

Comp. 8-16-54

Shot or Treated.

Contractor.

Tested. 10-16-54

County Ellis

KANSAS



Elevation. 2050 CM

CASING:

10 3/4 C.M. 262.27' w/ 130 sx cmt.

7 in. C.M. 3517.30' w/ 100 sx cmt.

2 3/8 EUE Tubing 3527.47' C.M. Figures Indicate Bottom of Formations. 192.73 BW/ 20 2/3 hrs.

shale	150
shale & shells	267
shale	440
sand	480
sand & shale	850
shale & shells	975
red bed	1192
anhydrite	1235
shale & shells	1425
salt & shale	1780
lime & shale	2085
lime	2200
lime & shale	2360
lime	2435
lime & shale	3060
lime	3195
lime & shale	3270
lime	3529
Total Depth	

TOPS: (CM)	Lane-Wells	Sample
Topeka		2954
Heebner	3222	3214
Dodge		3241
Lansing-KC	3266	3263
Arbuckle	3519	3515
Lane Wells TD		3533

Treated w/ 500 gals. Dowell XXF32,
 4000 gals 26° gravity crude & 2500#
 sand