

5-32-4E

Company - TEXAS CO.  
Farm - Schwantes

No. 1

SEC. 5  
NWc SE


T. 32

R. 4 E

Total Depth. 3500'  
Comm. 6-7-44 Comp. 7-4-44  
Shot or Treated.  
Contractor. Earl F. Wakefield  
Issued. 8-5-44 Rotary O-3500

County.

Cowley  
KANSAS



CASING:  
8 5/8" 144' Cem.

Elevation. \_\_\_\_\_

Production. Dry

Figures Indicate Bottom of Formations.

gravel	50	shale	2960
shale	65	sand brkn & shale	2974
lime brkn	100	shale	3068
lime	165	lime Miss.	3179
sand	175	lime wht	3193
lime & shale	218	lime blk	3206
sand	225	lime	3248
shale & lime shells	320	lime blk	3324
shale & shells	380	shale	3332
sand	400	lime wht	3350
shale & shells	420	lime	3360
shale	460	lime brkn & shale	3378
shale & shells	518	shale	3390
red bed	525	lime	3404
lime	580	shale	3486
shale & shells	605	lime Arbuckle	3500
lime	625	Total Depth.	
shale & shells	820		
shale	910	Tops:	
shale & shells	925	Stonaker	2000
shale	1065	K. C.	2422
lime	1080	Miss.	3064
shale & shells	1250	Kind.	3362
lime brkn	1300	Chattanooga	3404
lime	1360	Misener	3480
shale	1450	Arbuckle	3482
lime	1478		
shale & shells	1540	Cored 2942-53, no show of	
lime brkn	1590	oil in any formation	
lime sdy	1645	Ran Schlumberger Survey	
shale & shells	1665	at 3500, no show of oil	
lime	1770	or gas	
lime brkn & shale	1825		
shale & shells	1880		
lime	1968		
lime brkn & sand strks	2001		
sand	2077		
shale	2080		
lime & sand	2115		
shale & shells	2200		
shale sdy	2214		
shale & shells	2256		
shale	2428		
shale & sand	2444		
sand	2455		
lime	2488		
sand	2490		
sand brkn & shale	2534		
lime	2596		
lime hd	2616		
lime	2670		
shale	2686		
lime	2708		
shale	2756		
lime	2780		
lime brkn & shale	2800		
lime brkn	2859		