

WELL LOG BUREAU - KANSAS GEOLOGICAL SOCIETY
508 East Murdock Wichita, Kansas


Company - CITIES SERVICE OIL CO.
Farm - Stokes No. 99

SEC. 33 T. 25 R. 5E
NW NW SE
355' S. 330' E. of Center

Total Depth. 2416
Comm. 11-12-50 Comp. 12-9-50
Shot or Treated.
Contractor. B. & R. Drlg. Inc. & Chet Myers
Issued. 6-23-51

County. Butler

KANSAS



CASING:
8 5/8" 79' cem. w/65 sx
5 1/2" 2404' cem. w/150 sx

Elevation. 1355 R.T.B.
1357 (2nd)
Production. 19 30.198 BW
23/hrs.

Figures Indicate Bottom of Formations.

lime	25
shale	30
shale & shells	40
shale	50
lime	55
shale & shells	70
shale	79
lime & shale	210
lime	375
lime & shale	1743
lime	1905
shale & shells	1980
lime	2235
lime & shale	2300
lime	2373
lime & shale	2390
lime	2416
Total Depth	

Tops:	
Iatan Lime	1567
Base	1630
Lansing Lime	1670
Base	1802
Kansas City Lime	1957
Base	2122
Arbuckle Dol.	2403

Steel Line Measure:
471=471
2350=2363

1568-75 S.S.O.
1603-08 S.S.O.
1694-98 S.S.O.
1707-29 S.O.
1967-89 F.S.O.
1990-2002 S.O.
2015-25 S.S.O.
2057-59 S.O.
2079-2102 S.O.
2403-05 Stain
2405-09 S.S.O.
2409-16 S.O.

Best Pay 2412-16
First Free Oil 2412-14
Fill Up: 205' oil, 120' wtr.
in 12 hrs. at 2416' (Natural)
Acidized with 250 gals. used
51 bbls. load oil.

Note: All measurements taken
from R.T.B.