

WELL LOG BUREAU—KANSAS GEOLOGICAL SOCIETY  
508 East Murdock Wichita, Kansas


15-32-4E

Company. ARMER DRILLING CO., INC.  
Farm. YouB No. 1

SEC. 15 T. 32 R. 4E  
CNW NW

Total Depth. 2330  
Comm. 1-3-51 Comp. 2-21-51  
Shot or Treated.  
Contractor. Capitt Drilling, Inc.  
Issued. 7-28-51

County. Cowley KANSAS



Elevation. 1137 DF  
1139 RB (Und)  
Production. dry

CASING:

10 3/4" 83' Surface pipe  
7" 2315' cemented. w/ 50 sxs.

Figures Indicate Bottom of Formations.

surface clay	25
sand river, gravel	43
lime shells, shale	83
lime, shale	105
red rock	115
lime, shale	165
red rock	180
lime, shale	195
lime unbroken shale	305
red rock	312
lime, shale	335
lime	355
shale, lime	400
shale, shells	810
shale, lime	845
shale, hard lime	862
lime, shale breaks	965
shales, lime	1015
lime, shale	1035
lime	1055
shale, lime	1250
lime, shale (cherty)	1295
lime, shale	1370
lime, shale breaks	1450
lime, shells, shale	1510
lime	1528
shale, lime	1595
lime	1611
shale, shells	1860
shale sandy, lime	1915
shale, lime shells	2040
shale	2263
sand (Layton sand)	2287
sand	2330
Total Depth	

Tops:  
Layton Sand 2263

7" oil string pumped to  
bottom - Picked up 15'  
- cemented at 2315.