

# WELL RECORD

API: 15-205-24,395

Well No. 1-5 Farm Parker-Ames Producer Weger Petroleum Corp.

Location 2160fsl1520fel ne nw se Sec. 10 Twp. 28 Rg. 17E

Elevation \_\_\_\_\_ State Kansas County Wilson

Kind (Oil, Gas, Water, Dry Hole) \_\_\_\_\_ Contractor Fleming Drilling Inc.

Producing formation \_\_\_\_\_ Top \_\_\_\_\_ Bottom \_\_\_\_\_

Shot with \_\_\_\_\_ qts. \_\_\_\_\_ from \_\_\_\_\_ to \_\_\_\_\_

Packer Set at \_\_\_\_\_ Kind \_\_\_\_\_ Size \_\_\_\_\_

Liner \_\_\_\_\_ from \_\_\_\_\_ to \_\_\_\_\_ Perforated from \_\_\_\_\_ to \_\_\_\_\_

## LOG

ick- ess	Strata	Depth	Thick- ness	Strata	Depth
2	top soil	2	117	shale	978
4	lime, brkn.	6	8	shale, sand/lt odor	
4	clay	10			986
10	shale, surface	20	5	sand, shaley/show	991
78	shale	98	4	oil sand	995
32	lime	130		cored:	
98	lime, sandy	228	17	oil sand	1012
8	shale	236	3	oil sand, lt.	1015
82	lime	318		drilled:	
9	shale	323	4	sand, shaley	1019
14	lime	337	21	sand, oil show	1040
15	shale	352	10	sand, shaley	1050
75	lime	427	12	sand, lt.	1062
34	shale	461			
7	shale	528			
18	lime	546			
75	shale	631			
3	lime, 40'	634			
4	shale	638			
29	lime	667			
37	shale	704			
19	lime, 20'	723			
7	shale	730			
6	lime	736			
16	shale	752			
12	sand, shaley	764			
11	sand, shaley/odor	775			
44	shale	819			
1	lime	820			
41	shale	861			

Total Depth 1062'

Open Hole 20' of pipe(7") cemented with 5 sacks cement.

Casing \_\_\_\_\_ at \_\_\_\_\_

Casing \_\_\_\_\_ at \_\_\_\_\_

Casing \_\_\_\_\_ at \_\_\_\_\_

Cement Ran 1061' of 4 1/2" pipe with float-shoe on bottom. Cemented to top.

Tubing \_\_\_\_\_

Rods \_\_\_\_\_

Additional Information

Well was started 5/7/86

Completed 5/12/86

AUG 04 1986

KANSAS GEOLOGICAL SURVEY  
WICHITA BRANCH

AUG 1 1986

Date Completed \_\_\_\_\_

O. K. \_\_\_\_\_

Superintendent \_\_\_\_\_