

API: 15-205-24,400

# WELL RECORD

Well No. 2-5 Farm Parker Ames *Parker Ames* Ames Parker Producer Weger Petroleum Corp.

Location 1520'fsl-1840'fel SE NW SE Sec. 10 Twp. 28 Rg. 17

Elevation \_\_\_\_\_ State Kansas County Wilson

Kind (Oil, Gas, Water, Dry Hole) \_\_\_\_\_ Contractor Fleming Drilling, Inc.

Producing formation \_\_\_\_\_ Top \_\_\_\_\_ Bottom \_\_\_\_\_

Shot with \_\_\_\_\_ qts. \_\_\_\_\_ from \_\_\_\_\_ to \_\_\_\_\_

Packer Set at \_\_\_\_\_ Kind \_\_\_\_\_ Size \_\_\_\_\_

Liner \_\_\_\_\_ from \_\_\_\_\_ to \_\_\_\_\_ Perforated from \_\_\_\_\_ to \_\_\_\_\_

## LOG

Thickness	Strata	Depth	Thickness	Strata	Depth
1	top soil	1	12	shale	
	lime	10	27	shale	970
5	shale and lime	15	13	sand, shale/odor	983
3	lime	18	5	sand shale/show	988
2	shale	20		cored;	
84	shale	104	16	oil sand	1004
9	lime	113	2	oil sand & shale	1006
111	sand	224	2	oil sand	1008
6	shale	230		drilled;	
10	shale, lime	240	8	oil sand, shaley	1016
90	lime	330	32	show-oil sand	1048
15	shale	345			
17	lime	362			
59	lime	421			
5	shale	506			
37	lime	543			
84	shale	627			
4	lime, 40'	631			
4	shale	635			
28	lime	663			
40	shale	702			
20	lime, 20'	722			
6	shale	728			
5	lime, 5'	733			
10	shale	743			
20	shale, sandy/odor	763			
52	shale	815			
1	lime	816			
105	shale	921			
10	shale, sand/odor	931			

Total Depth ~~1048~~ 1048'

Open Hole set 20' of 7" pipe cemented with \_\_\_\_\_

Casing 4 sacks cement. at \_\_\_\_\_

Casing \_\_\_\_\_ at \_\_\_\_\_

Casing \_\_\_\_\_ at \_\_\_\_\_

Cement Ran 1048' of 4 1/2" pipe. Cent# 1015

950' and at jt. no# 15. Float-

Tubing shoe on bottom \_\_\_\_\_

Rods \_\_\_\_\_

Additional Information

Started 6-4-86

Completed 6/11/86

AUG 11 1986

Date Completed \_\_\_\_\_

O. K.

Superintendent