

UNION NATIONAL BANK BLDG WICHITA, KANSAS

Location. NE SW SW SE CORRECTED LOG. Sec. 22 T. 32 R.4E.

Lot 10 Blk 14 College Hill Addition.

Casing Record. 560 fr SL. 450' fr WL. SE $\frac{1}{4}$ County. Cowley.

10" 1778 Farm. Fee Lots No. 1


20" 8" 2201 Company. Roth and Faurot Oil and Gas Co.

15 $\frac{1}{8}$ " 433 65/8" Contr.

12 $\frac{1}{2}$ " 1020 53/16" Comm. 3-29-32 Comp. 5-10-32

Total Depth. 2420 Shot Quarts Between.

Correspondence Regarding This Well Should Be Referred To.



Elevation.

Figures Indicate Bottom of Formations.

Initial Production.

Date Issued. 11-19-32

Swab 85 bbls in 24 hours.

Formation	Depth	Formation	Depth.
soil	5	shale blue	972
lime	10	lime	980
enough water to drill with 120'		shale	1000
shale	20	lime	1010
lime	30	shale	1020
shale 3 BWPBR	40	lime	1028
lime	75	$\frac{1}{2}$ BWPBR 1125	
shale	105	shale	1068
sdv lime	120	lime	1076
red rock	125	shale grey	1110
lime	130	lime	1175
shale	150	shale	1240
red rock	155	lime	1285
lime	160	lime shells	1305
shale	180	lime	1345
red rock	185	bad hole 1415-1425	
lime	195	shale grey	1350
shale	225	shale red or brown	1355
lime	245	$\frac{1}{2}$ BWPBR 1475-1483	
red rock	250	lime shells	1358
red rock	270	shale red	1368
shale	275	lime	1430
lime	280	shale light	1475
shale	285	sand	1483
lime	310	sdv shale grey	1490
shale	320	lime	1570
lime	385	shale light	1625
red rock	400	limestone	1640
shale	410	shale dark	1645
red rock	428	shale light	1650
lime	433	lime	1652
shale	435	shale light red	1658
lime	445	lime	1680
shale	448	reamed from 1697 to 1760	
lime	480	shale brown	1690
shale	490	lime	1712
lime	525	shale white	1735
slate blue	527	lime	1750
lime	555	shale	1755
shale	560	sand bottom hard	1770
lime	575	5 BWPBR 1790	
shale	580	shale grey	1895
lime	590	lime	1902
shale	594	shale	1925
lime	610	water sand	1980
shale light	690	sdv shale	1995
lime shells	710	sand	2040
shale light	735	shale blue	2057
lime $\frac{1}{2}$ BWPBR 765-70	738	sdv lime	2065
shale grey	754	sdv shale grey	2115
lime	756	lime hard	2135
shale light	765	sdv lime	2173
sand	770	shale	2176
shale grey	820	lime shells	2187
lime	825	shale grey	2355
shale	850	sand	2420
lime	860	TD.	
shale grey	912	Show oil and gas 2380 inc. 2385.	
lime shells	914	1400' oil at 2395. 1800' oil 2405.	
shale dark	918	flow and swabbed 85 bbls in 24 hours.	
lime top hard	940		