


Plotted on
3-10-20E

APPERSON & FUNDT
 Stoenstry No. 1.

SEC. 3 T. 10 R. 20E.
 SW SE NW
 990' NL 326' WL SE $\frac{1}{4}$ NW $\frac{1}{4}$

Total Depth. 1474
 Comn. 7-16-41 Comp. 7-25-41
 Shot or Treated.
 Contractor. Barker
 Issued. 8-9-41

County Leavenworth.



CASING.

8 $\frac{1}{2}$ " 880'
 65/8" 1434'

Elevation. 1071 (Ohio)

Production. Oil 40 BPD

Figures Indicate Bottom of Formations.

shale	7-	38	shale	879	shalo	1474
lime		41	lime	880	Total Depth.	
shale		70	lime	885		
shale		80	shale	895		
lime		102	shale light	920	Underreamed pipe to	
shale		115	shale dark	925	oil sand 1434	
lime		128	lime	928		
shale light		165	shale dark	930		
shale		257	shale light	935		
lime		260 <i>3 Haskell</i>	shale and lime			
shale		265	shells	945		
shale	2 BW	295	shale light	950		
sand & water		305	lime	955		
shale		355 <i>8 Tong 55</i>	shale dark	965		
shale light		401	lime	970		
lime		409 <i>8 429 13 state</i>	shale	973		
shale		413 <i>4</i>	lime	977		
lime		420 <i>7</i>	shale dark	985		
lime		427 <i>7</i>	shale	1050		
shale dark		431 <i>4 Eudora</i>	shale light	1062		
lime		438	lime	1065		
shale		450	shale light	1092		
lime		470	lime	1095		
shale		500	shale light	1110		
lime		510	shale light	1135		
shale		520	4 BW 1140-50			
shale light		540	sand	1150		
lime		555	shale	1195		
shale		570	lime	1250 <i>1200</i>		
lime		575	shale blk	1220		
lime		582	sand	1235		
shale		590	?	1240		
lime		595	shale	1270		
shale		610	shale	1275		
lime		625	sand	1280		
shale dark		635	shale light	1285		
lime		643	shale dark	1310		
shale dark		646	shale	1320		
lime		680	shale	1340		
shale blk		685	shale	1355		
lime		695	shale blk	1370		
lime		715 20 BW	sand	1378		
lime		738	shale dark	1380		
shale dark		740	shale	1383		
shale light		745	sand	1390		
shale light 16 BW		765	shale blk	1412		
sand water 4 BW		785	shale white	1414		
shale		820	shale blk	1428		
shale light		848	sand Oil	1434 ✓		
lime shells		855	oil sand	1450		
lime shells		857	sand and shalo	1467		