COPY

FORM 55-38 BKS-8-23-CROMAC

OKLAHOMA NATURAL GAS CORPORATION

RECORD OF WELL. Serial No. 1582 /52 Oil, Gas or Dry? Oil

Central Field Kansas Okla., 192

Located on lands of Carrie E. Stewart Farm No. 8 Section 18 Township 28 Range 18E

Canville Township Neosho County. Location of Well Feet N-S

of and feet, E-W of Elevation Fee

Commenced , 19 Completed , 192

Drilling Contractor Rock Pressure lbs. Shut-in Hour

Test inches (Mercury / Water) inch (Orifice / Tube) Volume Thru Casing Ft. in 24 Hours

Test inches (Mercury / Water) inch (Orifice / Tube) Volume Thru Casing Ft. in 24 Hours

(NOTE—The above tests to be taken after the well is packed or capped.)

Shot Quarts Length of Shell Depth Top of Shot feet. Initial Production

Shot Quarts Length of Shell Depth Top of Shot feet. Bbls. Oi

Drive Pipe or Conductor—Kind		Size	10"	No. of Ft.	9	Inches	
Casing, No. Joints	Weight	"	6¼"	"	646	"	
Casing, " "	"	"		"		"	
Casing, " "	"	"		"		"	
Tubing, " "	"	"	2"	"	776	"	
Tubing, " "	"	"		"		"	
Tubing, " "	"	"		"		"	
Anchor, " "	"	"		"		"	
Rods or Wire Line	"	"		"		"	

Packer—Style Make Size Set at

Packer—Style Make Size Set at

Drive Shoe R. & L. Nipple set at Size Check Coupling set at

LOCATE WELL CORRECTLY

Depth of Well Feet @ $ Was Gas Used for Fuel?

Depth of Water Well Feet @ $ By Meter or Day?

Reamed Feet @ $ Meter, Kind? Number

Last State

Condition of Gas—Wet or Dry? State When Set

Type of Drilling Rig? Cubic Feet Passed

Total Cubic Feet Passed @ lbs. Pressure

Formation Record	Top	Bottom	Depth Where Flow Occurs	*Quantity Gas, Oil or Water	Formation Record	Top	Bottom	Depth Where Flow Occurs	*Quantity Gas, Oil or Water
776' of 5/8" Iron Sucker Rods									
2' of 2" Perforated Pipe									
1 2" x 6' Working Barrel									
1 1¼" Working Valve									
1 1¼" Standing Valve									
1 6½" x 2" x 2" Casinghead									
1 2" x 10" Nipple									
1 2" Mallable Tee									
1 2" x 4" Nipple									
1 2" C I Plug									
1 2" x 1-1/8" N.S.Co. Flange Stuffing Box, Female									
1 1-1/8" x 11' Steel Polish Rod									
2 1-1/8" Steel Polish Rod Clamps									
1 W.C.Norris Pumping Jack Complete									
2 2" x 3½ Pump Jack Anchors					BOTTOM OF HOLE	****			

NOTE: "If increase occurs in any sand report name of sand and show increased flow in "Quantity" column, gas in cubic ft. (or psig reading) oil and water in gallons. This test should be taken soon after gas, oil or water appears. If gas blows out, so state in remarks.

REMARKS:

FOREMAN SUPERINTENDENT

White to Engineer, Yellow to Accounting Dept., Blue to Land Dept., Green to Superintendent, Pink retained by Foreman.)