

36-10-23E

BLAIR & SMITH  
Snyder No. 1.

SEC. 36 T. 10 R. 23E

NE SW SW NE


2100' S 2200' W EL

2090

2190

County. Wyandotte

APR 9 1938

Total Depth. 815'  
Comm. 5-2-31 Comp. 5-20-31  
Shot or Treated.  
Contractor.  
Issued. 4-9-38

CASING:

65/8" 533'

Elevation. 925

Production. Dry

Figures Indicate Bottom of Formations.

soil	9	lime	495
sand	19	lime & sand	505
shale	35	shale	514
lime	47	lime	518
shale	49	shale	521
lime	51	sand wtr <i>Perru</i>	527 <sup>4</sup>
shale	77	shale	529
lime	82	lime <i>Lax</i>	532
shale	88	shale	542
lime brown	95	lime	543
shale	105	shale	548
lime	125	lime	560
lime brown	135	shale	568
shale	157	lime sdy <i>Ft. Scott</i>	570
lime	163	shale	588
lime brown	169	shale sdy	612
shale	183	shale grey	623
lime	190	shale sdy	625
shale	194	shale grey	665
lime	196	shale drk	670 gas bubbles
shale	205	lime	674
lime	208	shale blue	684
shale	223	shale sdy	740
lime	228	shale blue	745
shale	235	shale	755
lime	265	lime shells	757
shale	270	shale grey	759
lime	291	red bed	760
shale	295	shale grey	770
lime	298	sdv lime shells	790
shale	300	shale blue	795
lime <i>Hertha</i>	310	shale sdy	798
shale	325	sand	810
sand oil show	335	shale sdy	815
shale	427	Total Depth.	
red bed	435		
sand	438		
shale	448		
lime	452		
sand gas bubbles	458		
shale	465		
shale & sand (oil show)	470		
lime	474		
shale	480		
lime	482		
shale	489		

*no square**BV 12*